

# WHICH SERIES IS RIGHT FOR YOU?



**COOPER  
TIRES®**

**COMMERCIAL SERIES**  
**PRO WORK SEVERE**



**COMMERCIAL SERIES**  
**PRO WORK SEVERE**

## **COOPER BRAND LINE OF COMMERCIAL TIRES**

At Cooper Tires, we understand the importance of tires and the crucial role they play for your business and for your safety. As an American company since 1914, our focus is on making quality tires that perform. Our line of commercial truck tires has been designed and engineered to deliver the quality and value you expect from Cooper® by focusing on total cost of ownership.





# INDEX

	PAGE
Cooper Tire Commercial Tires Intro . . .	1
Verifications and Classifications . . . . .	3
Features . . . . .	4

## **PRO SERIES**

### **LONG HAUL APPLICATION**

	PAGE
Pro Series LHS . . . . .	5
Pro Series LHD . . . . .	5
Pro Series LHT . . . . .	5

## **WORK SERIES**

### **REGIONAL HAUL APPLICATION**

	PAGE
Work Series RHA . . . . .	7
Work Series ASA . . . . .	7
Work Series AWD . . . . .	7
Work Series RHD . . . . .	9
Work Series ASD . . . . .	9
Work Series RHT . . . . .	9

## **SEVERE SERIES**

### **MIXED SERVICE APPLICATION**

	PAGE
Severe Series MSA . . . . .	11
Severe Series WBA . . . . .	11
Severe Series MSD . . . . .	11

### **ADDITIONAL INFORMATION**

	PAGE
Cooper Tire Fleet Solutions . . . . .	13
Premium Warranty . . . . .	14
Competitive Comparison . . . . .	14

# VERIFICATIONS AND CLASSIFICATIONS



At Cooper Tire we know it's all about total cost of ownership for your tire program. Value also means high utilization of your assets, including a very effective tire program. The PRO and WORK Series are competitively priced and provide a superior balance of fuel efficiency and tread wear, all built around a durable casing designed for retreadability. **If your goal is low cost of ownership, the PRO and WORK Series tires from Cooper® are your answers.**



Fuel saving technologies are continuously evolving, and at Cooper Tire we understand its importance to you and your fleet. Through a combination of innovative compounding, tire construction and tread design, our Energy Conservation Optimization (ECO) tires offer ultra-low rolling resistance which provides increased fuel economy. ECO tires exceed the SmartWay standard requirements and deliver superior performance and savings.



In today's e-commerce world, we recognize that uptime is of paramount importance. The demands on your fleets' tires are ever increasing, which is why we have developed our durable Final Mile lineup of tires. No matter the freight, our Final Mile lineup is engineered to withstand the rigors associated with urban delivery while also delivering the all season traction and handling your fleet requires.



U.S. EPA'S SmartWay Transport partnership is a market-driven partnership aimed at helping businesses move goods in the cleanest most efficient way possible. Since 2004, SmartWay partners have eliminated 51.6 million metric tons of CO<sub>2</sub>, resulting in savings of 120.7 million barrels of oil and \$16.8 billion in fuel costs. Cooper® Tires offers a full range of SmartWay verified tires. These tires meet the program's stringent low-rolling resistance criteria – helping to reduce fuel consumption, ultimately cutting utility costs and benefiting the environment.

Learn more about SmartWay by visiting [www.epa.gov/smartway](http://www.epa.gov/smartway).

# FEATURES



**COMMERCIAL SERIES**  
**PRO WORK SEVERE**



Frequent starts, tight turns, stops and potential curb impacts make tire needs unique and challenging. Scrub Guard technology is our answer and features proprietary compounds and proven tread designs to minimize the impact of these severe conditions.



If you drive in off-road conditions or have frequent tight turns with curbs abundant on your routes, Chip Guard technology is the protection you are looking for. Chip Guard features proprietary compounds and purposeful tread patterns to minimize the impact of these severe conditions.



# PRO SERIES LONG HAUL APPLICATION

The Cooper® PRO Series™ is an on-highway, long-haul line-up featuring proprietary technology and is SmartWay verified. The Cooper PRO Series delivers savings to your fleet through competitive acquisition cost, innovative rubber compounds which balance rolling

resistance and long mileage, and a highly engineered casing designed for multiple retreads. Combined with the low cost of ownership and a superior warranty, the PRO Series™ is designed to meet your bottom line expectations. Run with the PROs, with the Cooper® PRO Series™.

## PRO SERIES LHS™



The Cooper® PRO Series™ LHS is a fuel efficient, 18/32nds long-haul steer tire that combines an innovative compound with premium dimensions, a wide footprint, and a decoupling groove to help deliver long, even wear and savings to your tire program's bottom line. This Low Cost of Ownership™ tire is all about savings including a casing designed and warranted for multiple retreads and a full replacement value warranty for the first 50% of treadwear.



## PRO SERIES LHD™



The Cooper® PRO Series™ LHD is a fuel efficient, long-haul drive tire with premium dimensions and a deep 30/32nds tread depth that delivers the long tread life you expect from your closed shoulder drive tires. This Low Cost of Ownership™ tire is all about savings including a casing designed and warranted for multiple retreads and a full replacement value warranty for the first 50% of treadwear.




## PRO SERIES LHT™



The Cooper® PRO Series™ LHT is Cooper's premium fuel efficient trailer tire, designed for long haul applications. At 12/32nds deep, the SmartWay verified LHT utilizes an advanced compound as well as a highly engineered casing to provide the fuel efficiency and durability that your fleet requires. This Low Cost of Ownership™ tire is all about savings including a casing designed and warranted for multiple retreads and a full replacement value warranty for the first 50% of treadwear.




**RUN WITH THE PROS**



**PRO SERIES LHS™**

**SMARTWAY**


Material #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000035310	295/75R22.5 G/14 144/141L 75 mph 120 km/h	(9.00) 8.25-9.00	110 760	6,175 2,800	5,675 2,575	40.20 1,021	11.3 287	18.78 477	13.2 335	516 320	18.0 14.3	26 660	9.3 235	113 51.7	029142930303
90000035311	295/75R22.5 H/16 149/146L 75 mph 120 km/h	(9.00) 8.25-9.00	125 850	7,160 3,250	6,610 3,000	40.20 1,021	11.3 287	18.78 477	13.2 335	516 320	18.0 14.3	26 660	9.3 235	115 52.5	029142930310
90000035278	11R22.5 G/14 144/142L 75 mph 120 km/h	(8.25) 7.50-8.25	105 720	6,175 2,800	5,840 2,650	41.69 1,059	11.1 281	19.41 493	12.5 318	497 309	18.0 14.3	26 660	9.3 235	117 53.2	029142929888
90000035279	11R22.5 H/16 146/143L 75 mph 120 km/h	(8.25) 7.50-8.25	120 830	6,610 3,000	6,005 2,725	41.73 1,060	11.1 283	19.41 493	12.5 318	497 309	18.0 14.3	26 660	9.3 235	118 54.0	029142929895
90000035314	285/75R24.5 H/16 147/144L 75 mph 120 km/h	(8.25) 7.50-9.00	120 830	6,780 3,075	6,175 2,800	41.38 1,051	10.9 278	19.41 493	12.5 318	501 311	18.0 14.3	26 660	9.3 235	119 54.4	029142930341
90000035312	11R24.5 G/14 146/143L 75 mph 120 km/h	(8.25) 7.50-8.25	105 720	6,610 3,000	6,005 2,725	43.70 1,110	11.1 281	20.39 518	12.5 318	474 295	18.0 14.3	26 660	9.3 235	125 57.5	029142930327
90000035313	11R24.5 H/16 149/146L 75 mph 120 km/h	(8.25) 7.50-8.25	120 830	7,160 3,250	6,610 3,000	43.74 1,111	11.0 280	20.43 519	12.5 318	474 295	18.0 14.3	26 660	9.3 235	127 58.1	029142930334



**PRO SERIES LHD™**

**M+S SMARTWAY**

Material #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000033215	295/75R22.5 G/14 144/141L 75 mph 120 km/h	(9.00) 8.25-9.00	110 760	6,175 2,800	5,675 2,575	40.94 1,040	11.4 289	19.09 485	13.2 335	506 315	30.0 23.6	28 711	9.6 244	129 58.8	029142911265
90000033210	11R22.5 G/14 144/142L 75 mph 120 km/h	(8.25) 7.50-8.25	105 720	6,175 2,800	5,840 2,650	42.13 1,070	11.5 292	19.61 498	12.5 318	492 306	30.0 23.6	26 660	9.7 247	133 60.8	029142911210
90000033211	11R22.5 H/16 146/143L 75 mph 120 km/h	(8.25) 7.50-8.25	120 830	6,610 3,000	6,005 2,725	42.17 1,071	11.5 293	19.61 498	12.5 318	492 306	30.0 23.6	26 660	9.7 247	135 61.6	029142911227
90000033214	285/75R24.5 G/14 144/141L 75 mph 120 km/h	(8.25) 7.50-9.00	110 760	6,175 2,800	5,675 2,575	42.20 1,072	10.7 273	19.76 502	12.5 318	491 305	30.0 23.6	28 711	9.5 241	135 61.4	029142911258
90000033213	11R24.5 G/14 146/143L 75 mph 120 km/h	(8.25) 7.50-8.25	105 720	6,610 3,000	6,005 2,725	44.13 1,121	11.3 287	20.59 523	12.5 318	470 292	30.0 23.6	26 660	9.7 247	143 65.1	029142911241
90000033212	11R24.5 H/16 149/146L 75 mph 120 km/h	(8.25) 7.50-8.25	120 830	7,160 3,250	6,610 3,000	44.13 1,121	11.4 289	20.59 523	12.5 318	470 292	30.0 23.6	26 660	9.7 247	145 66.0	029142911234



**PRO SERIES LHT™**

**SMARTWAY**

Material #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000035155	295/75R22.5 G/14 144/141L 75 mph 120 km/h	(9.00) 8.25-9.00	110 760	6,175 2,800	5,675 2,575	40.20 1,021	11.3 287	18.54 471	13.2 335	516 320	12.0 9.5	26 660	8.7 222	101 46.1	029142928485
90000035156	11R22.5 G/14 144/142L 75 mph 120 km/h	(8.25) 7.50-8.25	105 720	6,175 2,800	5,840 2,650	41.42 1,052	11.1 283	19.29 490	12.5 318	501 311	12.0 9.5	24 610	8.5 216	108 49.2	029142928492
90000035158	285/75R24.5 G/14 144/141L 75 mph 120 km/h	(8.25) 7.50-9.00	110 760	6,175 2,800	5,675 2,575	41.02 1,042	10.9 276	19.29 490	12.5 318	505 314	12.0 9.5	26 660	8.7 222	110 50.0	029142929314
90000035157	11R24.5 G/14 146/143L 75 mph 120 km/h	(8.25) 7.50-8.25	105 720	6,610 3,000	6,005 2,725	43.39 1,102	11.1 281	20.28 515	12.5 318	478 297	12.0 9.5	24 610	8.5 216	116 52.9	029142929307

# WORK SERIES REGIONAL HAUL APPLICATION

The Cooper® WORK Series™ is an on/off-highway, regional-haul line-up featuring proprietary technology and SmartWay verified tires in steer and drive positions. The WORK Series™ delivers the right mix of efficiency and durability for demanding regional-haul applications. Your fleet has many starts, turns and stops. This application is where

the WORK Series™ shines. With a no-nonsense 50% treadwear full replacement value warranty, the WORK Series™ is all business, providing a low cost of ownership for your bottom line. Get to work, with the WORK Series™ from Cooper®.

## WORK SERIES RHA™



The Cooper® WORK Series™ RHA gives your regional fleet a premium 22.5/32nds deep, four rib tread design all position tire that provides you the wide footprint needed to maximize traction. The tapered grooves and stone ejectors are designed to resist stone drilling - a casing's worst enemy. The sidewall features curb guard protection for those tight turns in town. This Low Cost of Ownership™ tire is all about savings including a casing designed and warranted for multiple retreads and a full replacement value warranty for the first 50% of treadwear.



## WORK SERIES ASA™



The Cooper® WORK Series™ ASA provides your fleet with a 17/32nds all position tire engineered for regional and pick up and delivery applications. Optimized for final mile delivery, the scrub resistant compound, all steel construction, curb bar, and stone ejectors combine to resist the hazards associated with urban applications. This Low Cost of Ownership™ tire is all about savings including a casing designed and warranted for multiple retreads and a full replacement value warranty for the first 50% of treadwear.



## WORK SERIES AWD™




The Cooper® WORK Series™ AWD provides your fleet with an open shoulder, 26/32nds, highly siped drive tire that is optimized for superior performance in all weather conditions. A wide footprint and deep tread provide the long, even wear that you expect from a premium drive tire, while full depth sipes, shoulder notches, and our Snow Groove Technology™ provide enhanced traction in a multitude of applications and weather conditions. This Low Cost of Ownership™ tire is all about savings including a casing designed and warranted for multiple retreads and a full replacement value warranty for the first 50% of treadwear.






**GET TO WORK**



**WORK SERIES RHA™**

**SMARTWAY**


Material #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000036128	255/70R22.5 H/16 140/137L 75 mph 120 km/h	(7.50) 6.75-8.25	120 830	5,510 2,500	5,070 2,300	36.85 936	10.157 258	17.17 436	11.3 287	563 350	18.0 14.3	28 711	8.2 209	91 41.1	029142935476
90000033195	295/75R22.5 G/14 144/141L 75 mph 120 km/h	(9.00) 8.25-9.00	110 760	6,175 2,800	5,675 2,575	40.39 1,026	11.1 283	18.86 479	13.2 335	513 319	22.5 18.0	30 762	8.8 225	112 51.2	029142910824
90000033199	295/75R22.5 H/16 149/146L 75 mph 120 km/h	(9.00) 8.25-9.00	110 760	6,175 2,800	5,675 2,575	40.20 1,021	11.3 287	18.86 479	13.2 335	516 320	22.5 18.0	26 762	8.8 225	114 52.0	029142910862
90000033194	11R22.5 G/14 144/142L 75 mph 120 km/h	(8.25) 7.50-8.25	110 760	6,175 2,800	5,675 2,575	40.20 1,021	11.3 287	19.41 493	13.2 335	516 320	22.5 18.0	26 660	8.8 225	117 53.6	029142910817
90000033193	11R22.5 H/16 146/143L 75 mph 120 km/h	(8.25) 7.50-8.25	120 830	6,610 3,000	6,005 2,725	41.69 1,059	11.3 286	19.41 493	12.5 318	497 309	22.5 18.0	26 660	8.8 225	121 55.4	029142910800
90000033198	285/75R24.5 G/14 144/141L 75 mph 120 km/h	(8.25) 7.50-9.00	110 760	6,175 2,800	5,675 2,575	41.69 1,059	10.8 274	19.57 497	12.5 318	497 309	22.5 18.0	30 762	8.8 225	118 53.6	029142910855
90000033197	11R24.5 G/14 146/143L 75 mph 120 km/h	(8.25) 7.50-8.25	105 720	6,610 3,000	6,005 2,725	43.58 1,107	11.1 281	20.35 517	12.5 318	476 296	22.5 18.0	26 660	8.8 225	128 58.4	029142910848
90000033196	11R24.5 H/16 149/146L 75 mph 120 km/h	(8.25) 7.50-8.25	120 830	7,160 3,250	6,610 3,000	43.58 1,107	11.1 281	20.35 517	12.5 318	476 296	22.5 18.0	26 660	8.8 225	128 58.4	029142910831



**WORK SERIES ASA™**

*New product availability - June 2020.*

Material #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000038409	225/70R19.5 G/14 128/126N 87 mph 140 km/h	(6.75) 6.00-6.75	110 760	3,970 1,800	3,750 1,700	32.17 817	9.0 229	14.96 380	10.0 254	645 401	17.0 13.4	28 711	7.6 193	66 30.1	029142951469
90000038480	245/70R19.5 H/16 136/134M 81 mph 130 km/h	(7.50) 6.75-7.50	120 825	4,940 2,240	4,675 2,120	33.19 843	9.9 251	15.35 390	11.0 279	625 388	17.0 13.4	26 660	8.4 213	73 32.9	029142951476



**WORK SERIES AWD™**

**M+S 3-PEAK MOUNTAIN SNOWFLAKE**

*New product availability - June 2020.*

Material #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000038002	295/75R22.5 G/14 144/141L 75 mph 120 km/h	(9.00) 8.25-9.00	110 760	6,175 2,800	5,675 2,575	40.75 1,035	11.3 287	18.98 482.00	13.2 335	509 316	26.0 20.8	28 711	9.8 248.0	121 55	029142949725
90000036546	11R22.5 H/16 146/143L 75 mph 120 km/h	(8.25) 7.50-8.25	120 830	6,610 3,000	6,005 2,725	41.93 1,065	11.2 285	19.49 495	12.5 318	494 307	26.0 20.8	28 711	9.8 248	128 57.9	029142939016
90000036547	11R24.5 H/16 149/146L 75 mph 120 km/h	(8.25) 7.50-8.25	120 830	7,160 3,250	6,610 3,000	43.94 1,116	11.2 285	20.51 521	12.5 318	472 293	26.0 20.8	28 711	9.8 248	138 62.4	029142939023

# WORK SERIES REGIONAL HAUL APPLICATION

The Cooper® WORK Series™ is an on/off-highway, regional-haul line-up featuring proprietary technology and SmartWay verified tires in steer and drive positions. The WORK Series™ delivers the right mix of efficiency and durability for demanding regional-haul applications. Your fleet has many starts, turns and stops. This application is where

the WORK Series™ shines. With a no-nonsense 50% treadwear full replacement value warranty, the WORK Series™ is all business, providing a low cost of ownership for your bottom line. Get to work, with the WORK Series™ from Cooper®.

## WORK SERIES RHD™



The Cooper® WORK Series™ RHD provides your regional fleet a premium 26/32nds deep open shoulder drive tread design to give you the footprint needed to maximize traction. The aggressive tread pattern balances fuel efficiency and mileage while also keeping cut and chip resistance in mind. The sidewall features curb guard protection for those tight turns in town. This Low Cost of Ownership™ tire is all about savings including a casing designed and warranted for multiple retreads and a full replacement value warranty for the first 50% of treadwear.



## WORK SERIES ASD™



The Cooper® WORK Series™ ASD is an 18/32nds open shoulder drive tire designed for regional and pick up and delivery applications. All steel construction and scrub resistant compounding provide the durability your fleet requires for a multitude of applications including final mile delivery. With Three Peak Mountain Snowflake certification the Cooper ASD provides the traction required for all weather conditions. This Low Cost of Ownership™ tire is all about savings including a casing designed and warranted for multiple retreads and a full replacement value warranty for the first 50% of treadwear.




## WORK SERIES RHT™



The Cooper® WORK Series™ RHT provides your fleet a premium high scrub and cut and chip resistant trailer tire. With tread depths ranging from 16/32nds to 18/32nds, the WORK Series™ RHT utilizes tread design and compounding to create one tough tire. This tire is built to take on severe turning on both tandem and spread axle trailers. This Low Cost of Ownership™ tire is all about savings including a casing designed and warranted for multiple retreads and a full replacement value warranty for the first 50% of treadwear.




**GET TO WORK**



**WORK SERIES RHD™**

**M+S \*SMARTWAY**

Material #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
* 90000033424	295/75R22.5 G/14 144/141L 75 mph 120 km/h	(9.00) 8.25-9.00	110 760	6,175 2,800	5,675 2,575	40.75 1,035	11.1 281	19.02 483	13.2 335	509 316	26.0 20.7	28 711	9.0 228	116 52.8	029142911296
* 90000033423	11R22.5 G/14 144/142L 75 mph 120 km/h	(8.25) 7.50-8.25	105 720	6,175 2,800	5,840 2,650	41.93 1,065	11.2 284	19.49 495	12.5 318	494 307	26.0 20.7	26 660	8.5 218	118 54.0	029142911289
90000033425	11R22.5 H/16 146/143L 75 mph 120 km/h	(8.25) 7.50-8.25	120 830	6,610 3,000	6,005 2,725	41.97 1,066	11.3 288	19.53 496	12.5 318	494 307	26.0 20.7	26 660	8.5 218	120 54.9	029142912002
* 90000033428	285/75R24.5 G/14 144/141L 75 mph 120 km/h	(8.25) 7.50-9.00	110 760	6,175 2,800	5,675 2,575	41.97 1,066	10.8 274	19.69 500	12.5 318	494 307	26.0 20.7	28 711	9.0 228	121 55.3	029142912033
* 90000033426	11R24.5 G/14 146/143L 75 mph 120 km/h	(8.25) 7.50-8.25	105 720	6,610 3,000	6,005 2,725	43.90 1,115	11.0 280	20.51 521	12.5 318	472 293	26.0 20.7	26 660	8.5 218	128 58.3	029142912019
90000033427	11R24.5 H/16 149/146L 75 mph 120 km/h	(8.25) 7.50-8.25	120 830	7,160 3,250	6,610 3,000	43.94 1,116	11.1 281	20.51 521	12.5 318	472 293	26.0 20.7	26 660	8.5 218	130 59.3	029142912026




**WORK SERIES ASD™**

**M+S 3-PEAK MOUNTAIN SNOWFLAKE**

*New product availability - June 2020.*

Material #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000038445	225/70R19.5 G/14 128/126N 87 mph 140 km/h	(6.75) 6.00-6.75	110 760	3,970 1,800	3,750 1,700	32.24 819	9.1 230	15.00 381	10 254	644 400	18.0 14.3	18 457	7.2 184	64 29.1	029142950981
90000038446	245/70R19.5 H/16 136/134M 81 mph 130 km/h	(7.50) 6.75-7.50	120 825	4,940 2,240	4,675 2,120	33.31 846	9.8 250	15.43 392	10.98 279	622 387	19.0 15.2	22 559	8.0 203	72 32.6	029142950998



**WORK SERIES RHT™**

*+ New sizes availability - Q4 2020.*

Material #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
+ 90000038702	215/75R17.5 H/16 135/133L 75 mph 120 km/h	(6.00) 6.00-6.75	125 850	4,805 2,180	4,540 2,060	30.51 775	8.5 217	14.331 364	9.4 239	680 422	16.0 12.6	18 457	7.126 181	60 27.1	029142952473
+ 90000038703	245/70R17.5 J/18 143/141K 68 mph 110 km/h	(7.50) 6.75-7.50	125 875	6,005 2,725	5,675 2,575	31.38 797	9.6 243	14.488 368	11.0 279	661 411	16.0 12.6	22 559	8.5039 216	69 31.4	029142952480
90000033109	255/70R22.5 H/16 140/137L 75 mph 120 km/h	(7.50) 6.75-8.25	120 830	5,510 2,500	5,070 2,300	36.69 932	10.3 262	17.09 434	11.3 287	565 351	16.0 12.5	28 711	8.2 209	89 40.7	029142910596
90000033170	275/70R22.5 J/18 148/145L 75 mph 120 km/h	(8.25) 7.50-8.25	130 900	6,175 3,150	5,675 2,900	38.07 967	11.0 279	17.68 449	12.24 311	545 338	18.0 14.5	28 711	9.0 229	105 47.8	029142910701
90000033172	295/75R22.5 G/14 144/141L 75 mph 120 km/h	(9.00) 8.25-9.00	110 760	6,175 2,800	5,675 2,575	39.92 1,014	11.1 281	18.66 474	13.2 335	519 323	16.0 12.7	28 711	8.5 216	106 48.2	029142910725
90000033171	11R22.5 G/14 144/142L 75 mph 120 km/h	(8.25) 7.50-8.25	105 720	6,175 2,800	5,840 2,650	41.22 1,047	11.3 287	19.21 488	12.5 318	503 313	16.0 12.7	24 610	8.5 216	110 50.3	029142910718
90000036162	11R24.5 G/14 146/143L 75 mph 120 km/h	(8.25) 7.50-8.25	105 720	6,610 3,000	6,005 2,725	43.31 1,100	11.1 282	20.24 514	12.5 318	479 297	16.0 12.7	24 610	8.5 216	121 55.4	029142935704

# SEVERE SERIES MIXED SERVICE APPLICATION

The Cooper® SEVERE Series™ is a mixed service line-up designed for extreme applications. Whether you run dump trucks, cement mixers or waste haulers, the heavy duty construction and innovative tread designs and compounds deliver the performance expected in these extreme conditions. With proprietary compounds that promote

chip, cut and scrub resistance, the SEVERE Series™ can help you tame the toughest conditions. Along with a highly engineered casing designed for multiple retreads, the SEVERE Series™ is your confident, go to solution. For the most severe, choose the SEVERE Series™ from Cooper®.

## SEVERE SERIES MSA™



The Cooper® SEVERE Series™ MSA provides your fleet a premium 24/32nds high scrub and cut and chip resistant all purpose mixed service tire. Tread design and compounding make the Cooper® SEVERE Series™ MSA one tough tire. This tire is built to take on severe turning, impacts and off-road driving conditions. The tough, full width, four belt construction ensures this casing will provide multiple retreads.



## SEVERE SERIES WBA™



The Cooper® SEVERE Series™ WBA is a robust 23/32nds wide base, all position tire, engineered to keep your fleet up and running in the most severe mixed service applications. Notched circumferential grooves provide off road traction while stone ejector ledges coupled with a heavy duty casing ensure retreadability.



## SEVERE SERIES MSD™



The Cooper® SEVERE Series™ MSD is a deep 32/32nds mixed service drive tire designed to handle the toughest off-road conditions, while delivering the long even wear your fleet requires on road. Triangular tie-bars in the outside shoulder help to promote traction throughout the life of the tire, while also mitigating heel-toe wear. Designed to reduce your tire program's total cost of ownership, the highly engineered, durable casing includes stone ejectors to ensure multiple retreads beyond the original tread life.






**FOR THE MOST SEVERE DEMANDS**


**SEVERE SERIES MSA™**

Material #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REV's miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000033159	315/80R22.5 L/20 160/157K 68 mph 110 km/h	(9.00) 9.00-9.75	130	10,000	9,090	42.99	12.7	19.96	13.8	482	24.0	28	11.3	168	029142911203
			900	4,540	4,125	1,092	323	507	351	300	19.0	711	286	76.8	



**SEVERE SERIES WBA™**

Material #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REV's miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000034947	385/65R22.5 L/20 160K 68 mph 110 km/h	(11.75) 11.75-12.25	130	9,920	---	42.36	15.2	19.61	---	489	23.0	46	12.0	176	029142926320
			900	4,500	---	1,076	387	498	---	304	18.4	1168	311	80.2	
90000034948	425/65R22.5 L/20 165K 68 mph 110 km/h	(12.25) 12.25-14.00	120	11,400	---	44.53	16.6	20.51	---	466	23.0	46	13.0	198	029142926337
			830	5,150	---	1,131	422	521	---	289	18.4	1168	343	90.0	



**SEVERE SERIES MSD™**

**M+S**

Material #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REV's miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000034674	11R22.5 H/16 146/143K 68 mph 110 km/h	(8.25) 7.50-8.25	120	6,610	6,005	42.36	11.3	19.69	12.5	489	32.0	26	9.4	140	029142924807
			830	3,000	2,725	1,076	287	500	318	304	25.5	660	240	64.0	
90000034675	11R24.5 H/16 149/146K 68 mph 110 km/h	(8.25) 7.50-8.25	120	7,160	6,610	44.41	11.2	20.71	12.5	467	32.0	26	9.4	150	029142924814
			830	3,250	3,000	1,128	285	526	318	290	25.5	660	240	68.5	



## COOPER TIRE & RUBBER COMPANY NATIONAL ACCOUNT FLEET SOLUTIONS PROGRAM

- Call Center: 1-844-FLEET RX
- Nationwide Emergency Road Service available\*
- Centralized pricing and billing direct from Cooper Tire & Rubber Company
- Standardized tire and service pricing coast to coast

\*Some restrictions apply.



# PREMIUM WARRANTY

## WHAT IS COVERED AND FOR HOW LONG

- Free Tire Replacement** – Cooper warrants to the original purchaser that if a Cooper Pro or Work Series tire becomes unserviceable due to an eligible adjustable condition (excludes ride complaints) during the first 50% of the original factory tread, the tire will be replaced with an equivalent new Cooper Pro or Work Series tire without charge. If a Cooper Severe Series tire becomes unserviceable due to an eligible adjustable condition (excludes ride complaints) during the first 2/32" (1.6mm) of factory original tread wear, the tire will be replaced with an equivalent new Cooper Severe Series tire without charge.
- Prorated Tire Replacement** – Cooper warrants to the original purchaser that if a Cooper Pro or Work Series tire becomes unserviceable due to an eligible adjustable condition (excludes ride complaints) beyond the first 50% of the original factory tread, the tire will be replaced with an equivalent new Cooper Pro or Work Series tire on a prorated basis. If a Cooper Severe Series tire becomes unserviceable due to an eligible adjustable condition (excludes ride complaints) after the first 2/32" (1.6mm) of wear on original factory tread, the tire will be replaced with an equivalent new Cooper Severe Series tire on a prorated basis. A replacement charge (defined below) will be required in order to obtain a replacement tire.








## CASING ALLOWANCE

In normal highway service and off-road service, if within **seven (7) years** of date of manufacture a Cooper all-steel radial medium truck tire becomes unserviceable and is not retreadable due to an adjustable condition in the casing, or if it does not provide two (2) retreads of service it is eligible for the applicable casing allowance specified:

First Retread = \$110.00 Second Retread = \$80.00		First Retread = \$80.00 Second Retread = \$50.00		First Retread = \$50.00 Second Retread = \$35.00	
11R22.5	315/80R22.5	255/70R22.5		225/70R19.5	
11R24.5	385/65R22.5	275/70R22.5		245/70R19.5	
295/75R22.5	425/65R22.5			215/75R17.5	
285/75R24.5				245/70R17.5	

Please refer to the Cooper Tire Warranty for complete details or visit [www.CooperTruckTires.com](http://www.CooperTruckTires.com).

# COMPETITIVE COMPARISON

							
PRO SERIES LHS™*	X LINE ENERGY Z*	101ZL SPEC -2*	FS591*	AL21*	R283A ECOPIA*	ENDURANCE LHS*	ECOPLUS HS3*
WORK SERIES RHA™*	XZE2	108R*	FS561	AH24*	R268 ECOPIA*	ENDURANCE RSA	HSR3*
WORK SERIES ASA™*	XZE	104ZR	FS561	AH35	R238*	ENDURANCE RSA	HS3 - 19.5
SEVERE SERIES MSA™	XZUS2	MY627W SPEC-2	FS860	AM09+	M870	ENDURANCE WHA	HAU3 WT
SEVERE SERIES WBA™	XZY3	MY507A	FS818	AM15	M854	G296	HTC1
PRO SERIES LHD™*	XDA ENERGY*	712L*	FD691*	DL21*	M710 ECOPIA*	ENDURANCE LHD*	HDL2*
WORK SERIES AWD™*	XDN2	SY767	-	DL12	M760*	RTD	HDW2
WORK SERIES RHD™*	X MULTI D*	TY517 MC2*	FD663	DH37*	M770	G182 RSD	HYBRID HD3*
WORK SERIES ASD™*	XDS2	TY303/TY287	FD690 PLUS	DH07	M729F	G622 RSD	HD3 - 19.5
SEVERE SERIES MSD™	X WORKS XDY	LY053	FD835	DM04	M775	G741 MSD	HDC1
PRO SERIES LHT™*	X LINE ENERGY T*	109L*	FT492*	TL21*	R123*	FUELMAX LHT*	HT3*
WORK SERIES RHT™	XTE/XZE	RY023*	-	TH22	R250 ED	G619 RST	HT3*

\*SmartWay Verified

\*RHD - Load Range H is not Smartway.

