

Firestone

ULTRA HIGH PERFORMANCE

Firehawk INDY 500®	180
Firehawk AS	182

TOURING

Champion With Fuel Fighter Technology	184
WeatherGrip	186

PASSENGER

All Season	188
------------------	-----

LAW ENFORCEMENT / HIGH-SPEED EMERGENCY

Firehawk Pursuit	190
Firehawk Pursuit AWT	190
Firehawk PVS	190

LIGHT TRUCK / SUV HIGHWAY

Destination LE3	192
-----------------------	-----

LIGHT TRUCK / SUV ALL-TERRAIN

Destination A/T2	194
Destination X/T	196

LIGHT TRUCK / SUV MAX-TRACTION

Destination M/T2	198
------------------------	-----

LIGHT TRUCK / COMMERCIAL HIGHWAY

Transforce HT2	200
----------------------	-----

LIGHT TRUCK / COMMERCIAL ALL-TERRAIN

Transforce AT2	202
----------------------	-----

WINTER

WinterForce 2	204
WinterForce 2 UV	206
WinterForce LT	208

TIRE SPECIFICATIONS CURRENT AT TIME OF PUBLICATION




TIRE RESOURCE MANUAL

Firestone

FIREHAWK™ **INDY 500**

ULTRA-HIGH SUMMER PERFORMANCE AT A GREAT VALUE

FEATURES AND BENEFITS

-  Summer performance
-  Improved water evacuation for more control on wet roads
-  Ultra-high performance with bold design

PROPRIETARY PULSE GROOVE™ TECHNOLOGY

improves water evacuation and helps increase resistance to hydroplaning

IMPROVED WET RUBBER COMPOUND AND TREAD DESIGN

provides 20% shorter stopping distance on wet roads

NEW TREAD COMPOUND AND WIDE SHOULDER BLOCKS

provide impressive handling and cornering in dry conditions



SIZE	SERVICE DESCRIPTION	LOAD RANGE	ARTICLE NUMBER	SIDEWALL STYLING	APPROVED RIM WIDTHS	MEASURING RIM WIDTH	OVERALL DIAMETER	SECTION WIDTH	TREAD DEPTH (32ND")	REVS PER MILE	UTQG	WEIGHT LBS
16" RIM DIAMETER												
195/55R16	87W	---	002932	BW	5.5-7.0	6.0	24.4	7.9	9	853	340 A A	18.8
205/55R16	91W	---	011969	BW	5.5-7.5	6.5	24.9	8.4	9	837	340 A A	21.2
205/50R16	87W	---	011986	BW	5.5-7.5	6.5	24.1	8.4	9	865	340 A A	20.6
225/50R16	92W	---	012003	BW	6.0-8.0	7.0	24.9	9.2	9	837	340 A A	22.6
205/45R16	87W	XL	012020	BW	6.5-7.5	7.0	23.2	8.1	9	897	340 A A	19.9
17" RIM DIAMETER												
225/55R17	97W	---	002931	BW	6.0-8.0	7.0	26.8	9.2	10	778	340 A A	24.6
235/55R17	99W	---	002930	BW	6.5-8.5	7.5	27.2	9.7	10	767	340 A A	25.7
205/50R17	93W	XL	012037	BW	5.5-7.5	6.5	25.1	8.4	9	829	340 A A	22.1
225/50R17	94W	---	012054	BW	6.0-8.0	7.0	25.9	9.2	10	804	340 A A	24.1
235/50R17	96W	---	002929	BW	6.5-8.5	7.5	26.3	9.7	10	792	340 A A	25.1
205/45R17	88W	XL	012071	BW	6.5-7.5	7.0	24.3	8.1	9	859	340 A A	20.6
215/45R17	91W	XL	012088	BW	7.0-8.0	7.0	24.7	8.4	9	845	340 A A	21.6
225/45R17	94W	XL	012105	BW	7.0-8.5	7.5	25.0	8.9	10	835	340 A A	23.2
235/45R17	94W	---	012139	BW	7.5-9.0	8.0	25.4	9.3	10	822	340 A A	23.1
245/45R17	99W	XL	012156	BW	7.5-9.0	8.0	25.7	9.6	10	812	340 A A	25.4
205/40R17	84W	XL	012190	BW	7.0-8.0	7.5	23.5	8.4	9	888	340 A A	19.9
245/40R17	91W	---	012207	BW	8.0-9.5	8.5	24.7	9.8	10	843	340 A A	22.3
255/40R17	94W	---	012224	BW	8.5-10.0	9.0	25.0	10.2	10	832	340 A A	24.7
18" RIM DIAMETER												
235/55R18	100W	---	004350	BW	6.5-8.5	7.5	28.2	9.7	10	740	340 A A	28.2
225/50R18	95W	---	012241	BW	6.0-8.0	7.0	26.9	9.2	10	775	340 A A	25.5
235/50R18	101W	XL	002928	BW	6.5-8.5	7.5	27.3	9.7	10	764	340 A A	28.0
215/45R18	93W	XL	012258	BW	7.0-8.0	7.0	25.6	8.4	9	813	340 A A	23.1
225/45R18	95W	XL	012275	BW	7.0-8.5	7.5	25.9	8.9	10	803	340 A A	23.8
235/45R18	98W	XL	012292	BW	7.5-9.0	8.0	26.3	9.3	9	791	340 A A	25.5
245/45R18	100W	XL	012309	BW	7.5-9.0	8.0	26.7	9.6	10	782	340 A A	26.7
255/45R18	103W	XL	011952	BW	8.0-9.5	8.5	27.1	10.0	10	770	340 A A	28.0
215/40R18	89W	XL	012326	BW	7.0-8.5	7.5	24.8	8.6	9	841	340 A A	22.5
225/40R18	92W	XL	012360	BW	7.5-9.0	8.0	25.1	9.1	10	831	340 A A	23.1
235/40R18	95W	XL	012377	BW	8.0-9.5	8.5	25.4	9.5	10	820	340 A A	24.2
245/40R18	97W	XL	012394	BW	8.0-9.5	8.5	25.7	9.8	10	810	340 A A	25.6
255/40R18	99W	XL	012411	BW	8.5-10.0	9.0	26.0	10.2	10	801	340 A A	27.2
275/40R18	99W	---	002927	BW	9.0-11.0	9.5	26.7	10.9	10	782	340 A A	28.2
245/35R18	92W	XL	012428	BW	8.0-9.5	8.5	24.8	9.8	10	841	340 A A	24.4
255/35R18	94W	XL	012445	BW	8.5-10.0	9.0	25.0	10.2	10	833	340 A A	25.4
265/35R18	97W	XL	012462	BW	9.0-10.5	9.5	25.3	10.7	10	823	340 A A	26.0
275/35R18	95W	---	012496	BW	9.0-11.0	9.5	25.6	10.9	10	815	340 A A	26.5
19" RIM DIAMETER												
P245/50R19	104W	XL	002926	BW	7.0-8.5	7.5	28.7	10.0	10	726	340 A A	30.2
225/45R19	96W	XL	012530	BW	7.0-8.5	7.5	27.0	8.9	10	772	340 A A	26.2
245/45R19	98W	---	012547	BW	7.5-9.0	8.0	27.7	9.6	10	753	340 A A	27.0
225/40R19	93W	XL	012581	BW	7.5-9.0	8.0	26.1	9.1	10	798	340 A A	25.4
245/40R19	98W	XL	012598	BW	8.0-9.5	8.5	26.7	9.8	10	779	340 A A	27.0
255/40R19	100W	XL	012615	BW	8.5-10.0	9.0	27.1	10.2	10	770	340 A A	28.9
265/40R19	98W	---	002925	BW	9.0-10.5	9.5	27.4	10.7	10	760	340 A A	28.0
275/40R19	101W	---	012632	BW	9.0-11.0	9.5	27.7	10.9	10	753	340 A A	29.3
225/35R19	88W	XL	012649	BW	7.5-9.0	8.0	25.2	9.1	10	825	340 A A	24.0
235/35R19	91W	XL	012666	BW	8.0-9.5	8.5	25.5	9.5	10	818	340 A A	24.7
245/35R19	93W	XL	012683	BW	8.0-9.5	8.5	25.8	9.8	10	808	340 A A	26.2
255/35R19	96W	XL	012700	BW	8.5-10.0	9.0	26.0	10.2	10	801	340 A A	27.7
265/35R19	98W	XL	012717	BW	9.0-10.5	9.5	26.3	10.7	10	791	340 A A	28.8
275/35R19	100W	XL	012751	BW	9.0-11.0	9.5	26.6	10.9	10	784	340 A A	29.8
285/35R19	99W	---	003260	BW	9.5-11.0	10.0	26.9	11.4	10	775	340 A A	29.5
265/30R19	93W	XL	012802	BW	9.0-10.0	9.5	25.3	10.7	10	823	340 A A	27.4
275/30R19	96W	XL	012819	BW	9.0-10.0	9.5	25.6	10.9	10	815	340 A A	28.8
285/30R19	98W	XL	012836	BW	9.5-10.5	10.0	25.8	11.4	10	808	340 A A	30.3
325/30R19	101W	---	002924	BW	11.0-12.0	11.5	26.7	13.0	10	779	340 A A	33.0
20" RIM DIAMETER												
245/45R20	103W	XL	012853	BW	7.5-9.0	8.0	28.7	9.6	10	727	340 A A	29.0
255/45R20	101W	---	012870	BW	8.0-9.5	8.5	29.1	10.0	10	717	340 A A	29.9
245/40R20	99W	XL	012887	BW	8.0-9.5	8.5	27.7	9.8	10	751	340 A A	28.3
275/40R20	106W	XL	012921	BW	9.0-11.0	9.5	28.7	10.9	10	727	340 A A	32.2
255/35R20	97W	XL	012938	BW	8.5-10.0	9.0	27.0	10.2	10	771	340 A A	28.6
275/35R20	102W	XL	012972	BW	9.0-11.0	9.5	27.6	10.9	10	756	340 A A	30.8
285/35R20	100W	---	002922	BW	9.5-11.0	10.0	27.9	11.4	10	747	340 A A	30.7
305/35R20	104W	---	002921	BW	10.0-12.0	11.0	28.4	12.3	10	733	340 A A	34.1
285/30R20	99W	XL	012989	BW	9.5-10.5	10.0	26.8	11.4	10	778	340 A A	31.6






Firestone

FIREHAWK™ AS

OUR BEST ALL-SEASON HIGH PERFORMANCE TIRE

FEATURES AND BENEFITS

-  All-season performance
-  Improved water evacuation for more control on wet roads
-  Sport performance at a great value

50000

Mile Limited Treadwear Warranty

80000

Kilometer Treadwear Warranty

INCREASED CHANNELS

improve water evacuation to help reduce the risk of hydroplaning

20% MORE BITING EDGES**

provide increased traction control in snowy conditions

FULL DEPTH TREAD FEATURES

help keep sporty performance throughout the life of the tire

*50,000 mile limited treadwear warranty for H and V speed rated tires; 40,000 mile limited treadwear warranty for W speed rated tires. **As compared to the prior generation Firestone Firehawk tire. Certain restrictions and limitations apply. See warranty manual for details.



SIZE	SERVICE DESCRIPTION	LOAD RANGE	ARTICLE NUMBER	SIDEWALL STYLING	APPROVED RIM WIDTHS	MEASURING RIM WIDTH	OVERALL DIAMETER	SECTION WIDTH	TREAD DEPTH (32ND")	REVS PER MILE	UTQG	WEIGHT LBS
15" RIM DIAMETER												
195/65R15	91H	---	001400	BW	5.5-7.0	6.0	25.0	7.9	11	833	480 A A	19.1
195/60R15	88H	---	001401	BW	5.5-7.0	6.0	24.2	7.9	11	860	480 A A	19.0
185/55R15	82V	---	001402	BW	5.0-6.5	6.0	23.0	7.6	11	905	480 A A	18.4
16" RIM DIAMETER												
205/60R16	92H	---	001404	BW	5.5-7.5	6.0	25.7	8.2	11	812	480 A A	21.9
215/60R16	95V	---	001405	BW	6.0-7.5	6.5	26.1	8.7	11	797	480 A A	23.5
195/55R16	87V	---	001407	BW	5.5-7.0	6.0	24.4	7.9	11	853	480 A A	20.8
205/55R16	91H	---	001408	BW	5.5-7.5	6.5	24.9	8.4	11	837	480 A A	21.7
215/55R16	97V	XL	001409	BW	6.0-7.5	7.0	25.3	8.9	11	824	480 A A	25.3
225/55R16	95H	---	004348	BW	6.0-8.0	7.0	25.8	9.2	11	809	480 A A	26.0
195/50R16	84V	---	001410	BW	5.5-7.0	6.0	23.7	7.9	11	879	480 A A	20.1
17" RIM DIAMETER												
215/55R17	94V	---	001411	BW	6.0-7.5	7.0	26.3	8.9	11	792	480 A A	23.1
225/55R17	97V	---	001413	BW	6.0-8.0	7.0	26.8	9.2	11	778	480 A A	26.8
235/55R17	99V	---	001414	BW	6.5-8.5	7.5	27.2	9.7	11	767	480 A A	26.9
205/50R17	93V	XL	001415	BW	5.5-7.5	6.5	25.1	8.4	11	829	480 A A	24.1
215/50R17	95V	XL	001416	BW	6.0-7.5	7.0	25.5	8.9	11	817	480 A A	25.7
225/50R17	98V	XL	001417	BW	6.0-8.0	7.0	25.9	9.2	11	804	480 A A	27.5
215/45R17	91V	XL	001418	BW	7.0-8.0	7.0	24.7	8.4	11	845	480 A A	23.6
225/45R17	94V	XL	001419	BW	7.0-8.5	7.5	25.0	8.9	11	835	480 A A	24.4
235/45R17	97V	XL	001421	BW	7.5-9.0	8.0	25.4	9.3	11	822	480 A A	26.5
18" RIM DIAMETER												
215/55R18	95H	---	001423	BW	6.0-7.5	7.0	27.3	8.9	11	764	480 A A	24.8
235/55R18	100V	---	001424	BW	6.5-8.5	7.5	28.2	9.7	11	740	480 A A	28.6
225/50R18	95V	---	001426	BW	6.0-8.0	7.0	26.9	9.2	11	775	480 A A	25.3
235/50R18	97V	---	001427	BW	6.5-8.5	7.5	27.3	9.7	11	764	480 A A	26.5
225/45R18	95V	XL	001428	BW	7.0-8.5	7.5	25.9	8.9	11	803	480 A A	25.5
235/45R18	94V	---	004347	BW	7.5-9.0	8.0	26.3	9.3	11	791	480 A A	25.0
245/45R18	100V	XL	001430	BW	7.5-9.0	8.0	26.7	9.6	11	782	480 A A	29.1
245/40R18	97V	XL	001432	BW	8.0-9.5	8.5	25.7	9.8	11	810	480 A A	27.8
19" RIM DIAMETER												
245/50R19	105V	XL	001433	BW	7.0-8.5	7.5	28.7	10.0	11	726	480 A A	33.4
235/40R19	96V	XL	004349	BW	8.0-9.5	8.5	26.4	9.5	11	788	480 A A	27.5
245/40R19	98V	XL	001435	BW	8.0-9.5	8.5	26.7	9.8	11	779	480 A A	29.3
20" RIM DIAMETER												
245/45R20	103V	XL	001436	BW	7.5-9.0	8.0	28.7	9.6	11	727	480 A A	30.4
275/40R20	106V	XL	001438	BW	9.0-11.0	9.5	28.7	10.9	11	727	480 A A	33.0





CAR



MINIVAN

ALL-SEASON TOURING

Firestone



CHAMPION[™] WITH FUEL FIGHTER[™] TECHNOLOGY

BUILT TO LAST A LONG TIME

FEATURES AND BENEFITS



70,000 mile limited treadwear warranty*



All-season performance



Fuel Fighter[™] technology offers improved rolling resistance, which helps improve fuel economy**

70000

Mile Limited Treadwear Warranty

110000

Kilometer Treadwear Warranty

FUEL FIGHTER[™] TECHNOLOGY

helps increase fuel efficiency with new construction features optimized for low rolling resistance

NEW TREAD PATTERN

offers dependable performance in wet, dry and wintry conditions

NEW TREAD COMPOUND & OPTIMIZED FOOTPRINT

improves traction in wet conditions with flexible tread compound



*Certain conditions and limitations apply. See warranty manual for details.

** As compared to the Firestone Affinity Touring tire.

SIZE	SERVICE DESCRIPTION	LOAD RANGE	ARTICLE NUMBER	SIDEWALL STYLING	APPROVED RIM WIDTHS	MEASURING RIM WIDTH	OVERALL DIAMETER	SECTION WIDTH	TREAD DEPTH (32ND")	REVS PER MILE	UTQG	WEIGHT LBS
14" RIM DIAMETER												
185/60R14	82H	---	015063	BW	5.0-6.5	5.5	22.8	7.4	10	915	600 A A	15.6
15" RIM DIAMETER												
205/70R15	96T	---	014808	BW	5.0-7.0	6.0	26.3	8.2	11	791	600 A B	21.1
215/70R15	98T	---	014910	BW	5.5-7.0	6.5	26.9	8.7	11	775	600 A B	24.2
175/65R15	84H	---	015046	BW	5.0-6.0	5.0	24.0	7.0	11	869	600 A A	16.3
185/65R15	88H	---	015080	BW	5.0-6.5	5.5	24.5	7.4	11	852	600 A A	17.7
195/65R15	91H	---	015131	BW	5.5-7.0	6.0	25.0	7.9	10	833	600 A A	18.1
205/65R15	94H	---	015199	BW	5.5-7.5	6.0	25.5	8.2	10	818	600 A A	19.0
185/60R15	84T	---	014791	BW	5.0-6.5	5.5	23.7	7.4	10	878	600 A B	16.7
195/60R15	88H	---	015114	BW	5.5-7.0	6.0	24.2	7.9	10	860	600 A A	17.2
205/60R15	91H	---	015165	BW	5.5-7.5	6.0	24.7	8.2	10	844	600 A A	19.2
215/60R15	94H	---	015233	BW	6.0-7.5	6.5	25.2	8.7	10	828	600 A A	20.1
185/55R15	82H	---	015386	BW	5.0-6.5	6.0	23.0	7.6	10	905	600 A A	16.2
195/55R15	85H	---	015403	BW	5.5-7.0	6.0	23.4	7.9	10	889	600 A A	16.5
16" RIM DIAMETER												
225/70R16	103T	---	014961	BW	6.0-7.5	6.5	28.4	9.0	10	733	600 A B	27.4
205/65R16	95H	---	023240	BW	5.5-7.5	6.0	26.5	8.2	10	787	600 A A	20.0
215/65R16	98T	---	014859	BW	6.0-7.5	6.5	27.0	8.7	10	771	600 A B	22.2
225/65R16	100H	---	015335	BW	6.0-8.0	6.5	27.5	9.0	10	758	600 A A	24.5
235/65R16	103T	---	014995	BW	6.5-8.5	7.0	28.0	9.5	10	743	600 A B	25.3
205/60R16	92H	---	015182	BW	5.5-7.5	6.0	25.7	8.2	10	812	600 A A	19.9
215/60R16	95T	---	015029	BW	6.0-7.5	6.5	26.1	8.7	10	797	600 A B	20.5
215/60R16	95V	---	015369	BW	6.0-7.5	6.5	26.1	8.7	10	797	600 A A	20.8
225/60R16	98H	---	015607	BW	6.0-8.0	6.5	26.6	9.0	10	783	600 A A	22.5
235/60R16	100T	---	014978	BW	6.5-8.5	7.0	27.1	9.5	10	769	600 A B	24.9
195/55R16	87H	---	015097	BW	5.5-7.0	6.0	24.4	7.9	10	853	600 A A	17.1
205/55R16	91H	---	015148	BW	5.5-7.5	6.5	24.9	8.4	10	837	600 A A	18.6
215/55R16	93H	---	015488	BW	6.0-7.5	7.0	25.3	8.9	10	824	600 A A	20.8
195/50R16	84H	---	000107	BW	5.5-7.0	6.0	23.7	7.9	10	879	600 A A	16.8
205/50R16	87H	---	015420	BW	5.5-7.5	6.5	24.1	8.4	10	865	600 A A	17.8
17" RIM DIAMETER												
215/65R17	99T	---	014876	BW	6.0-7.5	6.5	28.0	8.7	10	743	600 A B	23.9
225/65R17	102T	---	014944	BW	6.0-8.0	6.5	28.5	9.0	10	731	600 A B	25.3
235/65R17	104T	---	015012	BW	6.5-8.5	7.0	29.1	9.5	10	717	600 A B	27.1
215/60R17	96T	---	014825	BW	6.0-7.5	6.5	27.2	8.7	10	767	600 A B	23.3
225/60R17	99H	---	015284	BW	6.0-8.0	6.5	27.6	9.0	10	754	600 A A	27.2
235/60R17	102H	---	015352	BW	6.5-8.5	7.0	28.1	9.5	10	741	600 A A	25.4
215/55R17	94V	---	015505	BW	6.0-7.5	7.0	26.3	8.9	10	792	600 A A	21.1
225/55R17	97V	---	015590	BW	6.0-8.0	7.0	26.8	9.2	10	778	600 A A	22.3
235/55R17	99H	---	015641	BW	6.5-8.5	7.5	27.2	9.7	10	767	600 A A	25.2
205/50R17	89V	---	015437	BW	5.5-7.5	6.5	25.1	8.4	10	829	600 A A	19.0
215/50R17	95V	XL	015471	BW	6.0-7.5	7.0	25.5	8.9	10	817	600 A A	21.9
225/50R17	94V	---	015556	BW	6.0-8.0	7.0	25.9	9.2	10	804	600 A A	20.8
215/45R17	87V	---	015454	BW	7.0-8.0	7.0	24.7	8.4	10	845	600 A A	19.9
225/45R17	91V	---	015522	BW	7.0-8.5	7.5	25.0	8.9	10	835	600 A A	21.4
235/45R17	97H	XL	015624	BW	7.5-9.0	8.0	25.4	9.3	10	822	600 A A	24.4
18" RIM DIAMETER												
225/60R18	100H	---	015301	BW	6.0-8.0	6.5	28.6	9.0	10	728	600 A A	25.7
215/55R18	95H	---	015216	BW	6.0-7.5	7.0	27.3	8.9	10	764	600 A A	21.0
235/55R18	100V	---	015658	BW	6.5-8.5	7.5	28.2	9.7	10	740	600 A A	27.4
225/50R18	95T	---	014927	BW	6.0-8.0	7.0	26.9	9.2	10	775	600 A B	24.6
225/45R18	95V	XL	015539	BW	7.0-8.5	7.5	25.9	8.9	10	803	600 A A	24.2
235/45R18	94V	---	001814	BW	7.5-9.0	8.0	26.3	9.3	10	791	600 A A	23.9





Firestone



WEATHERGRIP™

BUILT TO HELP KEEP YOU IN CONTROL, NO MATTER THE WEATHER

FEATURES AND BENEFITS

- Confident wet performance year round
- Long-lasting performance with a 65,000 mile limited mileage warranty†
- 3 Peak Mountain Snowflake certified

65000

Limited Mileage Warranty†

105000

Kilometer Treadwear Warranty

†Certain conditions and limitations apply. See a Firestone representative or FirestoneTire.com for details.

FEATURING ALL-NEW TECHNOLOGY PACKAGES: HYDRO-GRIP™ & TRACTIONTECH™ TECHNOLOGY*

1 OPEN SHOULDER SLOTS

for enhanced water evacuation from contact patch

2 3D FULL-DEPTH SIPES

on ALL ribs for even wear throughout the tire's limited mileage warranty period and for enhanced snow traction

3 SNOW TRACTION CLAW™ TECHNOLOGY

on center and shoulder blocks with snow vices on intermediate ribs



SIZE	SERVICE DESCRIPTION	LOAD RANGE	ARTICLE NUMBER	SIDEWALL STYLING	APPROVED RIM WIDTHS	MEASURING RIM WIDTH	OVERALL DIAMETER	SECTION WIDTH	TREAD DEPTH (32ND")	REVS PER MILE	UTQG	WEIGHT LBS
16" RIM DIAMETER												
215/70R16	100H	---	009164	BW	5.5-7.0	6.5	27.9	8.7	10	747	640 A A	22.3
235/70R16	106H	---	009171	BW	6.0-8.0	7.0	29.0	9.5	10	719	640 A A	27.3
215/55R16	93H	---	008100	BW	6.0-7.5	7.0	25.3	8.9	10	824	640 A A	19.1
17" RIM DIAMETER												
215/65R17	99H	---	009170	BW	6.0-7.5	6.5	28.0	8.7	10	743	640 A A	23.0
235/65R17	104H	---	008101	BW	6.5-8.5	7.0	29.1	9.5	10	717	640 A A	27.1
18" RIM DIAMETER												
235/65R18	106H	---	009167	BW	6.5-8.5	7.0	30.0	9.5	10	693	640 A A	27.6
225/60R18	100H	---	009169	BW	6.0-8.0	6.5	28.6	9.0	10	728	640 A A	24.1
235/60R18	103H	---	009163	BW	6.5-8.5	7.0	29.1	9.5	10	716	640 A A	25.0
245/60R18	105H	---	009166	BW	7.0-8.5	7.0	29.6	9.8	10	704	640 A A	29.6
235/55R18	100H	---	009162	BW	6.5-8.5	7.5	28.2	9.7	10	740	640 A A	25.2
235/50R18	97V	---	009165	BW	6.5-8.5	7.5	27.3	9.7	10	764	640 A A	24.0
19" RIM DIAMETER												
235/55R19	101H	---	009168	BW	6.5-8.5	7.5	29.2	9.7	10	714	640 A A	24.8





CAR



MINIVAN



CUV

ALL-SEASON TOURING

Firestone

ALL SEASON

A QUALITY TIRE
AT A GREAT VALUE
FROM A BRAND
YOU CAN TRUST

FEATURES AND BENEFITS



A tire you can count on



All-season performance



Built to last

65000

Mile Limited Treadwear Warranty

105000

Kilometer Treadwear Warranty



DEEP SIPES

retain wet and all-season performance

SPECIALLY ENGINEERED

to provide performance in wet, dry, and snowy conditions with traction and handling all year long



*55,000 Mile Limited Treadwear Warranty for all CUV intended sizes; 65,000 Mile Limited Treadwear Warranty for all other sizes. Certain limitations and restrictions apply. See warranty manual for details.

SIZE	SERVICE DESCRIPTION	LOAD RANGE	ARTICLE NUMBER	SIDEWALL STYLING	APPROVED RIM WIDTHS	MEASURING RIM WIDTH	OVERALL DIAMETER	SECTION WIDTH	TREAD DEPTH (32ND")	REVS PER MILE	UTQG	WEIGHT LBS
14" RIM DIAMETER												
195/70R14	91T	---	004062	BW	5.0-6.5	6.0	24.8	7.9	11	840	560 A B	16.0
185/65R14	86T	---	004040	BW	5.0-6.5	5.5	23.5	7.4	10	888	560 A B	16.6
15" RIM DIAMETER												
205/70R15	96T	---	004044	BW	5.0-7.0	6.0	26.3	8.2	10	791	560 A B	18.9
215/70R15	98T	---	004014	BW	5.5-7.0	6.5	26.9	8.7	10	775	560 A B	20.7
175/65R15	84T	---	004054	BW	5.0-6.0	5.0	24.0	7.0	10	869	560 A B	15.2
185/65R15	88T	---	004018	BW	5.0-6.5	5.5	24.5	7.4	10	852	560 A B	15.8
205/65R15	94T	---	004012	BW	5.5-7.5	6.0	25.5	8.2	9	818	560 A B	17.8
185/60R15	84T	---	004058	BW	5.0-6.5	5.5	23.7	7.4	10	878	560 A B	15.4
16" RIM DIAMETER												
215/70R16	100S	---	003036	BW	5.5-7.0	6.5	27.9	8.7	10	747	480 A B	22.1
225/70R16	103T	---	003042	BW	6.0-7.5	6.5	28.4	9.0	10	733	480 A B	24.1
P235/70R16	104T	---	003024	BW	6.0-8.0	7.0	29.0	9.5	10	719	480 A B	26.3
205/65R16	95T	---	004030	BW	5.5-7.5	6.0	26.5	8.2	9	787	560 A B	19.3
215/65R16	98T	---	004020	BW	6.0-7.5	6.5	27.0	8.7	9	771	560 A B	22.7
225/65R16	100T	---	004046	BW	6.0-8.0	6.5	27.5	9.0	10	758	560 A B	23.3
235/65R16	103T	---	004028	BW	6.5-8.5	7.0	28.0	9.5	10	743	560 A B	26.8
215/60R16	95T	---	003816	BW	6.0-7.5	6.5	26.1	8.7	9	797	560 A B	19.9
225/60R16	98T	---	004002	BW	6.0-8.0	6.5	26.6	9.0	10	783	560 A B	21.2
235/60R16	100T	---	004068	BW	6.5-8.5	7.0	27.1	9.5	10	769	560 A B	25.3
185/55R16	83T	---	003051	BW	5.0-6.5	6.0	24.0	7.6	10	867	560 A B	16.8
215/55R16	93T	---	004042	BW	6.0-7.5	7.0	25.3	8.9	9	824	560 A B	18.7
205/50R16	87H	---	004070	BW	5.5-7.5	6.5	24.1	8.4	9	865	560 A B	18.6
17" RIM DIAMETER												
215/65R17	99T	---	004050	BW	6.0-7.5	6.5	28.0	8.7	9	743	560 A B	21.8
225/65R17	102T	---	003019	BW	6.0-8.0	6.5	28.5	9.0	10	731	480 A B	26.0
235/65R17	104T	---	003034	BW	6.5-8.5	7.0	29.1	9.5	10	717	480 A B	26.3
215/60R17	96T	---	004034	BW	6.0-7.5	6.5	27.2	8.7	9	767	560 A B	19.9
225/60R17	99T	---	004022	BW	6.0-8.0	6.5	27.6	9.0	10	754	560 A B	22.2
235/60R17	102T	---	004032	BW	6.5-8.5	7.0	28.1	9.5	10	741	560 A B	23.9
215/55R17	94H	---	007788	BW	6.0-7.5	7.0	26.3	8.9	9	792	560 A B	21.2
18" RIM DIAMETER												
225/60R18	100T	---	004060	BW	6.0-8.0	6.5	28.6	9.0	10	728	560 A B	23.2
235/65R18	106T	---	003068	BW	6.5-8.5	7.0	30.0	9.5	10	693	480 A B	29.8
P255/65R18	109S	---	003072	BW	7.0-9.0	7.5	31.1	10.2	10	671	480 A B	31.2
235/60R18	103H	---	003040	BW	6.5-8.5	7.0	29.1	9.5	10	716	480 A B	24.9
245/60R18	105T	---	003066	BW	7.0-8.5	7.0	29.6	9.8	10	704	480 A B	30.1
265/60R18	110T	---	003058	BW	7.5-9.5	8.0	30.5	10.7	10	683	480 A B	31.6
225/55R18	98H	---	003076	BW	6.0-8.0	7.0	27.8	9.2	10	749	480 A B	22.7
235/55R18	100H	---	003030	BW	6.5-8.5	7.5	28.2	9.7	10	740	480 A B	24.3
245/55R18	103T	---	003057	BW	7.0-8.5	7.5	28.6	10.0	10	728	560 A B	24.8
235/45R18	94H	---	003065	BW	7.5-9.0	8.0	26.3	9.3	10	791	560 A B	22.0
19" RIM DIAMETER												
P255/60R19	108S	---	003084	BW	7.0-9.0	7.5	31.1	10.2	10	671	480 A B	31.5
235/55R19	101H	---	003050	BW	6.5-8.5	7.5	29.2	9.7	10	714	480 A B	25.4
245/55R19	103S	---	003080	BW	7.0-8.5	7.5	29.7	10.0	10	703	480 A B	25.9
20" RIM DIAMETER												
P255/55R20	107H	---	003092	BW	7.0-9.0	8.0	31.0	10.4	10	672	480 A B	29.7
P245/50R20	102H	---	003082	BW	7.0-8.5	7.5	29.7	10.0	10	702	480 A B	27.2






Firestone

SOME TIRES LEAD AND PURSUE AT THE SAME TIME






FIREHAWK™ PURSUIT™

-  All-season with confident wet performance
-  Full-Depth tread features deliver long-lasting performance
-  Improved fuel efficiency with a 24% rolling resistance improvement over the previous generation Firehawk GT Pursuit

SPEED RATING: V & W






FIREHAWK™ PURSUIT™ AWT

-  3 Peak Mountain Snowflake Certified
-  All Season Performance - No need for seasonal changeovers
-  Designed for law enforcement and high speed emergency use

SPEED RATING: V & W



FIREHAWK™ PVS

-  High speed handling with solid traction in wet and snow
-  Thousands of biting edges help provide traction in the wet and snow
-  Designed for law enforcement and high speed emergency use in winter conditions

SPEED RATING: H & V



FIREHAWK™ PURSUIT™

SIZE	SERVICE DESCRIPTION	LOAD RANGE	ARTICLE NUMBER	SIDEWALL STYLING	APPROVED RIM WIDTHS	MEASURING RIM WIDTH	OVERALL DIAMETER	SECTION WIDTH	TREAD DEPTH (32ND")	REVS PER MILE	UTQG	WEIGHT LBS
17" RIM DIAMETER												
265/60R17	108V	---	011685	BW	---	---	---	---	---	0	N/A	---
235/55R17	99W	---	011687	BW	---	---	---	---	---	0	N/A	---
235/50R17	96W	---	011494	BW	6.5-8.5	7.5	26.3	9.7	---	792	N/A	---
18" RIM DIAMETER												
225/60R18	100W	---	011688	BW	---	---	---	---	---	0	N/A	---
245/55R18	103W	---	000702	BW	7.0-8.5	7.5	28.6	10.0	---	728	N/A	---
235/50R18	101W	XL	011686	BW	---	---	---	---	---	0	N/A	---
20" RIM DIAMETER												
275/55R20	113V	---	008921	BW	7.5-9.5	8.5	31.9	11.2	---	653	N/A	---

FIREHAWK™ PURSUIT™ AWT

SIZE	SERVICE DESCRIPTION	LOAD RANGE	ARTICLE NUMBER	SIDEWALL STYLING	APPROVED RIM WIDTHS	MEASURING RIM WIDTH	OVERALL DIAMETER	SECTION WIDTH	TREAD DEPTH (32ND")	REVS PER MILE	UTQG	WEIGHT LBS
17" RIM DIAMETER												
265/60R17	108V	---	011691	BW	---	---	---	---	---	---	N/A	---
235/50R17	96V	---	011496	BW	6.5-8.5	7.5	26.3	9.7	---	792	N/A	---
18" RIM DIAMETER												
225/60R18	100V	---	011690	BW	---	---	---	---	---	---	N/A	---
255/60R18	108V	---	011894	BW	---	---	---	---	---	---	N/A	---
245/55R18	103V	---	000694	BW	7.0-8.5	7.5	28.6	10.0	---	728	N/A	---

FIREHAWK™ PVS

SIZE	SERVICE DESCRIPTION	LOAD RANGE	ARTICLE NUMBER	SIDEWALL STYLING	APPROVED RIM WIDTHS	MEASURING RIM WIDTH	OVERALL DIAMETER	SECTION WIDTH	TREAD DEPTH (32ND")	REVS PER MILE	UTQG	WEIGHT LBS
17" RIM DIAMETER												
265/60R17	108V	---	011691	BW	---	---	---	---	---	---	N/A	---
235/50R17	96V	---	011496	BW	6.5-8.5	7.5	26.3	9.7	---	792	N/A	---
18" RIM DIAMETER												
225/60R18	100V	---	011690	BW	---	---	---	---	---	---	N/A	---
255/60R18	108V	---	011894	BW	---	---	---	---	---	---	N/A	---
245/55R18	103V	---	000694	BW	7.0-8.5	7.5	28.6	10.0	---	728	N/A	---








Firestone

DESTINATION™ LE3

IT'S OUR BEST-SELLING TIRE FOR A REASON

FEATURES AND BENEFITS

-  Firestone's longest limited warranty†
-  Sustained performance throughout tread life
-  Dependable wet, dry and snow performance

70000

Mile Limited Warranty†

†Conditions apply. See FirestoneTire.com/warranty for details.



1 TRACTIONTECH™ TECHNOLOGY

provides more consistent wear over longer tire life*

2 HYDRO-GRIP™ TECHNOLOGY

for enhanced water evacuation from contact patch under wet conditions*

3 FULL-DEPTH 3D SIPES

for enhanced snow traction and improved performance throughout the tire's limited warranty*



SIZE	SERVICE DESCRIPTION	LOAD RANGE	ARTICLE NUMBER	SIDEWALL STYLING	APPROVED RIM WIDTHS	MEASURING RIM WIDTH	OVERALL DIAMETER	SECTION WIDTH	TREAD DEPTH (32ND")	REVS PER MILE	UTQG	WEIGHT LBS
15" RIM DIAMETER												
215/75R15	100T		005343	OWL	5.5-7.0	6.00	27.7	8.5	10	753	700 A B	---
225/75R15	102T		005344	OWL	6.0-7.5	6.00	28.3	8.8	10	736	700 A B	---
235/75R15	109T	XL	005346	OWL	6.0-8.0	7.00	28.9	9.3	10	722	700 A B	13.2 LB
265/75R15	112T		005348	OWL	7.0-9.0	7.50	30.7	10.5	10	679	700 A B	---
225/70R15	100T		005345	OWL	6.0-7.5	6.50	27.4	9.0	10	759	700 A B	---
16" RIM DIAMETER												
225/75R16	104T		005334	OWL	6.0-7.5	6.00	29.3	8.8	10	711	700 A B	---
235/75R16	108T		005336	OWL	6.0-8.0	7.00	29.8	9.3	10	698	700 A B	---
245/75R16	111T		005340	OWL	6.5-8.0	7.00	30.5	9.8	10	684	700 A B	---
265/75R16	116T		005353	OWL	7.0-9.0	8.00	31.7	10.5	10	658	700 A B	---
205/70R16	97H		005349	BW	5.0-7.0	6.00	27.3	8.2	10	762	700 A B	---
215/70R16	100H		005350	BW	5.5-7.0	6.50	27.9	8.7	10	747	700 A B	---
225/70R16	103T		005335	OWL	6.0-7.5	6.50	28.4	9.0	10	733	700 A B	---
235/70R16	106H		005338	OWL	6.0-8.0	7.00	29.0	9.5	10	719	700 A B	---
245/70R16	107T		005341	OWL	6.5-8.0	7.00	29.5	9.8	10	705	700 A B	---
255/70R16	111T		005342	OWL	6.5-8.5	8.00	30.1	10.2	10	693	700 A B	---
265/70R16	112T		005354	OWL	7.0-9.0	8.00	30.6	10.7	10	680	700 A B	---
215/65R16	98H		005351	BW	6.0-7.5	6.50	27.0	8.7	10	771	700 A B	---
235/65R16	103H		005339	BW	6.5-8.5	7.00	28.0	9.5	10	743	700 A B	---
255/65R16	109H		005352	OWL	7.0-9.0	7.50	29.1	10.2	10	717	700 A B	---
17" RIM DIAMETER												
235/70R17	109T	XL	005362	OWL	6.0-8.0	7.00	29.0	9.5	10	719	700 A B	---
245/70R17	110T		005369	OWL	6.5-8.0	7.00	30.6	9.8	10	682	700 A B	---
255/70R17	112T		005371	OWL	6.5-8.5	8.00	31.1	10.2	10	670	700 A B	---
265/70R17	115T		005374	OWL	7.0-9.0	8.00	31.7	10.7	12	658	700 A B	---
215/65R17	99H		005357	BW	6.0-7.5	6.50	28.0	8.7	10	743	700 A A	---
225/65R17	102H		005359	BW	6.0-8.0	6.50	28.5	9.0	10	731	700 A B	---
235/65R17	104H		005365	BW	6.5-8.5	7.00	29.1	9.5	N/A	717	700 A B	---
245/65R17	107H		005370	OWL	7.0-8.5	7.00	29.5	9.8	10	705	700 A B	---
255/65R17	110H		005372	OWL	7.0-9.0	8.00	30.1	10.2	N/A	693	700 A B	---
265/65R17	112H		005375	OWL	7.5-9.5	8.00	30.6	10.7	10	682	700 A B	---
215/60R17	96H		005358	BW	6.0-7.5	6.50	27.2	8.7	10	767	700 A B	---
225/60R17	99H		005360	BW	6.0-8.0	6.50	27.6	9.0	10	754	700 A B	---
235/60R17	102H		005366	BW	6.5-8.5	7.00	28.1	9.5	10	741	700 A B	---
225/55R17	97V		005361	BW	6.0-8.0	7.00	26.8	9.2	10	778	700 A B	---
235/55R17	99H		005368	BW	6.5-8.5	7.50	27.2	9.7	10	767	700 A B	---
18" RIM DIAMETER												
255/70R18	113T		005385	OWL	6.5-8.5	7.50	32.1	10.2	10	649	700 A B	---
265/70R18	116T		005388	OWL	7.0-9.0	8.00	32.6	10.7	10	638	700 A B	---
235/65R18	106H		005379	OWL	6.5-8.5	7.00	30.0	9.5	10	693	700 A B	---
255/65R18	111H		005386	BW	7.0-9.0	7.50	31.1	10.2	10	671	700 A B	---
265/65R18	114H		005389	OWL	7.5-9.5	8.00	31.5	10.7	10	660	700 A B	---
275/65R18	116H		005392	OWL	7.5-9.5	8.00	32.1	11.4	10	649	700 A B	---
225/60R18	100H		005376	BW	6.0-8.0	6.50	28.6	9.0	10	728	700 A B	25.0 LB
235/60R18	103H		005380	BW	6.5-8.5	7.00	29.1	9.5	10	716	700 A B	---
245/60R18	105H		005384	BW	7.0-8.5	7.00	29.6	9.8	10	704	700 A B	---
265/60R18	110H		005391	OWL	7.5-9.5	8.00	30.5	10.7	10	683	700 A B	---
225/55R18	98H		005378	BW	6.0-8.0	7.00	27.8	9.2	10	749	700 A B	---
235/55R18	100V		005382	BW	6.5-8.5	7.50	28.2	9.7	10	740	700 A B	---
255/55R18	109H	XL	005387	BW	7.0-9.0	8.00	29.0	10.4	10	718	700 A B	---
235/50R18	97H		005383	BW	6.5-8.5	7.50	27.3	9.7	10	764	700 A B	25.1 LB
19" RIM DIAMETER												
255/60R19	109H		005403	BW	7.0-9.0	7.50	31.1	10.2	10	671	700 A B	---
225/55R19	99H		005393	BW	6.0-8.0	7.00	28.8	9.2	10	724	700 A B	---
235/55R19	101H		005394	BW	6.5-8.5	7.50	29.2	9.7	10	714	700 A B	---
245/55R19	103H		005397	BW	7.0-8.5	7.50	29.7	10.0	10	703	700 A B	---
275/55R19	111H		005399	BW	7.5-9.5	8.50	30.9	11.2	10	674	700 A B	---
235/50R19	99H		005395	BW	6.5-8.5	7.50	28.3	9.7	10	736	700 A B	---
255/50R19	107H	XL	005398	BW	7.0-9.0	8.00	29.1	10.4	10	716	700 A B	---
235/45R19	95H		005396	BW	7.5-9.0	8.00	27.4	9.3	10	761	700 A B	---
20" RIM DIAMETER												
245/60R20	107H		005412	BW	7.0-8.5	7.00	31.6	9.8	10	660	700 A B	---
275/60R20	115H		005409	BW	7.5-9.5	8.00	33.0	11.0	10	631	700 A B	---
235/55R20	102H		005400	BW	6.5-8.5	7.50	30.2	9.7	10	691	700 A B	---
255/55R20	107H		005405	BW	7.0-9.0	8.00	31.0	10.4	10	672	700 A B	---
275/55R20	113H		005410	BW	7.5-9.5	8.50	31.9	11.2	10	653	700 A B	---
245/50R20	102H		005401	BW	7.0-8.5	7.50	29.7	10.0	10	702	700 A B	29.6 LB
255/50R20	109H	XL	005406	BW	7.0-9.0	8.00	30.1	10.4	10	693	700 A B	---
265/50R20	107H		005408	BW	7.5-9.5	8.50	30.5	10.9	10	684	700 A B	---
275/45R20	110H	XL	005411	BW	8.5-10.5	9.00	29.8	10.8	10	700	700 A B	---
22" RIM DIAMETER												
285/45R22	110H		005413	BW	9.0-10.5	9.50	32.1	11.2	10	649	700 A B	---





Firestone

DESTINATION™ A/T2

BUILT TOUGH FOR DEPENDABILITY, ON OR OFF-ROAD

FEATURES AND BENEFITS



Dependable on and off-road traction



Longer-lasting performance[^]



Built for wet performance and off-road handling, plus 3 Peak Mountain Snowflake certification

5 5 0 0 0

Limited Mileage Warranty[†]

9 0 0 0 0

Kilometer Treadwear Warranty

[^]As compared to Firestone Destination™ A/T.

[†]Certain conditions and limitations apply.

See a Firestone representative or FirestoneTire.com for details.



FEATURING ALL-NEW TECHNOLOGY PACKAGES: HYDRO-GRIP™ & TRACTIONTECH™ TECHNOLOGY*

1 AGGRESSIVE SHOULDER TREAD PATTERN

helps to improve off-road handling

2 FULL-DEPTH INTERLOCKING 3D SIPE TECHNOLOGY

helps to provide even wear and consistent performance through the limited mileage warranty period

3 INCREASED SURFACE AND SEE-THROUGH VOID

helps to improve water evacuation to improve wet stopping and handling



SIZE	SERVICE DESCRIPTION	LOAD RANGE	ARTICLE NUMBER	SIDEWALL STYLING	APPROVED RIM WIDTHS	MEASURING RIM WIDTH	OVERALL DIAMETER	SECTION WIDTH	TREAD DEPTH (32ND")	REVS PER MILE	UTQG	WEIGHT LBS
15" RIM DIAMETER												
P235/75R15	105S	---	014043	OWL	6.0-8.0	6.5	28.9	9.3	12	722	540 AB	29.5
16" RIM DIAMETER												
P225/75R16	104S	---	014111	OWL	6.0-7.5	6.0	29.3	8.8	12	711	540 AB	34.2
P245/75R16	109S	---	014145	OWL	6.5-8.0	7.0	30.5	9.8	12	684	540 AB	34.3
P265/75R16	114T	---	014162	OWL	7.0-9.0	7.5	31.7	10.5	12	658	540 AB	37.8
P235/70R16	104S	---	014213	OWL	6.0-8.0	7.0	29.0	9.5	12	719	540 AB	30.0
P245/70R16	106S	---	014247	OWL	6.5-8.0	7.0	29.5	9.8	12	705	540 AB	32.7
P255/70R16	109S	---	014264	OWL	6.5-8.5	7.5	30.1	10.2	12	693	540 AB	36.0
P265/70R16	111T	---	014298	OWL	7.0-9.0	8.0	30.6	10.7	12	680	540 AB	35.2
17" RIM DIAMETER												
P235/75R17	108S	---	014315	OWL	6.0-8.0	6.5	30.9	9.3	12	675	540 AB	33.6
P255/75R17	113S	---	014349	OWL	6.5-8.5	7.0	32.1	10.0	12	650	540 AB	37.1
P235/70R17	108S	XL	014366	OWL	6.0-8.0	7.0	30.0	9.5	12	694	540 AB	32.4
P245/70R17	108S	---	014383	OWL	6.5-8.0	7.0	30.6	9.8	12	682	540 AB	34.8
P255/70R17	110S	---	014417	OWL	6.5-8.5	7.5	31.1	10.2	12	670	540 AB	36.3
P265/70R17	113S	---	014434	OWL	7.0-9.0	8.0	31.7	10.7	12	658	540 AB	38.3
P285/70R17	117T	---	014468	OWL	7.5-9.5	8.5	32.8	11.5	12	636	540 AB	42.1
P235/65R17	103S	---	014502	OWL	6.5-8.5	7.0	29.1	9.5	12	717	540 AB	28.9
P245/65R17	105T	---	014519	OWL	7.0-8.5	7.0	29.5	9.8	12	705	540 AB	33.0
P255/65R17	108S	---	014536	OWL	7.0-9.0	7.5	30.1	10.2	12	693	540 AB	35.1
P265/65R17	110S	---	014553	OWL	7.5-9.5	8.0	30.6	10.7	12	682	540 AB	36.5
18" RIM DIAMETER												
P255/70R18	112S	---	014570	OWL	6.5-8.5	7.5	32.1	10.2	12	649	540 AB	38.4
P265/70R18	114S	---	014587	OWL	7.0-9.0	8.0	32.6	10.7	12	638	540 AB	40.5
P265/65R18	112S	---	014689	OWL	7.5-9.5	8.0	31.5	10.7	12	660	540 AB	39.4
P275/65R18	114T	---	014706	OWL	7.5-9.5	8.0	32.1	11.0	12	649	540 AB	40.9
P245/60R18	104T	---	014723	BW	7.0-8.5	7.0	29.6	9.8	12	704	540 AB	32.3
P265/60R18	109T	---	014740	OWL	7.0-9.5	8.0	30.5	10.7	12	683	540 AB	38.1
19" RIM DIAMETER												
P275/60R20	114S	---	014757	OWL	7.5-9.5	8.0	33.0	11.0	12	631	540 AB	43.0
P275/55R20	111S	---	014774	BW	7.5-9.5	8.5	31.9	11.2	12	653	540 AB	38.9

Firestone



GOLD PLEDGE





ALL-WEATHER, ALL-TERRAIN LIGHT TRUCK & SUV

Firestone



DESTINATION™ X/T

**BUILT TOUGH TO GIVE YOU PROVEN
“ANYWHERE” TRACTION AND
DURABILITY YOU CAN COUNT ON**

FEATURES AND BENEFITS



Dependable off-road traction



Heavy-duty toughness that lasts



Built for wet performance and off-road handling,
plus 3 Peak Mountain Snowflake certification

5 0 0 0 0

Limited Mileage Warranty†

8 0 0 0 0

Kilometer Treadwear Warranty

†Certain conditions and limitations apply.

See a Firestone representative or FirestoneTire.com for details.

FEATURING ALL-NEW TECHNOLOGY PACKAGES: HYDRO-GRIP™ & TRACTIONTECH™ TECHNOLOGY*

1 STAGGERED SHOULDER LUGS

and an aggressive off-shoulder tread design provide extra biting edges for off-road performance

2 FULL-DEPTH INTERLOCKING 3D SIPE TECHNOLOGY

helps to provide even wear and consistent performance through the limited mileage warranty period

3 OPEN SHOULDER SLOTS

provide off-road traction and also evacuate water to help reduce the risk of hydroplaning



SIZE	SERVICE DESCRIPTION	LOAD RANGE	ARTICLE NUMBER	SIDEWALL STYLING	APPROVED RIM WIDTHS	MEASURING RIM WIDTH	OVERALL DIAMETER	SECTION WIDTH	TREAD DEPTH (32ND")	REVS PER MILE	WEIGHT LBS
16" RIM DIAMETER											
LT285/75R16	126/123R	E	009608	OWL	7.5-9.0	8.0	32.8	11.3	16	634	51.8
17" RIM DIAMETER											
LT275/70R17	121/118R	E	008381	OWL	7.0-8.5	8.0	32.2	11.0	16	647	49.1
18" RIM DIAMETER											
LT285/65R18	125/122R	E	008375	BW	8.0-10.0	8.5	32.6	11.5	16	640	50.3
20" RIM DIAMETER											
LT275/60R20	123/120R	E	008383	BW	7.5-9.5	8.0	33.0	11.0	16	631	51.9
LT275/55R20	120/117R	E	008380	BW	7.5-9.5	8.5	31.9	11.2	16	653	49.1
LT285/55R20	122/119R	E	008376	BW	8.0-10.0	9.0	32.4	11.7	16	644	52.5
LT305/55R20	121/118R	E	008377	BW	8.5-11.0	9.5	33.2	12.4	16	627	56.8

Firestone



GOLD PLEDGE





Firestone

DESTINATION™ M/T2




TOUGH ENOUGH TO GO WHEREVER THE TRAIL TAKES YOU

FEATURES AND BENEFITS

 Made for off-roading

 Built tough

 Impressive performance in wet and snowy conditions

MUD AND STONE REJECTORS

clear debris from the tread to maximize usable life



ADDITIONAL BITING EDGES

provide 20% more biting edges for better traction on slick, wet surfaces and in the snow

NEW TREAD COMPOUND, 3-PLY SIDEWALL CONSTRUCTION, AND MORE AGGRESSIVE UPPER SIDEWALL LUGS

provide more traction in the mud and stronger resistance to chips and tears

SIZE	SERVICE DESCRIPTION SGL/DUAL	LOAD RANGE	ARTICLE NUMBER	SIDEWALL STYLING	APPROVED RIM WIDTHS	MEASURING RIM WIDTH	OVERALL DIAMETER	SECTION WIDTH	TREAD DEPTH (32ND")	REVS PER MILE	WEIGHT LBS	STUD SIZE
15" RIM DIAMETER												
LT235/75R15	104/101Q	C	003493	OWL	6.0-7.0	6.5	28.9	9.3	19	722	39.7	16
16" RIM DIAMETER												
LT245/85R16	120/116Q	E	003462	BW	6.0-7.5	6.5	31.7	9.3	19	656	49.0	16
LT245/75R16	120/116Q	E	245587	BW	6.5-8.0	7.0	30.5	9.8	19	684	47.9	16
LT265/75R16	123/120Q	E	245604	OWL	7.0-8.0	7.5	31.7	10.5	19	658	53.5	16
LT285/75R16	126/123Q	E	245621	OWL	7.5-9.0	8.0	32.8	11.3	20	634	59.9	17
LT315/75R16	127/124Q	E	003461	BW	8.0-10.0	8.5	34.6	12.3	21	603	68.4	17
17" RIM DIAMETER												
LT245/75R17	121/118Q	E	003459	OWL	6.5-7.5	7.0	31.5	9.8	19	661	49.9	16
LT255/75R17	111/108Q	C	011618	OWL	---	---	---	---	19	---	49.7	16
LT255/75R17	111/108Q	C	245655	OWL	6.5-8.5	7.0	32.1	10.0	19	650	49.7	16
LT265/70R17	121/118Q	E	245723	OWL	7.0-8.5	8.0	31.7	10.7	19	658	53.3	16
LT285/70R17	121/118Q	E	245740	BW	7.5-9.0	8.5	32.8	11.5	20	636	59.5	17
LT295/70R17	121/118Q	E	003808	BW	7.5-10.0	8.5	33.5	11.8	21	625	65.7	16
LT315/70R17	121/118Q	E	245757	BW	8.5-10.0	9.5	34.4	12.7	21	605	66.8	17
18" RIM DIAMETER												
LT275/70R18	125/122Q	E	245825	OWL	7.0-8.5	8.0	33.2	11.0	20	628	59.9	17
LT295/70R18	129/126Q	E	003456	BW	7.5-10.0	8.5	34.3	11.8	21	607	65.8	17
LT275/65R18	123/120Q	E	003457	BW	7.5-9.0	8.0	32.1	11.0	20	649	55.0	16
LT285/65R18	125/122Q	E	245859	BW	8.0-10.0	8.5	32.6	11.5	20	640	57.8	16
20" RIM DIAMETER												
LT275/65R20	126/123Q	E	245927	BW	7.5-9.5	8.0	34.3	11.0	20	611	58.1	16
FLOTATION SIZES												
15" RIM DIAMETER												
31X10.50R15LT	109Q	C	245502	OWL	7.0-9.0	8.5	30.5	10.5	20	683	47.2	17
32X11.50R15LT	113Q	C	003463	OWL	8.0-10.0	9.0	31.5	11.4	22	661	53.8	17
33X12.50R15LT	108Q	C	245519	OWL	8.5-11.0	10.0	32.5	12.5	22	641	57.8	17
17" RIM DIAMETER												
37X12.50R17LT	124Q	D	003803	BW	8.5-11.0	10.0	36.8	12.5	21	570	80.5	17
35X12.50R17LT	121Q	E	003810	BW	8.5-11.0	10.0	34.8	12.5	21	603	72.8	17
33X12.50R17LT	120Q	E	003815	BW	8.5-11.0	10.0	32.8	12.5	21	641	66.6	17
18" RIM DIAMETER												
35X12.50R18LT	123Q	E	003811	BW	8.5-11.0	10.0	34.8	12.5	21	603	73.0	17
20" RIM DIAMETER												
37X13.50R20LT	127Q	E	003805	BW	8.5-11.0	11.0	36.8	13.6	21	570	83.8	17
35X12.50R20LT	121Q	E	003812	BW	8.5-11.0	10.0	34.8	12.5	21	603	72.1	17
33X12.50R20LT	114Q	E	003813	BW	8.5-11.0	10.0	32.8	12.5	21	641	68.0	17
22" RIM DIAMETER												
37X13.50R22LT	123Q	E	003806	BW	8.5-11.0	11.0	36.8	13.6	21	570	82.2	17
35X12.50R22LT	117Q	E	003814	BW	8.5-11.0	10.0	34.8	12.5	21	603	73.9	17






Firestone

TRANSFORCE™ HT 2

BECAUSE EVERY JOB IS WORTH DOING RIGHT

FEATURES AND BENEFITS

-  All-season performance
-  Delivers solid traction in wet conditions to help reduce the risk of hydroplaning*
-  Tread design provides great chip and tear resistance*

*As compared to the Firestone Transforce HT



1 OPTIMIZED TIRE PROFILE

to help improve uneven wear, even with heavy loads*

2 SAW TOOTH EDGE SIPING

provide biting edges in snow while maintaining block stiffness

3 FULL DEPTH LATERAL SLOTS

provide water evacuation to help reduce the risk of hydroplaning*



SIZE	SERVICE DESCRIPTION SGL/DUAL	LOAD RANGE	ARTICLE NUMBER	SIDEWALL STYLING	APPROVED RIM WIDTHS	MEASURING RIM WIDTH	OVERALL DIAMETER	SECTION WIDTH	TREAD DEPTH (32ND")	REVS PER MILE	WEIGHT LBS
16" RIM DIAMETER											
LT215/85R16	115/112R	E	002758	BW	5.5-7.0	6.0	30.4	8.5	14	685	36.9
LT235/85R16	120/116R	E	002759	BW	6.0-7.5	6.5	31.7	9.3	15	656	39.7
LT225/75R16	115/112R	E	002760	BW	6.0-7.0	6.0	29.3	8.8	14	711	34.7
LT245/75R16	120/116R	E	002761	BW	6.5-8.0	7.0	30.5	9.8	14	684	39.1
LT265/75R16	123/120R	E	002762	BW	7.0-8.0	7.5	31.7	10.5	15	658	44.3
17" RIM DIAMETER											
LT235/80R17	120/117R	E	002766	BW	6.0-7.5	6.5	31.8	9.3	15	655	42.6
LT225/75R17	116/113R	E	002774	BW	6.0-7.5	6.0	30.3	8.8	14	687	36.5
LT245/75R17	121/118R	E	002777	BW	6.5-7.5	7.0	31.5	9.8	14	661	41.0
LT245/70R17	119/116R	E	002767	BW	6.5-8.0	7.0	30.6	9.8	14	682	40.9
LT265/70R17	121/118R	E	002768	OWL	7.0-8.5	8.0	31.7	10.7	15	658	46.7
18" RIM DIAMETER											
LT265/70R18	124/121R	E	002754	OWL	7.0-9.0	8.0	32.6	10.7	15	638	48.9
LT275/70R18	125/122S	E	002778	BW	7.0-8.5	8.0	33.2	11.0	16	628	51.3
LT275/65R18	123/120S	E	002773	OWL	7.5-9.0	8.0	32.1	11.0	16	649	48.9
TRANSFORCE CV											
16" RIM DIAMETER											
215/55R16	97H	XL	008699	BW	6.0-7.5	7.0	25.3	8.9	12	824	25.0
17" RIM DIAMETER											
215/50R17	95H	XL	008698	BW	6.0-7.5	7.0	25.5	8.9	12	817	24.5






Firestone

TRANSFORCE™ AT2

WHEREVER THE JOB IS, DEPEND ON FIRESTONE TO GET YOU THERE

FEATURES AND BENEFITS

-  Strong for on-road/off-road
-  Improved wet performance*
-  Longer-lasting performance



BUILT WITH A CHIP AND TEAR RESISTANT COMPOUND

tough enough to deal with rough road conditions like gravel

DEEPER TREAD FEATURES

improve wet and snow traction

PATTERN FEATURES COMBINED WITH AN INNOVATIVE TREAD-TO-ROAD CONTACT FOOTPRINT

help retain performance for longer over the course of the tire service life



SIZE	SERVICE DESCRIPTION SGL/DUAL	LOAD RANGE	ARTICLE NUMBER	SIDEWALL STYLING	APPROVED RIM WIDTHS	MEASURING RIM WIDTH	OVERALL DIAMETER	SECTION WIDTH	TREAD DEPTH (32ND")	REVS PER MILE	WEIGHT LBS
16" RIM DIAMETER											
LT215/85R16	115/112R	E	000178	BW	5.5-7.0	6.0	30.4	8.5	16	685	36.7
LT235/85R16	120/116R	E	000179	BW	6.0-7.5	6.5	31.7	9.3	17	656	41.3
LT225/75R16	115/112R	E	000180	BW	6.0-7.0	6.0	29.3	8.8	16	711	36.4
LT245/75R16	120/116R	E	000181	BW	6.5-8.0	7.0	30.5	9.8	17	684	41.3
LT265/75R16	123/120R	E	000182	BW	7.0-8.0	7.5	31.7	10.5	17	658	43.5
17" RIM DIAMETER											
LT235/80R17	120/117R	E	000185	BW	6.0-7.5	6.5	31.8	9.3	17	655	41.4
LT225/75R17	116/113R	E	000183	BW	6.0-7.5	6.0	30.3	8.8	16	687	37.8
LT245/75R17	121/118R	E	000184	OWL	6.5-7.5	7.0	31.5	9.8	17	661	43.1
LT245/70R17	119/116R	E	000186	BW	6.5-8.0	7.0	30.6	9.8	17	682	41.0
LT265/70R17	121/118R	E	000187	OWL	7.0-8.5	8.0	31.7	10.7	17	658	45.6
LT285/70R17	121/118R	E	000780	BW	7.5-9.0	8.5	32.8	11.5	18	636	50.1
18" RIM DIAMETER											
LT265/70R18	124/121R	E	000188	BW	7.0-9.0	8.0	32.6	10.7	17	638	49.5
LT275/70R18	125/122R	E	000189	OWL	7.0-8.5	8.0	33.2	11.0	18	628	53.1
LT275/65R18	123/120R	E	000190	OWL	7.5-9.0	8.0	32.1	11.0	16	649	50.7
20" RIM DIAMETER											
LT275/65R20	126/123R	E	000191	BW	7.5-9.5	8.0	34.1	11.0	16	611	51.2
LT265/60R20	121/118R	E	000192	BW	7.5-9.5	8.0	32.5	10.7	15	641	47.0





CAR



MINIVAN

STUDDABLE WINTER

Firestone

WINTERFORCE™ 2

BUILT TO KEEP YOU WORKING THROUGH THE WINTER

FEATURES AND BENEFITS



Winter performance and grip you can rely on



Long-lasting performance



Great value



SPECIAL COLD WEATHER COMPOUND, OPEN SHOULDER SLOTS & TREAD DESIGN

provide better grip in wintry conditions vs. an all-season tire

FULL DEPTH TREAD FEATURES

provide long-lasting performance winter after winter

GREAT WINTER PERFORMANCE

certified with the 3-Peak Mountain Snowflake designation and pinned for size #11 studs



SIZE	SERVICE DESCRIPTION	LOAD RANGE	ARTICLE NUMBER	SIDEWALL STYLING	APPROVED RIM WIDTHS	MEASURING RIM WIDTH	OVERALL DIAMETER	SECTION WIDTH	TREAD DEPTH (32ND")	REVS PER MILE	WEIGHT LBS	STUD SIZE
14" RIM DIAMETER												
185/65R14	86S	---	148691	BW	5.0-6.5	5.5	23.5	7.4	12	888	19.1	11
185/60R14	82S	---	148674	BW	5.0-6.5	5.5	22.8	7.4	12	915	18.8	11
15" RIM DIAMETER												
P205/75R15	97S	---	148980	BW	5.0-7.0	5.5	27.1	8.0	12	768	22.1	11
205/70R15	96S	---	148963	BW	5.0-7.0	6.0	26.3	8.2	12	791	21.2	11
215/70R15	98S	---	149048	BW	5.5-7.0	6.5	26.9	8.7	12	775	26.5	11
175/65R15	84S	---	003849	BW	5.0-6.0	5.0	24.0	7.0	12	869	16.8	11
185/65R15	88S	---	148844	BW	5.0-6.5	5.5	24.5	7.4	12	852	20.4	11
195/65R15	91S	---	148895	BW	5.5-7.0	6.0	25.0	7.9	12	833	25.1	11
205/65R15	94S	---	148929	BW	5.5-7.5	6.0	25.5	8.2	12	818	18.7	11
185/60R15	84S	---	148827	BW	5.0-6.5	5.5	23.7	7.4	12	878	17.5	11
195/60R15	88S	---	148878	BW	5.5-7.0	6.0	24.2	7.9	12	860	23.1	11
16" RIM DIAMETER												
205/65R16	95S	---	003844	BW	5.5-7.5	6.0	26.5	8.2	12	787	20.9	11
225/65R16	100S	---	003848	BW	6.0-8.0	6.5	27.5	9.0	12	758	25.6	11
205/60R16	92S	---	149099	BW	5.5-7.5	6.0	25.7	8.2	12	812	21.7	11
215/60R16	95S	---	149133	BW	6.0-7.5	6.5	26.1	8.7	12	797	23.2	11
225/60R16	98S	---	149184	BW	6.0-8.0	6.5	26.6	9.0	12	783	24.3	11
235/60R16	100S	---	149201	BW	6.5-8.5	7.0	27.1	9.5	12	769	28.0	11
205/55R16	91S	---	149082	BW	5.5-7.5	6.5	24.9	8.4	12	837	23.1	11
215/55R16	93S	---	149116	BW	6.0-7.5	7.0	25.3	8.9	12	824	20.2	11
195/50R16	84S	---	008666	BW	5.5-7.0	6.0	23.7	7.9	12	879	18.0	11
205/50R16	87S	---	149065	BW	5.5-7.5	6.5	24.1	8.4	12	865	20.5	11
17" RIM DIAMETER												
215/65R17	99S	---	149252	BW	6.0-7.5	6.5	28.0	8.7	12	743	24.0	11
215/55R17	94S	---	149235	BW	6.0-7.5	7.0	26.3	8.9	12	792	21.8	11
225/55R17	97S	---	149286	BW	6.0-8.0	7.0	26.8	9.2	12	778	23.0	11
235/55R17	99S	---	149320	BW	6.5-8.5	7.5	27.2	9.7	12	767	25.6	11
215/50R17	95S	XL	003852	BW	6.0-7.5	7.0	25.5	8.9	12	817	23.5	11
225/50R17	94S	---	149269	BW	6.0-8.0	7.0	25.9	9.2	12	804	22.7	11
215/45R17	91S	XL	009474	BW	---	---	---	0.0	12	---	24.8	11
18" RIM DIAMETER												
225/60R18	100S	---	149337	BW	6.0-8.0	6.5	28.6	9.0	12	728	27.3	11





Firestone

WINTERFORCE™ 2 UV

BUILT TO KEEP YOU WORKING THROUGH THE WINTER

FEATURES AND BENEFITS

- Winter performance and grip you can rely on
- Long-lasting performance
- Great value



SPECIAL COLD WEATHER COMPOUND, OPEN SHOULDER SLOTS & TREAD DESIGN

provide better grip in wintry conditions vs. an all-season tire

FULL DEPTH TREAD FEATURES

provide long-lasting performance winter after winter

GREAT WINTER PERFORMANCE

certified with the 3-Peak Mountain Snowflake designation and pinned for size #11 studs



SIZE	SERVICE DESCRIPTION	LOAD RANGE	ARTICLE NUMBER	SIDEWALL STYLING	APPROVED RIM WIDTHS	MEASURING RIM WIDTH	OVERALL DIAMETER	SECTION WIDTH	TREAD DEPTH (32ND")	REVS PER MILE	WEIGHT LBS	STUD SIZE
15" RIM DIAMETER												
P215/75R15	100S	---	148368	BW	5.5-7.0	6.0	27.7	8.5	12	753	24.6	11
P225/75R15	102S	---	148419	BW	6.0-7.5	6.0	28.3	8.8	12	736	26.1	11
P235/75R15	108S	XL	148470	BW	6.0-8.0	6.5	28.9	9.3	12	722	30.8	11
P265/75R15	112S	---	148606	BW	7.0-9.0	7.5	30.7	10.5	12	679	34.6	11
16" RIM DIAMETER												
P225/75R16	104S	---	148436	BW	6.0-7.5	6.0	29.3	8.8	12	711	27.8	11
P245/75R16	109S	---	148572	BW	6.5-8.0	7.0	30.5	9.8	12	684	35.6	11
P265/75R16	114S	---	003454	BW	7.0-9.0	7.5	31.7	10.5	12	658	37.2	11
215/70R16	100S	---	148232	BW	5.5-7.0	6.5	27.9	8.7	12	747	25.0	11
225/70R16	103S	---	148266	BW	6.0-7.5	6.5	28.4	9.0	12	733	26.9	11
P235/70R16	104S	---	148453	BW	6.0-8.0	7.0	29.0	9.5	12	719	28.8	11
P245/70R16	106S	---	148521	BW	6.5-8.0	7.0	29.5	9.8	12	705	34.2	11
P255/70R16	109S	---	148589	BW	6.5-8.5	7.5	30.1	10.2	12	693	34.8	11
265/70R16	112S	---	148317	BW	7.0-9.0	8.0	30.6	10.7	12	680	36.6	11
215/65R16	98S	---	148215	BW	6.0-7.5	6.5	27.0	8.7	12	771	24.5	11
235/65R16	103S	---	008653	BW	6.5-8.5	7.0	28.0	9.5	12	743	32.4	11
17" RIM DIAMETER												
P245/70R17	108S	---	148538	BW	6.5-8.0	7.0	30.6	9.8	12	682	34.3	11
265/70R17	115S	---	148351	BW	7.0-9.0	8.0	31.7	10.7	12	658	38.8	11
225/65R17	102S	---	148249	BW	6.0-8.0	6.5	28.5	9.0	12	731	27.4	11
235/65R17	104S	---	148300	BW	6.5-8.5	7.0	29.1	9.5	12	717	29.8	11
P245/65R17	105S	---	148487	BW	7.0-8.5	7.0	29.5	9.8	12	705	32.5	11
215/60R17	96S	---	003855	BW	6.0-7.5	6.5	27.2	8.7	12	767	24.3	11
235/60R17	102S	---	003856	BW	6.5-8.5	7.0	28.1	9.5	12	741	26.3	11
18" RIM DIAMETER												
P275/65R18	114S	---	003854	BW	7.5-9.5	8.0	32.1	11.0	12	649	39.7	11
265/60R18	110S	---	003857	BW	7.5-9.5	8.0	30.5	10.7	12	683	34.5	11
235/55R18	100S	---	003853	BW	6.5-8.5	7.5	28.2	9.7	12	740	27.4	11





STUDDABLE WINTER

Firestone

WINTERFORCE™ LT

PATENTED TREAD TO TAME WINTER

FEATURES AND BENEFITS



Delivers solid traction in snow, wet or icy conditions



Directional tread design provides a comfortable ride



Winter tire limited warranty*



HIGH SIPE DENSITY BITING EDGES

provide additional traction in snow, wet and ice conditions

STUD PINS

help promote solid ice traction when installed with optional studs

Stud size #15

DIRECTIONAL TREAD PATTERN

helps provide traction with a quiet, comfortable ride



SIZE	SERVICE DESCRIPTION SGL/DUAL	LOAD RANGE	ARTICLE NUMBER	SIDEWALL STYLING	APPROVED RIM WIDTHS	MEASURING RIM WIDTH	OVERALL DIAMETER	SECTION WIDTH	TREAD DEPTH (32ND")	REVS PER MILE	WEIGHT LBS	STUD SIZE
16" RIM DIAMETER												
LT215/85R16	115/112R	E	246488	BW	5.5-7.0	6.0	30.4	8.5	16	681	36.6	15
LT235/85R16	120/116R	E	246318	BW	6.0-7.5	6.5	31.7	9.3	17	653	42.4	15
LT225/75R16	115/112R	E	246250	BW	6.0-7.0	6.0	29.3	8.8	16	706	37.2	15
LT245/75R16	120/116R	E	246267	BW	6.5-8.0	7.0	30.5	9.8	17	679	42.9	15
LT265/75R16	123/120R	E	246284	BW	7.0-8.0	7.5	31.7	10.5	17	653	46.4	15
LT285/75R16	126/123R	E	246386	BW	7.5-9.0	8.0	32.8	11.3	19	629	53.8	15
17" RIM DIAMETER												
LT235/80R17	120/117R	E	246369	BW	6.0-7.5	6.5	31.8	9.3	17	651	42.8	15
LT225/75R17	116/113R	E	246420	BW	6.0-7.5	6.0	30.3	8.8	16	681	40.0	15
LT245/75R17	121/118R	E	246335	BW	6.5-7.5	7.0	31.5	9.8	17	657	44.4	15
LT255/75R17	111/108R	C	232973	BW	6.5-8.5	7.0	32.1	10.0	17	646	42.4	15
LT245/70R17	119/116R	E	246454	BW	6.5-8.0	7.0	30.6	9.8	17	679	45.6	15
LT265/70R17	121/118R	E	246471	BW	7.0-8.5	8.0	31.7	10.7	18	653	49.9	15
18" RIM DIAMETER												
LT275/70R18	125/122R	E	246403	BW	7.0-8.5	8.0	33.2	11.0	19	624	53.8	15
LT275/65R18	123/120R	E	246437	BW	7.5-9.0	8.0	32.1	11.0	19	645	52.2	15
20" RIM DIAMETER												
LT275/65R20	126/123R	E	232871	BW	7.5-9.5	8.0	34.1	11.0	18	611	57.3	15
WINTERFORCE CV												
16" RIM DIAMETER												
215/55R16	97R	XL	008697	BW	6.0-7.5	7.0	25.3	8.9	12	824	25.0	STUDLESS
17" RIM DIAMETER												
215/50R17	95R	XL	008696	BW	6.0-7.5	7.0	25.5	8.9	12	817	25.3	STUDLESS

