



Yokohama Tire Corporation is the North American arm of Yokohama Rubber Co. Ltd., a global manufacturer of premium tires since 1917.

Headquartered in Southern California, we are honored to be ranked among the most elite tire manufacturers in the world, engineering products for passenger cars and commercial trucks. With our plant in Mississippi and production facility in Virginia, we proudly make many of our products right here in the USA.

Yokohama has always been synonymous with advanced tire technology. Our core focus on technological advancements has enabled us to pioneer numerous groundbreaking innovations and industry firsts. We were the first to introduce asymmetric tread design to the United States and the first to engineer products using nanotechnology.

We are continually committed to leveraging our technological strength to improve tire performance, and we are always dedicated to environmental protection.



- 1 / Product Families
- 2 / Performance Continuums
- 3 / Programs
- 4 / Definitions

REPLACEMENT

ADVAN

Ultra-High Performance

- 5 / ADVAN A052
- 6 / ADVAN Neova AD08R
- 7 / ADVAN Sport V105
- 9 / ADVAN Apex
- 11 / ADVAN Sport ZPS
- 12 / Yokohama A-008P
- 13 / ADVAN Fleva V701
- 14 / ADVAN Sport A/S+

AVID

Grand Performance

- 16 / AVID ENVigor ZPS

Grand Touring

- 17 / AVID Ascend GT

Passenger/Touring

- 19 / AVID Ascend LX
- 20 / AVID Touring-S

PARADA

High Performance SUV, Crossover

- 21 / PARADA Spec-X

GEOLANDAR

Trucks, SUVs and Crossovers

- 22 / GEOLANDAR CV G058
- 23 / GEOLANDAR X-CV
- 24 / GEOLANDAR H/T G056
- 26 / GEOLANDAR A/T G015
- 28 / GEOLANDAR X-AT
- 30 / GEOLANDAR M/T G003
- 32 / GEOLANDAR X-MT

WINTER TIRES

- 34 / BluEarth Winter V906 / V906 SUV
- 35 / iceGUARD iG53
- 36 / iceGUARD G075

LIGHT TRUCK COMMERCIAL

- 38 / Y356
- TY213B

ORIGINAL EQUIPMENT

- 39 / OE REFERENCE MANUAL

HIGH PERFORMANCE, PASSENGER & LIGHT TRUCK

- 42 / ADVAN A048
- ADVAN A10A / A10F
- ADVAN A11A

- 43 / ADVAN A13C
- ADVAN A83A
- ADVAN A83B
- 44 / ADVAN Neova AD07
- ADVAN Sport V103
- 45 / ADVAN Sport V105
- 46 / ADVAN Sport ZPS (V105)
- ADVAN Sport V107
- 47 / ADVAN S.T. V802
- AVID S30B / S30D
- AVID S33
- 48 / AVID S33B
- AVID S33D
- AVID S34B
- 49 / AVID S34D
- AVID S34F / S34FA / S34FV
- AVID S34M
- 50 / AVID S34NV / S34PV
- AVID S34P
- AVID S34RV / RY
- 51 / AVID GT S35
- AVID GT S35A
- AVID GT S35B / S35C
- 52 / BluEarth AE50
- BluEarth S34BZ / S34TZ
- C.drive2 / C.drive2 ZPS
- 53 / GEOLANDAR G038G
- GEOLANDAR G055/G055G
- GEOLANDAR SUV G055E
- 54 / GEOLANDAR H/T G056B
- GEOLANDAR G91A / G91AV
- GEOLANDAR G91F / G91FV
- 55 / GEOLANDAR G91HV
- GEOLANDAR G92C
- GEOLANDAR G95A
- 56 / GEOLANDAR G96B
- GEOLANDAR A/T G015
- GEOLANDAR H/T G033
- 57 / GEOLANDAR X-CV G057
- GEOLANDAR X-CV G99A

LIGHT TRUCK COMMERCIAL

- 57 / RY103
- 58 / TY213A
- TY213B
- TY287
- 59 / TY303A
- Y742S

PRODUCT FAMILIES

From commuting in the family sedan to taking on the trail in your 4x4, there's a Yokohama that's perfect for everyone.

ADVAN®

ADVAN® FAMILY

Everything we've learned from engineering tires for the racetrack has been rolled into our line of ultra-high performance products.

AVID® FAMILY

Innovation for the everyday. Our line of AVID® products offers reliable all-season performance, superior comfort, and most importantly: they're built to last.

AVID®

GEOLANDAR®

GEOLANDAR® FAMILY

Tough, durable and long-lasting, these tires are built for wherever life takes you. On-road or off, there's a GEOLANDAR® perfect for your truck, SUV or crossover.

WINTER PRODUCTS

Winter driving can be unpredictable, which is why we've built advanced traction technologies into each of our winter tires.

iceGUARD® **BluEarth®**

YOKOHAMA TIRE PERFORMANCE CONTINUUMS

**PASSENGER/
PERFORMANCE** ↑

PERFORMANCE

ADVAN A052[®]

ADVAN NEOVA[®] AD08R

ADVAN SPORT[®] V105

ADVAN APEX[®]

ADVAN SPORT[®] ZPS

YOKOHAMA A-008P

ADVAN FLEVA[®] V701

ADVAN SPORT[®] A/S+

AVID ENVIGOR[®] ZPS

AVID ASCEND GT[®]

AVID ASCEND LX[®]

AVID TOURING-S[®]

TOURING

**LIGHT
TRUCK** ↑

OFF-ROAD

GEOLANDAR X-MT[®]

GEOLANDAR M/T[®] G003

GEOLANDAR X-AT[®]

GEOLANDAR[®] A/T G015

GEOLANDAR[®] H/T G056

GEOLANDAR CV[®] G058

GEOLANDAR X-CV[®]

PARADA SPEC-X[®]

HIGHWAY

**WINTER
TIRE** ↑

PERFORMANCE

BLUEEARTH WINTER[®] V906
BLUEEARTH WINTER[®] V906 SUV

ICEGUARD[®] iG53

ICEGUARD[®] G075

UTILITY

PROGRAMS

4 PERFORMANCE PROGRAM

The 4 Performance Program assists dealers in fulfilling the needs of customers who are looking to purchase ultra-high performance tires. Direct Dealers can place orders for up to four (4) units of the following eligible tires: ADVAN Apex®, ADVAN FLEVA® V701, ADVAN Sport® V105, ADVAN Sport ZPS®, ADVAN Neova® AD08R, ADVAN Sport® A/S+ and ADVAN A052®. A \$15.00 per tire freight charge will be applied at the time the order is placed. Shipments under this program can be delivered to any authorized ship-to location or authorized drop-ship location. Please clarify at the time of order that your tires qualify under the 4 Performance Program.

The O.E. Ship Three Program allows dealers to service Yokohama customers who are trying to match the O.E. tires on their car. Direct Dealers are eligible to receive up to three (3) tires of a designated O.E. part number, freight prepaid within 72 hours. To place an order, Direct Dealers should contact their Yokohama Customer Service Representative and identify the order as an O.E. Ship Three. A fee of \$15.00 per eligible tire will be applied and the order will then be shipped and should be received within 72 hours.

O.E. SHIP THREE



Yokohama's Performance Promise guarantees customers will be happy with their new tires. If within 30 days they are not completely satisfied, tires can be returned to the dealership of purchase along with the original sales receipt and Yokohama will refund the full purchase price. Offer applies only to the original purchased set of four (select) Yokohama tires. See Yokohama Warranty Claims Procedure Manual for details.

BluEarth® is an ecologically-friendly series of tires from Yokohama that pursues the highest standards of performance, while striving to protect the global environment.



M+S

This mark is commonly found on "all season" tires. In several formats, the letters "M" and "S" indicate the tire is intended for limited mud and snow service. Other formats include: "MS," "M/S," or "M&S."

This mark is commonly found on dedicated winter/snow tires. Tires that meet the USTMA definition for passenger and light truck tires for use in severe snow conditions are marked on at least one sidewall with the letters "M" and "S" plus a pictograph of a mountain with a snowflake, as shown here.



Sidewall	BW	Blackwall
	OWL	Outlined White Letters
Load Index	SL	Standard Load
	XL	Extra Load or Reinforced Load
UTQG	Treadwear/Traction/Temperature	

LEGEND

ADVAN A052®



ULTRA-HIGH PERFORMANCE Performance Cars | Competition

Nothing rewards your passion for extreme grip and high speeds like the race-ready ADVAN A052®.

FEATURES AND BENEFITS



ULTIMATE HANDLING

Ultra-high turn up and lower belt angle for ultimate handling on and off the track.



MAXIMUM GRIP

Dedicated motorsports-inspired compound for maximum wet and dry grip on and off the track.



RACE READY

Engineered to dominate in sanctioned competition categories requiring a 200 UTQG tire.



CONSISTENT PERFORMANCE

Tread design delivers consistent contact to the road while minimizing localized heat.



TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
185/55R14 80V	110105285	SL	200/A/A	15.2	6.0	5.0 - 6.5	7.6	22.0	6.7	7	10.1	945	992@51
195/50R15 86V	110105269	XL	200/A/A	17.2	6.0	5.5 - 7.0	8.0	22.6	7.2	7	10.5	917	1169@50
195/55R15 89V	110105270	XL	200/A/A	18.1	6.0	5.5 - 7.0	8.0	23.4	7.2	7	10.7	890	1279@50
205/50R15 89V	110105271	XL	200/A/A	18.7	6.5	5.5 - 7.5	8.5	23.0	7.6	7	10.6	902	1279@50
225/50R15 95V	110105272	XL	200/A/A	20.3	7.0	6.0 - 8.0	9.2	23.9	8.3	7	11.0	869	1521@50
195/45R16 84W	110105273	XL	200/A/A	17.0	6.5	6.0 - 7.5	7.8	22.8	7.0	7	10.7	911	1103@50
195/50R16 88W	110105274	XL	200/A/A	18.5	6.0	5.5 - 7.0	7.9	23.6	7.2	7	11.0	879	1235@50
205/50R16 91W	110115220	XL	200/A/A	19.6	6.5	5.5 - 7.5	8.4	24.2	7.6	7	11.2	858	1356@50
205/55R16 94W	110115221	XL	200/A/A	20.9	6.5	5.5 - 7.5	8.4	25.0	7.6	7	11.5	831	1477@50
225/45R16 93W	110115223	XL	200/A/A	19.8	7.5	7.0 - 8.5	8.9	24.1	8.3	7	11.1	863	1433@50
225/50R16 96W	110115222	XL	200/A/A	21.6	7.0	6.0 - 8.0	9.1	25.0	8.3	7	11.5	831	1566@50
245/45R16 94W	110105275	SL	200/A/A	21.4	8.0	7.5 - 9.0	9.8	24.6	8.9	7	11.3	845	1477@51
205/40R17 84W	110105276	XL	200/A/A	18.5	7.5	7.0 - 8.0	8.5	23.4	7.6	7	11.0	888	1103@50
205/45R17 88W	110115224	XL	200/A/A	19.4	7.0	6.5 - 7.5	8.2	24.3	7.6	7	11.4	854	1235@50
215/40R17 87W	110105277	XL	200/A/A	19.6	7.5	7.0 - 8.5	8.8	23.7	8.0	7	11.1	878	1202@50
215/45R17 91W	110115206	XL	200/A/A	20.3	7.0	7.0 - 8.5	8.4	24.7	7.8	7	11.5	840	1356@50
225/45R17 94W	110115207	XL	200/A/A	20.9	7.5	7.0 - 8.5	8.9	25.1	8.3	7	11.7	828	1477@50
235/45R17 97W	110115208	XL	200/A/A	22.3	8.0	7.5 - 9.0	9.3	25.5	8.7	7	11.8	815	1610@50
245/40R17 95W	110105278	XL	200/A/A	22.1	8.5	8.0 - 9.5	9.9	24.7	9.2	7	11.5	840	1521@50
255/40R17 98W	110115209	XL	200/A/A	19.4	9.0	8.5 - 10.0	10.2	25.2	9.6	7	11.7	826	1654@50
225/35R18 87Y	110105279	XL	200/A/A	20.7	8.0	7.5 - 9.0	9.1	24.2	8.4	7	11.4	859	1202@50
225/40R18 92Y	110115210	XL	200/A/A	21.6	8.0	8.5 - 10.0	9.1	25.1	8.4	7	11.8	827	1389@50
235/40R18 95Y	110115211	XL	200/A/A	22.7	8.5	8.0 - 9.5	9.5	25.5	8.8	7	11.9	815	1521@50
235/45R18 98Y	110105280	XL	200/A/A	24.0	8.0	7.5 - 9.0	9.5	26.3	8.7	7	12.2	789	1654@50
245/40R18 97Y	110115212	XL	200/A/A	24.0	8.5	8.0 - 9.5	9.8	25.8	9.2	7	12.0	805	1610@50
255/35R18 94Y	110115213	XL	200/A/A	23.6	9.0	8.5 - 10.0	10.2	25.1	9.6	7	11.8	828	1477@50
255/40R18 99Y	110115214	XL	200/A/A	24.9	9.0	8.5 - 10.0	10.3	26.1	9.6	7	12.2	795	1709@50
265/35R18 97Y	110115215	XL	200/A/A	24.5	9.5	9.0 - 10.5	10.6	25.4	10.0	7	11.9	818	1610@50
265/40R18 101Y	110115216	XL	200/A/A	25.6	9.5	9.0 - 10.5	10.7	26.5	10.0	7	12.3	785	1819@50
265/45R18 104Y	110105281	XL	200/A/A	26.7	9.0	8.5 - 10.0	10.6	27.4	9.7	7	12.7	757	1985@50
275/40R18 103Y	110105282	XL	200/A/A	26.2	9.5	9.0 - 11.0	11.0	26.7	10.3	7	12.4	778	1929@50
295/30R18 98Y	110115217	XL	200/A/A	26.2	10.5	10.0 - 11.0	11.8	25.1	11.2	7	11.8	828	1654@50
295/35R18 103Y	110115218	XL	200/A/A	27.6	10.5	10.0 - 11.5	11.8	26.2	11.2	7	12.2	792	1929@50
315/30R18 98Y	110115219	SL	200/A/A	28.0	11.0	10.5 - 11.5	12.6	25.6	12.0	7	11.9	813	1654@51
245/35ZR19 93Y	110115225	XL	200/A/A	23.4	8.5	8.0 - 9.5	9.7	25.7	9.1	7	12.1	807	1433@50
235/40ZR19 (96Y)	110115229	XL	200/A/A	24.0	8.5	8.0 - 9.5	9.5	26.4	8.8	7	12.4	786	1565@50
255/35ZR19 (96Y)	110115227	XL	200/A/A	24.8	9.0	8.5 - 10.0	10.2	26.0	9.6	7	12.2	799	1565@50
265/40ZR19 (102Y)	110115228	XL	200/A/A	26.8	9.5	9.0 - 10.5	10.6	27.4	10.0	7	12.8	757	1874@50
275/35ZR19 (100Y)	110115226	XL	200/A/A	25.9	9.5	9.0 - 11.0	10.8	26.6	10.3	7	12.5	781	1764@50
295/35R19 104Y	110115233	XL	200/A/A	29.6	10.5	10.0 - 11.5	11.8	27.2	11.2	7	12.7	765	1984@50
245/30ZR20 (90Y)	110115231	XL	200/A/A	23.0	8.5	8.0 - 9.0	9.6	25.8	9.1	7	12.3	804	1323@50
245/35ZR20 (95Y)	110115232	XL	200/A/A	24.7	8.5	8.0 - 9.5	9.6	26.8	9.1	7	12.6	776	1521@50
255/40ZR20 101Y	110105283	XL	200/A/A	26.7	9.0	8.5 - 10.0	10.4	27.9	9.6	7	13.1	745	1819@50
285/35ZR20 104Y	110105284	XL	200/A/A	29.1	10.0	9.5 - 11.0	11.6	28.0	10.9	7	13.1	743	1985@50
295/30R20 101Y	110115230	XL	200/A/A	28.5	10.5	10.0 - 11.0	11.7	27.0	11.2	7	12.7	768	1819@50

ULTRA-HIGH PERFORMANCE Performance Cars

The ultimate street sport summer tire with unprecedented grip and consistent performance.

FEATURES AND BENEFITS



ULTIMATE HANDLING

Unique construction provides fast and responsive handling for street or track.



MAXIMUM GRIP

Motorsports-derived compound for maximum starting, stopping and turning grip.



WET TRACTION

Aggressive directional design provides powerful grip in wet.



CONSISTENT PERFORMANCE

Lap times stay fast throughout the life of the tire for maximum enjoyment of track days.



TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
205/50R15 86V	110108102	SL	200/AA/A	20.1	6.5	5.5 - 7.5	8.4	23.0	7.7	9	10.6	902	1168@51
205/55R16 91V	110108106	SL	200/AA/A	20.9	6.5	5.5 - 7.5	8.4	24.8	7.7	9	11.4	838	1356@51
225/50R16 92V	110108109	SL	200/AA/A	23.1	7.0	6.0 - 8.0	9.3	24.7	8.5	9	11.4	840	1389@51
205/45R17 84W	110108110	SL	200/AA/A	21.4	7.0	6.5 - 7.5	8.2	24.1	7.7	9	11.3	861	1102@51
205/50R17 89W	110108111	SL	200/AA/A	22.0	6.5	5.5 - 7.5	8.4	25.0	7.7	9	11.6	831	1279@51
215/40R17 83W	110108112	SL	200/AA/A	21.2	7.5	7.0 - 8.5	8.6	23.7	8.2	9	11.1	877	1074@51
215/45R17 87W	110108113	SL	200/AA/A	22.5	7.0	7.0 - 8.0	8.5	24.5	8.0	9	11.4	847	1201@51
225/45R17 91W	110108114	SL	200/AA/A	23.6	7.5	7.0 - 8.5	8.9	24.8	8.5	9	11.6	836	1356@51
235/40R17 90W	110108115	SL	200/AA/A	24.7	8.5	8.0 - 9.5	9.6	24.3	9.1	10	11.4	854	1323@51
235/45R17 94W	110108116	SL	200/AA/A	25.1	8.0	7.5 - 9.0	9.4	25.2	8.9	10	11.7	824	1477@51
245/40R17 91W	110108117	SL	200/AA/A	25.8	8.5	8.0 - 9.5	9.8	24.6	9.4	10	11.5	844	1356@51
245/45R17 95W	110108118	SL	200/AA/A	26.4	8.0	7.5 - 9.0	9.6	25.6	9.1	10	11.8	813	1521@51
255/40R17 94W	110108119	SL	200/AA/A	26.5	9.0	8.5 - 10.0	10.4	24.9	9.8	10	11.6	834	1477@51
215/45R18 89W	110108121	SL	200/AA/A	23.1	7.0	7.0 - 8.0	8.5	25.6	8.0	9	11.9	813	1279@51
225/40R18 88W	110108122	SL	200/AA/A	23.4	8.0	7.5 - 9.0	9.1	25.0	8.7	9	11.7	831	1235@51
225/45R18 91W	110108123	SL	200/AA/A	24.7	7.5	7.0 - 8.5	8.9	25.8	8.5	9	12.1	804	1356@51
235/40R18 91W	110108124	SL	200/AA/A	25.1	8.5	8.0 - 9.5	9.6	25.3	9.1	10	11.9	821	1356@51
245/40R18 93W	110108125	SL	200/AA/A	26.7	8.5	8.0 - 9.5	9.8	25.6	9.4	10	12.0	811	1433@51
245/45R18 96W	110108126	SL	200/AA/A	27.8	8.0	7.5 - 9.0	9.6	26.6	9.1	10	12.3	782	1565@51
255/35R18 90W	110108127	SL	200/AA/A	26.0	9.0	8.5 - 10.0	10.1	25.0	9.9	10	11.7	831	1323@51
255/40R18 95W	110108128	SL	200/AA/A	27.6	9.0	8.5 - 10.0	10.2	26.1	9.8	10	12.1	797	1521@51
265/35R18 93W	110108129	SL	200/AA/A	27.8	9.5	9.0 - 10.5	10.6	25.3	10.3	10	11.9	821	1433@51
265/40R18 101W	110108130	XL	200/AA/A	29.1	9.5	9.0 - 10.5	10.6	26.3	10.2	10	12.3	789	1819@50
285/30R18 93W	110108131	SL	200/AA/A	26.8	10.0	9.5 - 10.5	11.2	24.8	9.9	10	11.6	839	1433@51
295/30R18 94W	110108132	SL	200/AA/A	28.9	10.5	10.0 - 11.0	11.7	25.0	11.5	10	11.7	831	1477@51
225/35R19 88W	110108133	XL	200/AA/A	23.1	8.0	7.5 - 9.0	9.0	25.3	8.7	9	11.9	822	1235@50
235/35R19 87W	110108134	SL	200/AA/A	24.7	8.5	8.0 - 9.5	9.4	25.4	9.1	10	12.0	817	1201@51
245/35R19 89W	110108135	SL	200/AA/A	25.1	8.5	8.0 - 9.5	9.6	25.8	9.4	10	12.1	806	1279@51
245/40R19 94W	110108136	SL	200/AA/A	27.5	8.5	8.0 - 9.5	9.7	26.7	9.4	10	12.5	778	1477@51
255/30R19 91W	110108137	XL	200/AA/A	25.6	9.0	8.5 - 9.5	10.1	25.2	9.9	10	11.9	826	1356@50
255/35R19 92W	110108138	SL	200/AA/A	27.1	9.0	8.5 - 10.0	10.1	26.1	9.9	10	12.3	797	1389@51
265/30R19 89W	110108139	SL	200/AA/A	26.7	9.5	9.0 - 10.0	10.6	25.4	10.3	10	12.0	819	1279@51
265/35R19 94W	110108140	SL	200/AA/A	28.4	9.5	9.0 - 10.5	10.5	26.3	10.2	10	12.4	789	1477@51
275/30R19 92W	110108141	SL	200/AA/A	27.6	9.5	9.0 - 10.0	10.7	25.6	10.6	10	12.1	813	1389@51
275/35R19 96W	110108142	SL	200/AA/A	29.6	9.5	9.0 - 11.0	10.9	26.6	10.6	10	12.5	782	1565@51
295/30R19 100W	110108143	XL	200/AA/A	30.0	10.5	10.0 - 11.0	11.6	26.0	11.5	10	12.2	798	1764@50
305/30R19 102W	110108144	XL	200/AA/A	31.3	11.0	10.5 - 11.5	12.2	26.3	11.8	10	12.3	790	1874@50

ULTRA-HIGH PERFORMANCE Performance Cars

A tire you can trust to do it all with maximum grip, comfort and tread life.

FEATURES AND BENEFITS



O.E. HANDLING

Matrix rayon body ply construction for precise handling when you need it.



O.E. GRIP

Sport compound with asymmetric tread design for tremendous wet and dry grip.



QUIET RIDE

Specially designed multi-pitch sipes provide a quiet ride.



LONG TREAD LIFE

A stable, solid rib design and new tread compound provide longer treadwear.



Also See Original Equipment Fitments on Page 46

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
195/50R16 84V	110110603	SL	280/AA/A	18.4	6.0	5.5-7.0	7.7	23.7	6.1	9	11.0	875	1102@51
205/55ZR17 91Y	110110583	SL	240/AA/A	22.5	6.5	5.5-7.5	8.4	25.8	6.9	10	11.9	804	1356@51
215/45ZR17 91Y	110110585	XL	240/AA/A	21.0	7.0	7.0-8.0	8.3	24.6	7.0	10	11.5	843	1356@50
225/45R17 91W	110110516	SL	240/AA/A	21.1	7.5	7.0-8.5	8.9	25.0	7.7	10	11.6	831	1356@51
225/45ZR17 94Y	110110521	XL	240/AA/A	22.6	7.5	7.0-8.5	8.8	24.9	7.6	10	11.6	835	1477@50
225/50R17 94W	110110631	SL	240/AA/A	22.1	7.0	6.0-8.0	9.3	25.9	7.2	10	12.0	801	1477@51
225/55ZR17 101Y	110110597	XL	240/AA/A	25.0	7.0	6.0-8.0	9.1	26.7	7.4	10	12.3	777	1819@50
235/45ZR17 97Y	110110528	XL	240/AA/A	23.6	8.0	7.5-8.5	9.2	25.3	7.9	10	11.7	820	1609@50
235/50ZR17 96Y	110110584	SL	240/AA/A	25.7	7.5	6.5-8.5	9.6	26.3	8.0	10	12.1	791	1566@51
245/40R17 91W	110110517	SL	240/AA/A	23.4	8.5	8.0-9.5	9.9	24.8	8.4	10	11.5	839	1356@51
255/40ZR17 98Y	110110596	XL	240/AA/A	24.4	9.0	8.5-10.0	10.2	25.0	8.8	10	11.6	832	1653@50
215/40ZR18 89Y	110110586	XL	240/AA/A	21.0	7.5	7.0-8.5	8.7	24.7	7.5	10	11.6	840	1279@50
225/40ZR18 92Y	110110530	XL	240/AA/A	22.8	8.0	7.5-9.0	9.1	25.1	7.9	10	11.8	828	1389@50
225/45ZR18 95Y	110110527	XL	240/AA/A	23.6	7.5	7.0-8.5	8.8	26.0	7.6	10	12.1	799	1521@50
225/45R18 95Y	110110632	XL	240/AA/A	21.9	7.5	7.0-8.5	8.9	25.9	7.4	10	12.1	801	1521@50
235/40ZR18 (95Y)	110110541	XL	240/AA/A	23.6	8.5	8.0-9.5	9.5	25.4	8.2	10	11.9	818	1521@50
235/45ZR18 (98Y)	110110561	XL	240/AA/A	24.4	8.0	7.5-9.0	9.3	26.3	7.9	10	12.2	789	1653@50
235/50ZR18 101Y	110110602	XL	240/AA/A	26.7	7.5	6.5-8.5	9.5	27.2	8.0	10	12.6	763	1819@50
235/60R18 103V	110110598	SL	240/AA/A	30.0	7.0	6.5-8.5	9.6	29.3	7.2	10	13.4	709	1929@51
245/35ZR18 92Y	110110587	XL	240/AA/A	23.1	8.5	8.0-9.5	9.8	24.8	8.5	10	11.7	837	1389@50
245/40R18 97Y	110110633	XL	240/AA/A	23.0	8.5	8.0-9.5	9.9	25.7	8.3	10	12.0	808	1609@50
245/40ZR18 97Y	110110522	XL	240/AA/A	23.9	8.5	8.0-9.5	9.6	25.7	8.3	10	12.0	809	1609@50
245/50ZR18 (104Y)	110110563	XL	240/AA/A	27.4	7.5	7.0-8.5	9.7	27.7	8.1	10	12.8	750	1984@50
255/35ZR18 94Y	110110531	XL	240/AA/A	24.4	9.0	8.5-10.0	10.2	25.0	8.9	10	11.7	829	1477@50
255/40R18 95Y	110110518	SL	240/AA/A	25.2	9.0	8.5-10.0	10.4	26.1	8.4	10	12.1	797	1521@51
255/45ZR18 103Y	110110550	XL	240/AA/A	27.4	8.5	8.0-9.5	9.9	27.1	8.6	10	12.6	766	1929@50
265/45ZR18 (101Y)	110110601	SL	240/AA/A	28.6	9.0	8.5-10.0	10.6	27.3	8.9	10	12.6	761	1819@51
275/35ZR18 (99Y)	110110564	XL	240/AA/A	26.9	9.5	9.0-11.0	10.9	25.6	9.4	10	11.9	813	1709@50
275/45ZR18 (107Y)	110110565	XL	240/AA/A	31.1	9.0	8.5-10.5	10.8	27.8	9.3	10	12.8	747	2149@50
285/35R18 97Y	110110519	SL	240/AA/A	27.6	10.0	9.5-11.0	11.6	25.9	9.6	10	12.1	802	1609@51
225/35ZR19 88Y	110110534	XL	240/AA/A	21.6	8.0	7.5-9.0	9.1	25.2	7.9	10	11.9	823	1235@50
225/40ZR19 (93Y)	110110549	XL	240/AA/A	23.5	8.0	7.5-9.0	9.1	26.2	7.9	10	12.3	793	1433@50
235/35ZR19 (91Y)	110110523	XL	240/AA/A	23.3	8.5	8.0-9.5	9.5	25.5	8.3	10	12.0	815	1356@50
235/40ZR19 (96Y)	110110566	XL	240/AA/A	24.6	8.5	8.0-9.5	9.5	26.5	8.3	10	12.4	785	1565@50
235/40ZR19 (92Y)	110110604	SL	240/AA/A	23.2	8.5	8.0-9.5	9.7	26.4	8.0	9	12.4	786	1389@51
235/45ZR19 95Y	110110600	SL	240/AA/A	25.4	8.0	7.5-9.0	9.3	27.3	7.9	10	12.7	760	1521@51
235/55R19 101V	110110599	SL	240/AA/A	29.3	7.5	6.5-8.5	9.7	29.3	7.3	10	13.5	709	1819@51
245/35ZR19 (93Y)	110110558	XL	240/AA/A	24.3	8.5	8.0-9.5	9.7	25.8	8.5	10	12.2	804	1433@50
245/40ZR19 (98Y)	110110559	XL	240/AA/A	25.8	8.5	8.0-9.5	9.6	26.7	8.3	10	12.5	777	1653@50
245/40ZR19 98Y	110110634	XL	240/AA/A	24.9	8.5	8.0-9.5	10.0	26.8	8.3	10	12.5	776	1653@50
245/45ZR19 98Y	110110533	SL	240/AA/A	26.9	8.0	7.5-9.0	9.4	27.8	8.1	10	12.9	748	1653@51
245/50R19 105W	110133802	XL	240/AA/A	34.4	7.5	7.0-8.5	10.1	28.7	7.9	10	13.3	723	2039@50
255/30ZR19 (91Y)	110110524	XL	240/AA/A	24.0	9.0	8.5-9.5	10.2	25.1	8.9	10	11.9	828	1356@50
255/35ZR19 (96Y)	110110535	XL	240/AA/A	25.5	9.0	8.5-10.0	10.2	26.1	8.9	10	12.3	796	1565@50
255/35ZR19 96Y	110110638	XL	240/AA/A	25.6	9.0	8.5-10.0	10.2	26.0	8.9	10	12.2	798	1565@50
255/40ZR19 (100Y)	110110544	XL	240/AA/A	27.1	9.0	8.5-9.5	10.1	27.2	8.8	10	12.7	765	1764@50
255/45ZR19 (100Y)	110110567	SL	240/AA/A	28.0	8.5	8.0-9.5	9.9	28.0	8.6	10	13.0	741	1764@51
265/30ZR19 (93Y)	110110543	XL	240/AA/A	24.8	9.5	9.0-10.0	10.6	25.4	9.3	10	12.0	819	1433@50
265/35ZR19 (98Y)	110110525	XL	240/AA/A	26.2	9.5	9.0-10.5	10.6	26.3	9.3	10	12.4	789	1653@50

(Continued next page)

ADVAN Sport® V105

(Continued from previous page)

TIRES SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
265/40ZR19 (98Y)	110110605	SL	240/AA/A	27.4	9.5	9.0 - 10.5	10.9	27.3	9.6	9	12.7	760	1653@51
265/40ZR19 (102Y)	110110568	XL	240/AA/A	28.9	9.5	9.0 - 10.5	10.7	27.4	9.3	10	12.8	758	1874@50
275/30ZR19 (96Y)	110110560	XL	240/AA/A	26.7	9.5	9.0 - 10.0	10.8	25.6	9.4	10	12.1	812	1565@50
275/35ZR19 (100Y)	110110569	XL	240/AA/A	27.3	9.5	9.0 - 11.0	10.9	26.6	9.4	10	12.4	782	1764@50
275/35ZR19 100Y	110110635	XL	240/AA/A	29.4	9.5	9.0 - 11.0	11.1	26.6	10.0	10	12.5	781	1764@50
275/40ZR19 (105Y)	110110545	XL	240/AA/A	30.4	9.5	9.0 - 11.0	10.8	27.8	9.4	10	12.9	748	2039@50
275/40ZR19 105Y	110193337	XL	240/A/A	28.2	9.5	9.0 - 11.0	10.8	27.5	9.1	9	12.8	755	2039@50
285/30ZR19 98Y	110110639	XL	240/AA/A	27.8	10.0	9.5 - 10.5	11.3	25.9	10.0	10	12.2	803	1653@50
285/30ZR19 98Y	110110536	XL	240/AA/A	27.9	10.0	9.5 - 10.5	11.3	25.8	10.0	10	12.2	805	1653@50
285/35ZR19 (99Y)	110110595	SL	240/AA/A	29.5	10.0	9.5 - 11.0	11.3	26.8	9.9	10	12.6	775	1709@51
285/40ZR19 (103Y)	110110551	SL	240/AA/A	30.7	10.0	9.5 - 11.0	11.4	28.0	9.9	10	13.0	742	1929@51
285/40ZR19 107Y	110193338	XL	240/A/A	29.5	10.0	9.5 - 11.0	11.4	27.8	9.9	9	12.9	746	2149@50
295/30ZR19 (100Y)	110110526	XL	240/AA/A	28.6	10.5	10.0 - 11.0	11.7	26.1	10.3	10	12.2	797	1764@50
295/35ZR19 (100Y)	110110606	SL	240/AA/A	30.4	10.5	10.0 - 11.5	12.2	27.2	11.0	9	12.7	765	1764@51
295/35ZR19 (104 Y)	110110571	XL	240/AA/A	30.9	10.5	10.0 - 11.5	11.8	27.0	10.3	10	12.6	768	1984@50
305/30ZR19 (102Y)	110110572	XL	240/AA/A	31.0	11.0	10.5 - 11.5	12.3	26.3	10.8	10	12.3	791	1874@50
225/35ZR20 (90Y)	110110547	XL	240/AA/A	23.6	8.0	7.5 - 9.0	9.1	26.3	7.9	10	12.4	791	1323@50
235/35ZR20 (92Y)	110110574	XL	240/AA/A	24.7	8.5	8.0 - 9.5	9.5	26.5	8.3	10	12.5	785	1389@50
245/30ZR20 (90Y)	110110593	XL	240/AA/A	25.3	8.5	8.0 - 9.0	9.8	25.9	8.5	10	12.3	803	1323@50
245/35ZR20 (95Y)	110110594	XL	240/AA/A	25.4	8.5	8.0 - 9.5	9.6	26.8	8.5	10	12.6	776	1521@50
245/35ZR20 95Y	110110636	XL	240/AA/A	26.8	8.5	8.0 - 9.5	9.8	26.7	8.9	10	12.6	778	1521@50
245/40ZR20 (99Y)	110110577	XL	240/AA/A	27.2	8.5	8.0 - 9.5	9.6	27.7	8.3	10	13.0	749	1709@50
245/45R20 103Y	110133805	XL	240/AA/A	29.5	8.0	7.5 - 9.0	9.8	28.7	8.3	10	13.4	724	1929@50
255/30ZR20 (92Y)	110110589	XL	240/AA/A	24.1	9.0	8.5 - 9.5	10.3	26.1	8.9	10	12.4	797	1389@50
255/30R20 (92Y)	110110546	XL	240/AA/A	25.7	9.0	8.5 - 9.5	10.0	26.1	8.9	10	12.4	796	1389@50
255/35ZR20 (97Y)	110110548	XL	240/AA/A	27.2	9.0	8.5 - 10.0	10.1	27.1	8.9	10	12.8	767	1609@50
255/40ZR20 (101Y)	110110556	XL	240/AA/A	27.8	9.0	8.5 - 10.0	10.6	28.2	9.1	10	13.2	737	1819@50
265/30ZR20 (94Y)	110110578	XL	240/AA/A	26.7	9.5	9.0 - 10.0	10.4	26.3	9.3	10	12.5	789	1477@50
265/35ZR20 (99Y)	110110554	XL	240/AA/A	28.4	9.5	9.0 - 10.5	10.6	27.3	9.3	10	12.9	760	1709@50
265/40ZR20 104Y	110110579	XL	240/AA/A	31.0	9.5	9.0 - 10.5	10.6	28.4	9.2	10	13.3	732	1985@50
275/30ZR20 (97Y)	110110580	XL	240/AA/A	27.7	9.5	9.0 - 10.0	10.7	26.6	9.4	10	12.6	782	1609@50
275/30ZR20 97Y	110110637	XL	240/AA/A	28.8	9.5	9.0 - 10.0	11.2	26.4	10.0	10	12.5	786	1609@50
275/40R20 106Y	110133804	XL	240/A/A	30.6	9.5	9.0 - 11.0	11.1	28.7	9.9	10	13.4	724	2094@50
285/25ZR20 (93Y)	110110581	XL	240/AA/A	28.5	10.5	10.5 - 10.5	11.6	25.6	10.4	10	12.2	812	1433@50
285/30ZR20 (99Y)	110110552	XL	240/AA/A	29.6	10.0	9.5 - 10.5	11.3	26.9	9.9	10	12.7	774	1709@50
295/30ZR20 (101Y)	110110553	XL	240/AA/A	30.8	10.5	10.0 - 11.0	11.6	27.1	10.3	10	12.8	767	1819@50
295/35ZR20 (105Y)	110110557	XL	240/AA/A	33.9	10.5	10.0 - 11.5	12.4	28.0	10.7	10	13.1	743	2039@50
275/40R21 107Y	110133807	XL	240/A/A	33.3	9.5	9.0 - 11.0	9.8	29.6	9.8	10	13.9	702	2150@50
295/35R21 107Y	110110588	XL	280/AA/A	31.7	10.5	10.0 - 11.5	11.7	29.1	10.3	10	13.7	714	2149@50
315/35R21 111Y	110133808	XL	240/A/A	36.2	11.0	10.5 - 12.5	11.5	29.6	11.6	10	13.9	701	2403@50
305/35R23 111Y	110110630	XL	240/AA/A	39.3	11.0	10.0 - 12.0	12.2	31.5	10.7	10	14.8	659	2403@50



ULTRA-HIGH PERFORMANCE Performance Cars

An ultra-high performance street tire with big grip for today's popular bigger sizes.

FEATURES AND BENEFITS



PRECISE HANDLING

A strong sidewall and tread deliver precise and immediate cornering response.



MAXIMUM GRIP

A competition-inspired tread design and advanced compound provide confident wet and dry grip.



QUIET RIDE

Rigid construction and optimized groove angles minimize road noise.



LONG TREAD LIFE

Advanced micro-silica compound with rounded rib design extends tread life.



Non-staggered Fits and

Front Position Tires Used in Staggered Fits

2 5 0 0 0 Mile Limited Treadwear Warranty

Rear Position Tires Used in Staggered Fitment Applications

1 2 5 0 0 Mile Limited Treadwear Warranty



TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
225/45R17 94Y	110160101	XL	280/AA/A	22.4	7.5	7.0 - 8.5	8.8	24.9	7.6	9	11.6	833	1477@50
245/40R17 95Y	110160102	XL	280/AA/A	23.3	8.5	8.0 - 9.5	9.6	24.6	8.3	9	11.5	843	1521@50
245/45R17 99Y	110160103	XL	280/AA/A	24.1	8.0	7.5 - 9.0	9.6	25.6	8.1	9	11.9	810	1709@50
225/40R18 92Y	110160104	XL	280/AA/A	22.1	8.0	7.5 - 9.0	9.0	25.1	7.9	9	11.8	827	1389@50
225/45R18 95Y	110160105	XL	280/AA/A	23.4	7.5	7.0 - 8.5	8.8	25.9	7.6	9	12.1	802	1521@50
235/40R18 95Y	110160106	XL	280/AA/A	23.8	8.5	8.0 - 9.5	9.4	25.4	8.2	9	11.9	818	1521@50
235/45R18 98Y	110160107	XL	280/AA/A	24.2	8.0	7.5 - 9.0	9.3	26.4	7.9	9	12.3	788	1653@50
235/50R18 101Y	110160108	XL	280/AA/A	27.2	7.5	6.5 - 8.5	9.5	27.2	8.0	9	12.6	762	1819@50
245/35R18 92Y	110160148	XL	280/AA/A	22.8	8.5	8.0 - 9.5	9.6	24.7	8.5	9	11.6	840	1389@50
245/40R18 97Y	110160109	XL	280/AA/A	25.0	8.5	8.0 - 9.5	9.6	25.8	8.3	9	12.0	805	1609@50
245/45R18 100Y	110160110	XL	280/AA/A	25.6	8.0	7.5 - 9.0	9.4	26.7	8.1	9	12.4	779	1764@50
255/35R18 94Y	110160111	XL	280/AA/A	24.2	9.0	8.5 - 10.0	10.1	25.1	8.9	9	11.8	828	1477@50
255/40R18 99Y	110160112	XL	280/AA/A	26.9	9.0	8.5 - 10.0	10.1	26.1	8.9	9	12.1	797	1709@50
255/45R18 103Y	110160113	XL	280/AA/A	28.0	8.5	8.0 - 9.5	9.9	27.0	8.6	9	12.5	768	1929@50
265/35R18 97Y	110160114	XL	280/AA/A	25.4	9.5	9.0 - 10.5	10.5	25.3	9.3	9	11.9	821	1609@50
275/35R18 99Y	110160147	XL	280/AA/A	26.3	9.5	9.0 - 11.0	10.8	25.4	9.4	9	11.9	817	1709@50
275/40R18 103Y	110160115	XL	280/AA/A	29.3	9.5	9.0 - 11.0	10.8	26.7	9.4	9	12.4	778	1929@50
225/35R19 88Y	110160116	XL	280/AA/A	22.9	8.0	7.5 - 9.0	8.8	25.2	7.9	9	11.9	823	1235@50
225/40R19 93Y	110160117	XL	280/AA/A	23.1	8.0	7.5 - 9.0	9.0	26.1	7.9	9	12.3	795	1433@50
225/45R19 96Y	110160118	XL	280/AA/A	24.5	7.5	7.0 - 8.5	8.7	27.0	7.6	9	12.6	769	1565@50
235/35R19 91Y	110160119	XL	280/AA/A	24.3	8.5	8.0 - 9.5	9.4	25.5	8.3	9	12.0	816	1356@50
235/40R19 96Y	110160120	XL	280/AA/A	24.7	8.5	8.0 - 9.5	9.4	26.5	8.3	9	12.4	784	1565@50
245/35R19 93Y	110160121	XL	280/AA/A	24.0	8.5	8.0 - 9.5	9.6	25.8	8.5	9	12.2	804	1433@50
245/40R19 98Y	110160122	XL	280/AA/A	26.2	8.5	8.0 - 9.5	9.6	26.8	8.5	9	12.6	775	1653@50
245/45R19 102Y	110160123	XL	280/AA/A	26.9	8.0	7.5 - 9.0	9.4	27.7	8.1	9	12.9	750	1874@50
255/30R19 91Y	110160124	XL	280/AA/A	25.0	9.0	8.5 - 9.5	10.1	25.1	8.9	9	11.9	828	1356@50
255/35R19 96Y	110160125	XL	280/AA/A	25.6	9.0	8.5 - 10.0	10.1	26.1	8.9	9	12.2	797	1565@50
255/40R19 100Y	110160126	XL	280/AA/A	28.0	9.0	8.5 - 10.0	10.0	27.1	8.8	9	12.7	766	1764@50
265/35R19 98Y	110160127	XL	280/AA/A	27.1	9.5	9.0 - 10.5	10.6	26.4	9.3	9	12.4	787	1653@50
275/35R19 100Y	110160128	XL	280/AA/A	28.3	9.5	9.0 - 11.0	10.7	26.6	9.4	9	12.4	782	1764@50
275/40R19 105Y	110160151	XL	280/AA/A	31.0	9.5	9.0 - 11.0	10.6	27.8	9.4	9	12.9	748	2039@50
285/30R19 98Y	110160129	XL	280/AA/A	27.3	10.0	9.5 - 10.5	11.3	25.8	9.9	9	12.2	804	1653@50
285/35R19 103Y	110160130	XL	280/AA/A	29.8	10.0	9.5 - 11.0	11.3	26.9	9.9	9	12.6	771	1929@50
295/30R19 100Y	110160152	XL	280/AA/A	28.5	10.5	10.0 - 11.0	11.7	26.0	10.3	9	12.2	799	1764@50
305/30R19 102Y	110160150	XL	280/AA/A	30.9	11.0	10.5 - 11.5	12.2	26.2	10.8	9	12.3	792	1874@50
325/30R19 105Y	110160153	XL	280/AA/A	33.2	11.5	11.0 - 12.0	12.8	26.7	11.3	9	12.5	779	2039@50
235/35R20 92Y	110160131	XL	280/AA/A	26.5	8.5	8.0 - 9.5	9.3	26.5	8.3	9	12.5	784	1389@50
245/30R20 90Y	110160145	XL	280/AA/A	24.8	8.5	8.0 - 9.0	9.6	25.8	8.5	9	12.3	804	1323@50
245/35R20 95Y	110160132	XL	280/AA/A	24.9	8.5	8.0 - 9.5	9.6	26.8	8.5	9	12.6	775	1521@50

ADVAN APEX® V601

(Continued from previous page)

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
245/40R20 99Y	110160133	XL	280/AA/A	27.6	8.5	8.0 - 9.5	9.4	27.8	8.3	9	13.0	748	1709@50
245/45R20 103Y	110160134	XL	280/AA/A	28.5	8.0	7.5 - 9.0	9.4	28.7	8.1	9	13.4	724	1929@50
255/35R20 97Y	110160135	XL	280/AA/A	28.1	9.0	8.5 - 10.0	10.0	27.0	8.9	9	12.7	769	1609@50
265/30R20 94Y	110160154	XL	280/AA/A	28.0	9.5	9.0 - 10.0	10.4	26.4	9.3	9	12.5	788	1477@50
265/35R20 99Y	110160136	XL	280/AA/A	29.3	9.5	9.0 - 10.5	10.5	27.4	9.3	9	12.9	759	1709@50
275/30R20 97Y	110160137	XL	280/AA/A	28.4	9.5	9.0 - 10.0	10.6	26.6	9.4	9	12.6	782	1609@50
275/35R20 102Y	110160138	XL	280/AA/A	28.9	9.5	9.0 - 11.0	10.7	27.6	9.4	9	12.9	754	1874@50
275/40R20 106Y	110160139	XL	280/AA/A	32.1	9.5	9.0 - 11.0	10.7	28.7	9.4	9	13.4	725	2094@50
285/30R20 99Y	110160140	XL	280/AA/A	30.7	10.0	9.5 - 10.5	11.2	26.8	9.9	9	12.6	775	1709@50
285/35R20 104Y	110160141	XL	280/AA/A	31.2	10.0	9.5 - 11.0	11.2	27.9	9.9	9	13.1	745	1984@50
295/30R20 101Y	110160142	XL	280/AA/A	30.6	10.5	10.0 - 11.0	11.6	27.0	10.3	9	12.8	768	1819@50
305/30R20 103Y	110160143	XL	280/AA/A	32.5	11.0	10.5 - 11.5	12.1	27.2	10.8	9	12.8	762	1929@50
305/35R20 107Y	110160144	XL	280/AA/A	35.5	11.0	10.0 - 12.0	12.2	28.4	10.8	9	13.3	732	2149@50
245/35R21 96Y	110160146	XL	280/AA/A	26.8	8.5	8.0 - 9.5	9.6	27.8	8.3	9	13.2	746	1565@50
265/35R21 101Y	110160149	XL	280/AA/A	29.7	9.5	9.0 - 10.5	10.6	28.4	9.3	9	13.4	731	1819@50

RUNFLAT Performance Cars | Passenger Cars

Legendary ADVAN performance, engineered with Zero Pressure System runflat capabilities.

FEATURES AND BENEFITS



COMPETITIVE GRIP

Advanced tread compound delivers excellent wet and dry traction.



EXCELLENT WET TRACTION

Asymmetric tread design quickly and efficiently evacuates water.



LONG TREAD LIFE

Advanced construction and groove design controls stress to promote even wear.



RUNFLAT

Engineered to support the vehicle's weight during the loss of air pressure.



TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
195/55RF16 87V	110111301	SL	180/AA/A	24.1	6.0	5.5 - 7.0	7.8	24.4	6.5	10	11.3	851	1201@51
205/55RF16 91W	110111302	SL	180/AA/A	25.5	6.5	5.5 - 7.5	8.4	24.8	6.9	10	11.5	836	1356@51
225/50RF16 92W	110111303	SL	180/AA/A	27.3	7.0	6.0 - 8.0	9.1	24.9	7.8	10	11.5	835	1389@51
205/45RF17 84V	110111304	SL	180/AA/A	24.3	7.0	6.5 - 7.5	8.3	24.3	6.9	10	11.3	856	1102@51
225/45RF17 91Y	110111305	SL	180/AA/A	27.1	7.5	7.0 - 8.5	8.9	25.0	7.8	10	11.6	832	1356@51
225/50RF17 94Y	110110194	SL	180/AA/A	30.7	7.0	6.0 - 8.0	9.2	25.9	7.8	10	12.0	803	1477@51
245/45RF17 95Y	110110196	SL	180/AA/A	29.8	8.0	7.5 - 9.0	9.6	25.6	8.4	10	11.9	812	1521@51
255/40RF17 94Y	110111306	SL	180/AA/A	29.8	9.0	8.5 - 10.0	10.3	24.9	8.4	10	11.6	833	1477@51
225/40RF18 88Y	110111307	SL	180/AA/A	27.7	8.0	7.5 - 9.0	9.2	25.0	7.8	10	11.7	831	1235@51
245/40RF18 93Y	110110195	SL	180/AA/A	30.5	8.5	8.0 - 9.5	9.9	25.6	8.4	10	12.0	810	1433@51
255/35RF18 90Y	110110197	SL	180/AA/A	29.3	9.0	8.5 - 10.0	10.4	24.9	8.4	10	11.7	833	1323@51
275/35RF18 95Y	110110198	SL	180/AA/A	32.6	9.5	9.0 - 11.0	10.8	25.5	9.1	10	11.9	815	1521@51

YOKOHAMA A-008P



ULTRA-HIGH PERFORMANCE Classic Sports Cars

A classic design with modern advancements.

FEATURES AND BENEFITS



INSPIRED HANDLING

Asymmetric tread design maximizes the contact patch during cornering.



CONSISTENT GRIP

Dual layer tread compound provides consistent grip via outer cap while under tread compound dissipates heat.



WET TRACTION

Four circumferential grooves channel water in order to ensure sharp response and straight line stability even on wet roads.



O.E. ENHANCED

Yokohama and Porsche worked hand in hand in the 1980s to create a tire optimized for the cars of the decade, the new A-008P builds on that O.E. level with modern advancements.



TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
205/55ZR16 91W NO	110140815	SL	240/A/A	21.2	6.5	5.5 - 7.5	8.3	24.8	7.0	9	11.4	836	1356@51
225/50ZR16 92W	110140817	SL	240/A/A	23.6	7.0	6.0 - 8.0	9.2	24.9	8.3	9	11.5	834	1389@51
245/45ZR16 94W NO	110140816	SL	240/A/A	23.6	8.0	7.5 - 9.0	9.6	24.6	8.7	9	11.4	843	1477@51

HIGH PERFORMANCE Performance Cars | Passenger Cars

A high-performance summer tire that delivers efficient wet and dry handling.

FEATURES AND BENEFITS



COMPETITIVE HANDLING

Solid ribs increase block stiffness for high-speed stability and superior handling.



EFFICIENT GRIP

Excellent hydroplaning resistance and shorter stops on wet roads.



QUIET RIDE

An offset tread pattern increases stability and reduces pattern noise.



FUEL EFFICIENT

Nano-blend compound with micro silica reduces rolling resistance.



TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
185/55R15 82V	110170173	SL	300/AA/A	16.9	6.0	5.0 - 6.5	7.7	23.0	6.3	9	10.6	905	1047@51
195/50R15 82V	110170130	SL	300/AA/A	17.0	6.0	5.5 - 7.0	7.9	22.7	6.6	9	10.5	916	1047@51
195/55R15 85V	110170131	SL	300/AA/A	17.6	6.0	5.5 - 7.0	7.9	23.4	6.5	9	10.8	888	1136@51
205/50R15 86V	110170174	SL	300/AA/A	18.7	6.5	5.5 - 7.5	8.3	23.0	6.9	9	10.6	905	1169@51
205/55R15 88V	110170132	SL	300/AA/A	18.6	6.5	5.5 - 7.5	8.3	23.8	6.9	9	10.9	872	1235@51
195/45R16 84W	110170133	XL	300/AA/A	17.1	6.5	6.0 - 7.5	7.6	22.9	6.5	9	10.7	906	1103@50
195/50R16 84V	110170134	SL	300/AA/A	18.4	6.0	5.5 - 7.0	7.9	23.6	6.6	9	11.0	879	1103@51
195/55R16 87V	110170135	SL	300/AA/A	19.5	6.0	5.5 - 7.0	7.9	24.3	6.5	9	11.3	854	1202@51
205/45R16 87W	110170136	XL	300/AA/A	17.3	7.0	6.5 - 7.5	8.1	23.2	6.9	9	10.8	896	1202@50
205/50R16 87V	110170137	SL	300/AA/A	19.1	6.5	5.5 - 7.5	8.3	24.0	6.9	9	11.1	865	1202@51
205/55R16 91W	110170138	SL	300/AA/A	19.9	6.5	5.5 - 7.5	8.3	24.8	6.9	9	11.5	836	1356@51
215/55R16 93W	110170176	SL	300/AA/A	20.6	7.0	6.0 - 7.5	8.8	25.2	7.2	10	11.6	826	1433@51
225/50R16 92W	110170139	SL	300/AA/A	21.6	7.0	6.0 - 8.0	9.1	24.8	7.6	10	11.4	839	1389@51
225/55R16 95W	110170177	SL	300/AA/A	23.5	7.0	6.0 - 8.0	9.1	25.6	7.4	10	11.7	812	1521@51
195/40R17 81W	110170178	XL	300/AA/A	19.0	7.0	6.5 - 7.5	7.8	23.2	6.7	9	10.9	896	1019@50
195/45R17 85W	110170179	XL	300/AA/A	18.4	6.5	6.0 - 7.5	7.7	23.9	6.5	9	11.2	868	1136@50
205/40R17 88W	110170180	XL	300/AA/A	19.5	7.5	7.0 - 8.0	8.4	23.4	7.2	9	11.0	887	1103@50
205/45R17 88W	110170140	XL	300/AA/A	20.3	7.0	6.5 - 7.5	8.0	24.2	6.9	9	11.3	858	1235@50
205/50R17 93W	110170141	XL	300/AA/A	20.7	6.5	5.5 - 7.5	8.3	25.1	6.9	9	11.7	827	1433@50
215/40R17 87W	110170143	XL	300/AA/A	20.7	7.5	7.0 - 8.5	8.5	23.7	7.5	10	11.1	876	1202@50
215/45R17 91W	110170144	XL	300/AA/A	21.7	7.0	7.0 - 8.0	8.4	24.7	7.3	10	11.5	843	1356@50
215/50R17 95W	110170145	XL	300/AA/A	23.4	7.0	6.0 - 7.5	7.3	25.5	7.3	10	11.8	815	1521@50
215/55R17 94W	110170146	SL	300/AA/A	23.7	7.0	6.0 - 7.5	8.8	26.3	7.2	10	12.1	791	1477@51
225/50R17 98W	110170148	XL	300/AA/A	24.3	7.0	6.0 - 8.0	9.1	25.9	7.6	10	12.0	803	1654@50
235/40R17 90W	110170181	SL	300/AA/A	23.5	8.5	8.0 - 9.5	9.5	24.4	8.2	10	11.4	852	1323@51
235/45R17 97W	110170150	XL	300/AA/A	23.5	8.0	7.5 - 9.0	9.3	25.3	8.0	10	11.7	820	1610@50
255/40R17 94W	110170151	SL	300/AA/A	25.6	9.0	8.5 - 10.0	10.3	25.0	8.8	10	11.6	831	1477@51
205/40R18 86W	110170152	XL	300/AA/A	19.2	7.5	7.0 - 8.0	8.3	24.5	7.2	9	11.5	848	1169@50
215/35R18 84W	110170153	XL	300/AA/A	18.7	7.5	7.0 - 8.5	8.5	23.9	7.5	9	11.3	871	1103@50
215/40R18 89W	110170154	XL	300/AA/A	20.7	7.5	7.0 - 8.5	8.5	24.8	7.5	10	11.7	837	1279@50
215/45R18 93W	110170183	XL	300/AA/A	21.3	7.0	7.0 - 8.0	8.4	25.7	7.3	10	12.0	809	1433@50
225/35R18 87W	110170155	XL	300/AA/A	20.7	8.0	7.5 - 9.0	8.9	24.2	7.9	10	11.4	859	1202@50
225/50R18 99W	110170184	XL	300/AA/A	24.9	7.0	6.0 - 8.0	9.0	26.9	7.6	10	12.4	774	1709@50
235/55R18 100V	110170160	SL	300/AA/A	27.7	7.5	6.5 - 8.5	9.5	28.1	7.6	10	12.9	740	1764@51
235/45R19 95W	110170167	SL	300/AA/A	24.0	8.0	7.5 - 9.0	9.2	27.4	8.0	10	12.8	759	1521@51
265/30R19 93W	110170170	XL	300/AA/A	25.1	9.5	9.0 - 10.0	10.5	25.3	9.3	10	11.9	822	1433@50
225/35R20 90W	110170171	XL	300/AA/A	23.0	8.0	7.5 - 9.0	9.0	26.2	7.9	10	12.4	793	1323@50
255/30R20 92W	110170172	XL	300/AA/A	25.6	9.0	8.5 - 9.5	10.0	26.1	8.9	10	12.4	797	1389@50



ALL-SEASON ULTRA-HIGH PERFORMANCE Performance Cars | Passenger Cars

Finish first with a tire that delivers a performance trifecta: high mileage, comfort and handling.

FEATURES AND BENEFITS



SUPERIOR HANDLING

Engineered for enhanced cornering and crisp, responsive handling.



ALL-SEASON GRIP

HS-2 compound, z grooves and wavy sipes deliver dependable, all-season grip.



QUIET RIDE

Four-pitch tread variation keeps things quiet and comfortable.



LONG TREAD LIFE

HS-2 compound and optimized contact patch for traction and durability.



Non-staggered Fitments and Front Position Tires Used in Staggered Fitments

5 5 0 0 0 Mile Limited Treadwear Warranty

Rear Position Tires Used in Staggered Fitment Applications

2 7 5 0 0 Mile Limited Treadwear Warranty

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
205/55R16 91W	110140610	SL	440/AA/A	21.8	6.5	5.5 - 7.5	8.5	24.9	6.9	11	11.5	835	1356@51
225/50R16 92W	110140611	SL	440/AA/A	23.0	7.0	6.0 - 8.0	9.3	24.8	7.6	11	11.4	836	1389@51
225/55R16 95W	110140612	SL	440/AA/A	25.2	7.0	6.0 - 8.0	9.3	25.7	7.4	11	11.8	807	1521@51
205/50R17 93W	110140613	XL	440/AA/A	23.1	6.5	5.5 - 7.5	8.3	25.2	7.0	11	11.7	824	1433@50
215/45R17 87W	110140614	SL	440/AA/A	23.4	7.0	7.0 - 8.0	8.5	24.6	7.0	11	11.5	843	1201@51
215/50R17 95W	110140615	XL	440/AA/A	23.3	7.0	6.0 - 7.5	8.7	25.6	7.2	11	11.9	812	1521@50
215/55R17 94W	110140616	SL	440/AA/A	24.9	7.0	6.0 - 7.5	9.0	26.3	7.2	11	12.1	790	1477@51
225/45R17 94W	110140617	XL	440/AA/A	22.9	7.5	7.0 - 8.5	8.8	25.0	7.4	11	11.6	831	1477@50
225/50R17 98W	110140618	XL	440/AA/A	25.0	7.0	6.0 - 8.0	9.1	26.0	7.5	11	12.0	799	1653@50
225/55R17 97W	110140619	SL	440/AA/A	26.9	7.0	6.0 - 8.0	9.3	26.9	7.5	11	12.3	774	1609@51
235/45R17 97W	110140620	XL	440/AA/A	24.2	8.0	7.5 - 9.0	9.3	25.3	7.7	11	11.7	820	1609@50
235/50R17 96W	110140621	SL	440/AA/A	24.9	7.5	6.5 - 8.5	9.6	26.3	7.9	11	12.1	790	1565@51
235/55R17 99W	110140622	SL	440/AA/A	27.8	7.5	6.5 - 8.5	9.7	27.2	7.9	11	12.5	765	1709@51
245/40R17 95W	110140623	XL	440/AA/A	24.3	8.5	8.0 - 9.5	9.8	24.8	8.0	11	11.5	837	1521@50
245/45R17 99W	110140624	XL	440/AA/A	24.9	8.0	7.5 - 9.0	9.5	25.7	8.0	11	11.9	807	1709@50
255/40R17 94W	110140625	SL	440/AA/A	26.2	9.0	8.5 - 10.0	10.2	25.0	8.3	11	11.6	831	1477@51
255/45R17 98W	110140626	SL	440/AA/A	26.9	8.5	8.0 - 9.5	10.0	26.0	8.3	11	12.0	798	1653@51
215/40R18 89W	110140627	XL	440/AA/A	20.7	7.5	7.0 - 8.5	8.5	24.9	7.0	11	11.7	834	1279@50
215/45R18 93W	110140628	XL	440/AA/A	23.8	7.0	7.0 - 8.0	8.3	25.7	7.0	11	12.0	807	1433@50
225/40R18 92Y	110140629	XL	440/AA/A	23.4	8.0	7.5 - 9.0	9.0	25.1	7.4	11	11.8	828	1389@50
225/45R18 95W	110140630	XL	440/AA/A	24.0	7.5	7.0 - 8.5	8.8	26.0	7.4	11	12.1	799	1521@50
225/50R18 95W	110140631	SL	440/AA/A	26.9	7.0	6.0 - 8.0	9.1	26.9	7.5	11	12.5	773	1521@51
235/40R18 95Y	110140632	XL	440/AA/A	25.2	8.5	8.0 - 9.5	9.6	25.4	7.7	11	11.9	818	1521@50
235/45R18 98W	110140633	XL	440/AA/A	26.4	8.0	7.5 - 9.0	9.2	26.4	7.7	11	12.3	788	1653@50
235/50R18 97W	110140634	SL	440/AA/A	28.1	7.5	6.5 - 8.5	9.6	27.3	7.9	11	12.6	761	1609@51
245/35R18 92Y	110140635	XL	440/AA/A	24.7	8.5	8.0 - 9.5	9.6	24.8	8.0	11	11.6	839	1389@50
245/40R18 97Y	110140636	XL	440/AA/A	25.6	8.5	8.0 - 9.5	9.6	25.7	8.0	11	12.0	808	1609@50
245/45R18 100W	110140637	XL	440/AA/A	26.0	8.0	7.5 - 9.0	9.7	26.7	8.0	11	12.4	779	1764@50
245/50R18 100W	110140638	SL	440/AA/A	29.3	7.5	7.0 - 8.5	9.9	27.6	8.2	11	12.8	752	1764@51
255/35R18 94Y	110140639	XL	440/AA/A	25.4	9.0	8.5 - 10.0	10.1	25.0	8.3	11	11.7	831	1477@50
255/40R18 99Y	110140640	XL	440/AA/A	27.8	9.0	8.5 - 10.0	10.3	26.0	8.3	11	12.1	799	1709@50
255/45R18 99Y	110140641	SL	440/AA/A	28.9	8.5	8.0 - 9.5	10.2	27.0	8.3	11	12.5	769	1709@51
265/35R18 97Y	110140642	XL	440/AA/A	27.6	9.5	9.0 - 10.5	10.6	25.3	8.7	11	11.9	821	1609@50
265/40R18 101Y	110140643	XL	440/AA/A	28.2	9.5	9.0 - 10.5	10.6	26.4	8.7	11	12.3	788	1819@50
275/35R18 95Y	110140644	SL	440/AA/A	26.6	9.5	9.0 - 11.0	10.8	25.6	9.0	11	11.9	813	1521@51
275/40R18 99Y	110140645	SL	440/AA/A	29.7	9.5	9.0 - 11.0	10.9	26.6	9.0	11	12.4	781	1709@51
285/35R18 101Y	110140646	XL	440/AA/A	28.5	10.0	9.5 - 11.0	11.1	25.9	9.3	11	12.1	803	1819@50
225/40R19 93Y	110140647	XL	440/AA/A	24.5	8.0	7.5 - 9.0	9.0	26.1	7.4	11	12.3	796	1433@50
225/45R19 96Y	110140648	XL	440/AA/A	26.0	7.5	7.0 - 8.5	8.8	27.0	7.4	11	12.6	769	1565@50
235/35R19 91Y	110140649	XL	440/AA/A	25.8	8.5	8.0 - 9.5	9.5	25.5	7.9	11	12.0	814	1356@50
235/40R19 96Y	110140650	XL	440/AA/A	25.6	8.5	8.0 - 9.5	9.4	26.4	7.7	11	12.4	786	1565@50
245/35R19 93Y	110140651	XL	440/AA/A	25.8	8.5	8.0 - 9.5	9.7	25.7	8.1	11	12.1	807	1433@50
245/40R19 98Y	110140652	XL	440/AA/A	26.5	8.5	8.0 - 9.5	9.7	26.7	8.0	11	12.5	777	1653@50
245/45R19 102Y	110140653	XL	440/AA/A	28.3	8.0	7.5 - 9.0	9.6	27.8	8.0	11	12.9	748	1874@50

(Continued next page)

ADVAN Sport® A/S+

(Continued from previous page)

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (3/2" INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
255/35R19 96Y	110140654	XL	440/AA/A	27.3	9.0	8.5 - 10.0	10.1	26.0	8.3	11	12.2	798	1565@50
255/40R19 100Y	110140655	XL	440/AA/A	28.9	9.0	8.5 - 10.0	10.1	27.1	8.3	11	12.7	767	1764@50
255/45R19 104W	110140656	XL	440/AA/A	30.2	8.5	8.0 - 9.5	10.0	28.2	8.3	11	13.1	737	1984@50
265/35R19 98Y	110140657	XL	440/AA/A	28.0	9.5	9.0 - 10.5	10.5	26.3	8.7	11	12.4	789	1653@50
275/35R19 100Y	110140658	XL	440/AA/A	28.0	9.5	9.0 - 11.0	10.7	26.6	9.0	11	12.5	781	1764@50
275/40R19 101Y	110140659	SL	440/AA/A	30.4	9.5	9.0 - 11.0	10.7	27.8	9.0	11	12.9	748	1819@51
285/30R19 98Y	110140660	XL	440/AA/A	29.4	10.0	9.5 - 10.5	11.3	25.7	9.3	11	12.1	807	1653@50
285/35R19 99Y	110140661	SL	440/AA/A	31.5	10.0	9.5 - 11.0	11.2	26.9	9.3	11	12.6	774	1709@51
245/35R20 95Y	110140662	XL	440/AA/A	26.0	8.5	8.0 - 9.5	9.6	26.8	8.1	11	12.6	776	1521@50
245/40R20 99Y	110140663	XL	440/AA/A	28.3	8.5	8.0 - 9.5	9.7	27.7	8.0	11	13.0	749	1709@50
245/45R20 103Y	110140664	XL	440/AA/A	29.5	8.0	7.5 - 9.0	9.6	28.7	8.0	11	13.4	724	1929@50
255/35R20 97Y	110140665	XL	440/AA/A	28.4	9.0	8.5 - 10.0	10.0	27.1	8.3	11	12.8	767	1609@50
255/45R20 105Y	110140666	XL	440/AA/A	30.9	8.5	9.0 - 10.5	10.0	29.1	8.3	11	13.6	713	2039@50
265/35R20 99Y	110140667	XL	440/AA/A	29.6	9.5	9.0 - 10.5	10.6	27.3	8.7	11	12.9	760	1709@50
275/30R20 97Y	110140668	XL	440/AA/A	29.1	9.5	9.0 - 10.0	10.9	26.6	9.1	11	12.6	782	1609@50
275/35R20 102Y	110140669	XL	440/AA/A	29.1	9.5	9.0 - 11.0	10.9	27.7	9.0	11	13.0	750	1874@50
275/40R20 106Y	110140670	XL	440/AA/A	33.3	9.5	9.0 - 11.0	10.7	28.7	9.0	11	13.4	723	2094@50
285/30R20 99W	110140671	XL	440/AA/A	30.7	10.0	9.5 - 10.5	11.1	26.9	9.3	11	12.7	773	1709@50
245/35R21 96Y	110140672	XL	440/AA/A	26.2	8.5	8.0 - 9.5	9.6	27.8	8.1	11	13.2	746	1565@50
265/35R21 101Y	110140673	XL	440/AA/A	30.1	9.5	9.0 - 10.5	10.6	28.4	8.9	11	13.4	731	1819@50
275/35R21 103Y	110140674	XL	440/AA/A	31.3	9.5	9.0 - 11.0	10.8	28.7	9.2	11	13.5	725	1929@50

ALL-SEASON RUNFLAT Performance Cars | Passenger Cars

All-weather performance with the added confidence of a Zero Pressure System runflat capability.

FEATURES AND BENEFITS



WET TRACTION

Directional tread design and adaptive sipes channel water away for excellent wet grip.



RUNFLAT

Advanced runflat technology provides added durability in runflat mode.



HANDLING

Aggressive directional design and construction provide crisp and responsive handling.



QUIET RIDE

Multi-pitch design reduces unwanted resonance for a quieter ride.



TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
195/55RF16 87V	110132194	SL	560/A/A	24.9	6.0	5.5 - 7.0	7.8	24.4	6.5	10	11.3	850	1201@51
205/45RF17 84V	110132191	SL	560/A/A	25.4	7.0	6.5 - 7.5	8.2	24.3	6.9	11	11.3	856	1102@51
225/45RF17 91V	110132192	SL	560/A/A	28.0	7.5	7.0 - 8.5	8.9	25.0	8.0	11	11.6	832	1356@51
225/50RF17 94V	110132193	SL	560/A/A	31.2	7.0	6.0 - 8.0	9.2	25.8	7.5	11	11.9	805	1477@51
225/55RF17 97V	110132197	SL	560/A/A	30.1	7.0	6.0 - 8.0	9.0	26.6	7.2	11	12.2	780	1609@51
255/40RF17 94V	110132195	SL	560/A/A	29.6	9.0	8.5 - 10.0	10.3	25.1	8.4	11	11.7	828	1477@51
245/40RF18 93V	110132190	SL	560/A/A	32.2	8.5	8.0 - 9.5	9.9	25.6	8.7	11	12.0	812	1433@51
245/45RF18 96W	110132196	SL	560/A/A	31.5	8.0	7.5 - 9.0	9.6	26.6	8.3	11	12.4	780	1565@51

AVID Ascend GT®

ALL-SEASON Performance Cars | Passenger Cars | Crossovers/SUVs | Minivans



A next-generation touring tire that delivers all-weather performance all year long.

FEATURES AND BENEFITS



ALL-SEASON TRACTION

TriBlend compound provides confident traction in snow and wintry weather.



SHORTER WET/SNOW BRAKING

TriBlend compound and asymmetric groove arrangement deliver ultimate grip on wet and snowy roads.



QUIET RIDE

Multi-pitch tread design and Adaptive Shoulder reduce noise when new and protect against noise after worn.



LONG TREAD LIFE

Triple 3D sipes and an ultra-square contact patch provide long-lasting, all-season traction.



Non-staggered Fits and

Front Position Tires Used in Staggered Fits

6 5 0 0 0 Mile Limited Treadwear Warranty

Rear Position Tires Used in Staggered Fit Applications

3 2 5 0 0 Mile Limited Treadwear Warranty

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
175/65R15 84H	110132701	SL	740/A/A	17.6	5.0	5.0 - 6.0	6.9	24.1	5.4	12	11.0	864	1102@51
185/55R15 82V	110132702	SL	740/A/A	18.1	6.0	5.0 - 6.5	7.6	23.0	6.1	12	10.6	902	1047@51
185/65R15 88H	110132703	SL	740/A/A	19.4	5.5	5.0 - 6.5	7.5	24.5	5.7	12	11.2	847	1235@51
195/60R15 88H	110132704	SL	740/A/A	20.3	6.0	5.5 - 7.0	8.0	24.3	6.4	12	11.1	854	1235@51
195/65R15 91H	110132705	SL	740/A/A	20.5	6.0	5.5 - 7.0	7.9	25.0	6.1	12	11.4	830	1356@51
205/60R15 91H	110132706	SL	740/A/A	20.5	6.0	5.5 - 7.5	8.3	24.8	6.5	12	11.3	839	1356@51
P205/65R15 92H	110132707	SL	740/A/A	22.3	6.0	5.5 - 7.5	8.3	25.6	6.5	12	11.6	813	1400@51
185/55R16 83H	110132708	SL	740/A/A	18.7	6.0	5.0 - 6.5	7.7	24.0	6.1	12	11.1	865	1074@51
P185/60R16 86H	110132751	SL	740/A/A	19.6	6.0	5.0 - 6.5	7.6	24.8	5.9	12	11.4	839	1168@51
195/50R16 84V	110132709	SL	740/A/A	19.2	6.0	5.5 - 7.0	7.8	23.9	6.4	12	11.1	869	1102@51
195/55R16 87V	110132710	SL	740/A/A	19.4	6.0	5.5 - 7.0	7.8	24.4	6.4	12	11.3	852	1201@51
205/50R16 87V	110132752	SL	740/A/A	20.9	6.5	5.5 - 7.5	8.4	24.1	6.7	12	11.1	864	1201@51
205/55R16 91H	110132711	SL	740/A/A	21.8	6.5	5.5 - 7.5	8.3	25.0	6.7	12	11.5	830	1356@51
205/60R16 92H	110132712	SL	740/A/A	22.3	6.0	5.5 - 7.5	8.2	25.7	6.5	12	11.8	808	1389@51
205/60R16 92V	110132713	SL	740/A/A	22.3	6.0	5.5 - 7.5	8.2	25.6	6.5	12	11.7	812	1389@51
205/65R16 95H	110132714	SL	740/A/A	23.6	6.0	5.5 - 7.5	8.2	26.5	6.4	12	12.1	785	1521@51
215/55R16 97H	110132715	XL	740/A/A	23.1	7.0	6.0 - 7.5	8.9	25.4	7.0	12	11.7	818	1609@50
215/60R16 95H	110132717	SL	740/A/A	23.8	6.5	6.0 - 7.5	8.7	26.2	6.9	12	12.0	792	1521@51
215/60R16 95V	110132716	SL	740/A/A	23.8	6.5	6.0 - 7.5	8.7	26.2	6.9	12	12.0	792	1521@51
225/55R16 99V	110132753	XL	740/A/A	25.1	7.0	6.0 - 8.0	9.1	25.9	7.4	12	11.8	803	1709@50
205/50R17 93V	110132718	XL	740/A/A	22.7	6.5	5.5 - 7.5	8.3	25.1	6.7	12	11.7	828	1433@50
215/45R17 91V	110132719	XL	740/A/A	22.7	7.0	7.0 - 8.0	8.4	24.6	7.0	12	11.5	843	1356@50
215/50R17 95V	110132720	XL	740/A/A	23.4	7.0	6.0 - 7.5	8.7	25.5	7.0	12	11.8	814	1521@50
215/55R17 94V	110132721	SL	740/A/A	24.7	7.0	6.0 - 7.5	8.8	26.4	7.0	12	12.2	788	1477@51
225/45R17 91V	110132722	SL	740/A/A	23.8	7.5	7.0 - 8.5	8.9	25.0	7.4	12	11.6	832	1356@51
225/50R17 94V	110132723	SL	740/A/A	24.9	7.0	6.0 - 8.0	9.2	25.9	7.4	12	12.0	802	1477@51
225/55R17 97V	110132724	SL	740/A/A	26.7	7.0	6.0 - 8.0	9.1	26.9	7.4	12	12.4	771	1609@51
225/60R17 99V	110132725	SL	740/A/A	26.9	6.5	6.0 - 8.0	9.1	27.8	7.4	12	12.7	748	1709@51
235/45R17 97V	110132726	XL	740/A/A	24.3	8.0	7.5 - 9.0	9.4	25.4	7.8	12	11.8	819	1609@50
235/50R17 96V	110132727	SL	740/A/A	26.0	7.5	6.5 - 8.5	9.6	26.3	7.7	12	12.1	790	1565@51
235/55R17 99H	110132728	SL	740/A/A	27.1	7.5	6.5 - 8.5	9.7	27.2	7.7	12	12.5	765	1709@51
235/60R17 102H	110132729	SL	740/A/A	28.9	7.0	6.5 - 8.5	9.6	28.2	7.7	12	12.9	737	1874@51
245/45R17 99V	110132730	XL	740/A/A	24.9	8.0	7.5 - 9.0	9.6	25.6	8.1	12	11.9	811	1709@50
245/50R17 99V	110132731	SL	740/A/A	27.8	7.5	7.0 - 8.5	9.8	26.8	8.0	12	12.3	776	1709@51
P215/55R18 94H	110132732	SL	740/A/A	26.7	7.0	6.0 - 7.5	8.8	27.3	7.0	12	12.6	761	1477@51
225/40R18 92V	110132754	XL	740/A/A	24.0	8.0	7.5 - 9.0	9.2	25.1	7.5	12	11.8	828	1389@50
225/45R18 95V	110132733	XL	740/A/A	24.7	7.5	7.0 - 8.5	8.9	25.9	7.4	12	12.1	802	1521@50
225/50R18 95V	110132734	SL	740/A/A	26.9	7.0	6.0 - 8.0	9.1	26.9	7.4	12	12.5	774	1521@51
P225/55R18 97H	110132735	SL	740/A/A	27.8	7.0	6.0 - 8.0	9.2	27.8	7.4	12	12.8	748	1609@51
225/60R18 100H	110132736	SL	740/A/A	29.8	6.5	6.0 - 8.0	9.1	28.8	7.4	12	13.2	722	1764@51
235/45R18 94V	110132737	SL	740/A/A	26.5	8.0	7.5 - 9.0	9.4	26.3	7.8	12	12.3	789	1477@51
235/50R18 101V	110132738	XL	740/A/A	28.4	7.5	6.5 - 8.5	9.5	27.2	7.7	12	12.6	763	1819@50
235/55R18 100V	110132739	SL	740/A/A	29.5	7.5	6.5 - 8.5	9.6	28.3	7.7	12	13.0	734	1764@51
245/40R18 97V	110132740	XL	740/A/A	26.7	8.5	8.0 - 9.5	9.7	25.7	8.1	12	12.0	807	1609@50
245/45R18 96V	110132741	SL	740/A/A	27.6	8.0	7.5 - 9.0	9.7	26.7	8.0	12	12.4	779	1565@51
245/50R18 100V	110132742	SL	740/A/A	30.4	7.5	7.0 - 8.5	9.8	27.8	8.0	12	12.8	747	1764@51

(Continued next page)

AVID Ascend GT®

(Continued from previous page)

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
255/45R18 99V	110132743	SL	740/A/A	28.4	8.5	8.0 - 9.5	10.0	27.0	8.4	12	12.5	768	1709@51
235/40R19 96V	110132744	XL	740/A/A	26.2	8.5	8.0 - 9.5	9.4	26.4	7.8	12	12.4	786	1565@50
235/45R19 99V	110132745	XL	740/A/A	27.8	8.0	7.5 - 9.0	9.3	27.4	7.8	12	12.8	758	1709@50
245/40R19 94V	110132746	SL	740/A/A	28.0	8.5	8.0 - 9.5	9.8	26.8	8.2	12	12.5	776	1477@51
245/45R19 98V	110132747	SL	740/A/A	28.7	8.0	7.5 - 9.0	9.8	27.7	8.0	12	12.9	750	1653@51
255/40R19 100V	110132748	XL	740/A/A	27.8	9.0	8.5 - 10.0	10.0	27.0	8.4	12	12.6	768	1764@50
255/45R19 100V	110132749	SL	740/A/A	29.8	8.5	8.0 - 9.5	10.0	28.0	8.3	12	13.0	741	1764@51
245/45R20 99V	110132750	SL	740/A/A	30.0	8.0	7.5 - 9.0	9.5	28.7	8.0	12	13.4	723	1709@51

AVID Ascend LX®



* Made in the USA



ALL-SEASON Passenger Cars | Crossovers/SUVs | Minivans

A premium, high-mileage, all-season touring tire that goes the distance.

FEATURES AND BENEFITS



DEPENDABLE WINTER TRACTION

Exceptional strong grip for worry-free winter driving.



SUPERIOR WET TRACTION

Designed for reliable wet braking and resistance to hydroplaning.



QUIET RIDE

Designed for reduced pattern and road noise for a comfortable, smooth ride.



LONG TREAD LIFE

Uniform tread compound and shape deliver a longer tread life.



8 5 0 0 0

Mile Limited Treadwear Warranty

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
185/60R15 84H	110132801	SL	800/A/A	18.1	5.5	5.0 - 6.5	7.4	23.8	5.9	11	10.9	873	1102@51
185/65R15 88H	110132802	SL	800/A/A	18.6	5.5	5.0 - 6.5	7.5	24.5	5.7	11	11.2	848	1235@51
195/60R15 88H	110132803	SL	800/A/A	19.5	6.0	5.5 - 7.0	8.0	24.3	6.4	11	11.1	856	1235@51
195/65R15 91H	110132804	SL	800/A/A	20.2	6.0	5.5 - 7.0	7.9	25.0	6.1	11	11.4	831	1356@51
205/65R15 94H	110132805	SL	800/A/A	21.1	6.0	5.5 - 7.0	8.4	25.6	6.5	11	11.6	813	1477@51
205/70R15 96T	110132806	SL	800/A/B	21.6	6.0	5.0 - 7.0	8.2	26.4	6.4	11	11.9	787	1565@51
215/70R15 98T	110132807	SL	800/A/B	23.4	6.5	5.5 - 7.0	8.8	26.9	6.7	11	12.1	772	1653@51
P195/60R16 89H	110132808	SL	800/A/A	20.2	6.0	5.5 - 7.0	8.0	25.2	6.4	11	11.6	823	1279@51
205/55R16 91H	110132809	SL	800/A/A	20.8	6.5	5.5 - 7.5	8.4	25.0	6.7	11	11.5	832	1356@51
205/60R16 92H	110132810	SL	800/A/A	21.1	6.0	5.5 - 7.5	8.2	25.6	6.5	11	11.7	813	1389@51
205/65R16 95H	110132811	SL	800/A/A	22.0	6.0	5.5 - 7.5	8.4	26.4	6.5	11	12.1	786	1521@51
205/70R16 97T	110132812	SL	800/A/B	22.6	6.0	5.0 - 7.0	8.3	27.3	6.4	11	12.4	761	1609@51
215/55R16 97H	110132813	XL	800/A/A	22.2	7.0	6.0 - 7.5	8.7	25.4	7.0	11	11.7	817	1609@50
215/60R16 95H	110132814	SL	800/A/A	22.2	6.5	6.0 - 7.5	8.7	26.1	6.9	11	12.0	794	1521@51
215/65R16 98H	110132815	SL	800/A/A	23.0	6.5	6.0 - 7.5	8.7	27.0	6.7	11	12.3	768	1653@51
225/60R16 98H	110132816	SL	800/A/A	25.2	6.5	6.0 - 8.0	9.1	26.7	7.4	11	12.2	779	1653@51
225/65R16 100H	110132817	SL	800/A/A	26.1	6.5	6.0 - 8.0	8.9	27.6	7.0	11	12.5	754	1764@51
235/60R16 100H	110132818	SL	800/A/A	26.3	7.0	6.5 - 8.5	9.6	27.2	7.7	11	12.4	765	1764@51
235/65R16 103T	110132819	SL	800/A/B	28.4	7.0	6.5 - 8.5	9.5	28.0	7.5	11	12.7	742	1929@51
205/50R17 93V	110132820	XL	800/A/A	21.8	6.5	5.5 - 7.5	8.2	25.1	6.7	11	11.7	828	1433@50
215/45R17 87V	110132821	SL	800/A/A	21.7	7.0	7.0 - 8.0	8.4	24.6	7.0	11	11.5	843	1201@51
215/50R17 95H	110132822	XL	800/A/A	23.3	7.0	6.0 - 7.5	8.7	25.5	7.0	11	11.8	815	1521@50
215/55R17 94V	110132823	SL	800/A/A	24.6	7.0	6.0 - 7.5	8.8	26.3	7.0	11	12.1	789	1477@51
215/60R17 96H	110132824	SL	800/A/A	24.7	6.5	6.0 - 7.5	8.6	27.2	6.9	11	12.5	763	1565@51
215/65R17 99H	110132825	SL	800/A/A	26.0	6.5	6.0 - 7.5	8.5	28.0	6.7	11	12.8	741	1709@51
225/50R17 94V	110132826	SL	800/A/A	24.4	7.0	6.0 - 8.0	9.1	25.9	7.4	11	12.0	801	1477@51
225/55R17 97H	110132827	SL	800/A/A	26.0	6.5	6.0 - 8.0	9.1	26.9	7.4	11	12.4	772	1609@51
225/60R17 99H	110132828	SL	800/A/A	27.0	6.5	6.0 - 8.0	9.1	27.7	7.4	11	12.7	749	1709@51
225/65R17 102H	110132829	SL	800/A/A	27.7	6.5	6.0 - 8.0	9.1	28.6	7.0	11	13.0	727	1874@51
235/50R17 96H	110132830	SL	800/A/A	26.1	7.5	6.5 - 8.5	9.5	26.3	7.7	11	12.1	789	1565@51
235/60R17 102T	110132831	SL	800/A/B	27.6	7.0	6.5 - 8.5	9.5	28.1	7.7	11	12.8	739	1874@51
235/65R17 104H	110132832	SL	800/A/A	29.8	7.0	6.5 - 8.5	9.6	29.1	7.5	11	13.2	715	1984@51
P215/50R18 92V	110132839	SL	800/A/A	25.5	7.0	6.0 - 7.5	8.7	26.5	7.0	11	12.3	783	1389@51
225/45R18 95V	110132833	XL	800/A/A	25.2	7.5	7.0 - 8.5	8.8	26.0	7.4	11	12.1	799	1521@50
225/55R18 98H	110132834	SL	800/A/A	28.8	7.0	6.0 - 8.0	9.1	27.7	7.4	11	12.8	749	1653@51
225/60R18 100H	110132835	SL	800/A/A	29.4	6.5	6.0 - 8.0	9.1	28.8	7.4	11	13.2	722	1764@51
235/45R18 94V	110132836	SL	800/A/A	26.4	8.0	7.5 - 9.0	9.2	26.4	7.8	11	12.3	786	1477@51
235/55R18 100V	110132837	SL	800/A/A	30.0	7.5	6.5 - 8.5	9.6	28.1	7.7	11	12.9	739	1764@51
235/60R18 103H	110132838	SL	800/A/A	30.1	7.0	6.5 - 8.5	9.6	29.1	7.7	11	13.3	714	1929@51

★All AVID Ascend LX sizes are proudly made in the U.S.A.



ALL-SEASON Passenger Cars | Crossovers | Minivans

A tire you can trust to deliver competitive comfort, stability and traction in all conditions.

FEATURES AND BENEFITS



LONG TREAD LIFE

Innovative compound provides long wear and confident traction.



QUIET RIDE

Packed with features that combine to deliver a quiet and comfortable ride.



COMPETITIVE WET TRACTION

Symmetric tread design with multiple grooves and sipes for wet and winter weather confidence.



COMPETITIVE HANDLING

A still sidewall and tread block are built strong for sure-footed handling.



6 5 0 0 0 Mile Limited Treadwear Warranty

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
P185/60R15 84T	110131805	SL	620/A/B	18.0	5.5	5.0 - 6.5	7.4	23.7	5.9	10	10.9	875	1102@51
P185/65R15 86S	110131806	SL	620/A/B	18.4	5.5	5.0 - 6.5	7.4	24.4	5.6	10	11.2	850	1168@51
P195/60R15 87T	110131807	SL	620/A/B	19.0	6.0	5.5 - 7.0	7.8	24.3	6.2	10	11.1	856	1190@51
P195/65R15 89S	110131808	SL	620/A/B	19.4	6.0	5.5 - 7.0	8.0	25.0	5.9	10	11.4	831	1279@51
P205/60R15 90T	110131820	SL	620/A/B	20.0	6.0	5.5 - 7.5	8.1	24.7	6.1	10	11.3	840	1301@51
P205/65R15 92S	110131809	SL	620/A/B	21.2	6.0	5.5 - 7.5	8.3	25.4	6.2	10	11.6	818	1400@51
P205/70R15 95S	110131810	SL	620/A/B	22.1	6.0	5.0 - 7.0	8.2	26.4	6.5	10	11.9	787	1499@51
P215/60R15 93T	110131811	SL	620/A/B	21.4	6.5	6.0 - 7.5	8.7	25.1	6.9	10	11.4	827	1411@51
P215/65R15 95S	110131812	SL	620/A/B	22.1	6.5	6.0 - 7.5	8.9	25.9	6.7	10	11.8	801	1510@51
P215/70R15 98S	110131813	SL	620/A/B	24.5	6.5	5.5 - 7.0	8.9	26.9	6.9	10	12.1	774	1653@51
P235/75R15 105S	110131821	SL	620/A/B	30.5	6.5	6.0 - 8.0	9.2	28.9	6.2	11	12.9	718	2028@51
P205/55R16 89T	110131814	SL	620/A/B	21.1	6.5	5.5 - 7.5	8.5	24.9	7.0	10	11.5	835	1279@51
P205/60R16 91T	110131815	SL	620/A/B	21.3	6.0	5.5 - 7.5	8.2	25.6	6.5	10	11.8	810	1356@51
P215/60R16 94T	110131816	SL	620/A/B	22.4	6.5	6.0 - 7.5	8.8	26.1	6.9	10	12.0	794	1477@51
P215/65R16 98T	110131817	SL	620/A/B	24.3	6.5	6.0 - 7.5	8.7	27.0	6.9	10	12.3	770	1653@51
P215/70R16 99T	110131822	SL	620/A/B	26.3	6.5	5.5 - 7.0	8.7	27.8	6.1	10	12.6	746	1709@51
P225/60R16 97S	110131818	SL	620/A/B	24.5	6.5	6.0 - 8.0	9.0	26.6	7.2	10	12.1	780	1609@51
P235/65R16 103T	110131824	SL	620/A/B	27.6	7.0	6.5 - 8.2	9.4	27.9	6.9	10	12.6	744	1929@51
P235/70R16 104T	110131823	SL	620/A/B	29.6	7.0	6.0 - 8.0	9.3	28.9	6.7	11	13.0	719	1984@51
P215/55R17 94H	110131830	SL	620/A/A	25.8	7.0	6.0 - 7.5	8.8	26.4	7.4	11	12.2	787	1477@51
P215/60R17 96T	110131825	SL	620/A/B	26.0	6.5	6.0 - 7.5	8.6	27.2	6.5	10	12.5	765	1565@51
P215/65R17 99T	110131826	SL	620/A/B	25.8	6.5	6.0 - 7.5	8.6	28.1	6.3	10	12.8	740	1709@51
P225/50R17 94H	110131831	SL	620/A/A	26.0	7.0	6.0 - 8.0	9.1	25.9	7.8	11	10.1	801	1477@51
P225/55R17 97T	110131827	SL	620/A/B	26.2	7.0	6.0 - 8.0	9.1	26.8	7.2	10	12.3	776	1609@51
P225/60R17 98T	110131819	SL	620/A/B	27.6	6.5	6.0 - 8.0	8.9	27.7	7.2	10	12.7	749	1653@51
P225/65R17 102T	110131828	SL	620/A/B	27.2	6.5	6.0 - 8.0	8.9	28.5	6.7	10	13.0	728	1874@51
P235/60R17 102T	110131832	SL	620/A/B	27.8	7.0	6.5 - 8.5	9.4	28.1	7.4	11	12.8	739	1874@51
P235/65R17 104T	110131829	SL	620/A/B	29.0	7.0	6.5 - 8.5	9.4	29.0	6.9	10	13.2	716	1984@51

*All AVID Touring-S sizes are proudly made in the U.S.A.

PARADA Spec-X®



ALL-SEASON Crossovers/SUVs

A respected tire for those who respect good looks with performance to match.

FEATURES AND BENEFITS



SUPERIOR HANDLING

Sporty tread design and wide profile gives you confident handling on the street.



COMPETITIVE WET TRACTION

Provides tremendous water evacuation for outstanding traction in wet weather.



LONG TREAD LIFE

Special construction and dimpled design help achieve long even wear.



QUIET RIDE

A multi-pitched tread pattern reduces pattern and road noise for a quieter ride.



TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
225/60R18 100H	110100248	SL	420/A/A	28.6	6.5	6.0 - 8.0	8.9	28.5	6.9	11	13.1	730	1764@51
245/45R20 99V	110100247	SL	420/A/A	29.9	8.0	7.5 - 9.0	9.5	28.7	8.4	11	13.4	724	1709@51
255/40R20 101V	110100224	XL	420/A/A	31.1	9.0	8.5 - 10.0	10.1	28.1	8.9	11	13.2	739	1819@50
255/45R20 105V	110100225	XL	420/A/A	32.2	8.5	8.0 - 9.5	9.9	29.1	8.8	11	13.5	713	2039@50
275/40R20 106V	110100236	XL	420/A/A	33.9	9.5	9.0 - 11.0	10.8	28.6	9.6	11	13.3	726	2094@50
275/45R20 110V	110100226	XL	420/A/A	34.8	9.0	8.5 - 10.5	10.6	29.9	9.4	11	13.9	695	2337@50
275/55R20 117V	110100231	XL	420/A/A	39.9	8.5	7.5 - 9.5	10.9	31.9	9.0	11	14.7	650	2833@50
285/50R20 112V	110100229	SL	420/A/A	40.4	9.0	8.0 - 10.0	11.5	31.3	9.5	11	14.4	664	2469@51
295/45R20 114V	110100227	XL	420/A/A	40.8	10.0	9.5 - 11.0	11.6	30.6	10.2	11	14.1	679	2601@50
305/50R20 120V	110100230	XL	420/A/A	45.0	9.5	8.5 - 11.0	12.4	32.2	10.2	11	14.7	646	3086@50
255/30R22 95V	110100237	XL	420/A/A	29.9	9.0	8.5 - 9.5	9.9	28.3	9.1	11	13.5	733	1524@50
255/35R22 99V	110100238	XL	420/A/A	30.5	9.0	8.5 - 10.0	10.2	29.1	8.9	11	13.8	713	1709@50
265/30R22 97V	110100217	XL	420/A/A	31.4	9.5	9.0 - 10.0	10.2	28.6	9.6	11	13.6	727	1609@50
265/35R22 102V	110100218	XL	420/A/A	32.4	9.5	9.0 - 10.5	10.4	29.5	9.3	11	13.9	704	1874@50
265/40R22 106V	110100220	XL	420/A/A	35.9	10.0	9.0 - 10.5	10.6	30.5	9.3	11	14.3	681	2094@50
285/30R22 101V	110100239	XL	420/A/A	33.1	10.0	9.5 - 10.5	11.1	28.9	10.3	11	13.7	720	1819@50
285/35R22 106V	110100219	XL	420/A/A	36.6	10.0	9.5 - 11.0	11.0	30.1	10.0	11	14.2	690	2094@50
285/40R22 110V	110100240	XL	420/A/A	37.6	10.0	9.5 - 11.0	11.2	31.1	10.0	12	14.6	668	2337@50
285/45R22 114V	110100222	XL	420/A/A	39.7	9.5	9.0 - 10.5	10.9	32.2	9.8	11	15.0	645	2601@50
305/40R22 114V	110100221	XL	420/A/A	41.7	11.0	10.0 - 12.0	12.2	31.7	10.7	11	14.8	655	2601@50
305/45R22 118V	110100223	XL	420/A/A	44.1	10.0	9.5 - 11.5	11.5	32.9	10.5	11	15.2	632	2910@50
325/50R22 116V	110100241	XL	420/A/A	53.4	10.0	9.0 - 11.5	13.0	34.7	10.9	12	15.9	599	2756@50
285/40R24 112V	110100242	XL	420/A/A	40.4	10.0	9.5 - 11.0	11.7	33.0	10.0	12	15.5	630	2469@50
295/35R24 110V	110100210	XL	420/A/A	43.2	11.0	10.0 - 11.5	11.9	32.3	10.3	11	15.2	643	2337@50
305/35R24 112V	110100211	XL	420/A/A	43.9	11.0	10.0 - 12.0	12.1	32.7	10.7	11	15.4	636	2469@50
315/35R24 114V	110100212	XL	420/A/A	45.6	11.0	10.5 - 12.5	12.4	32.9	11.0	11	15.5	632	2601@50
325/45R24 116V	110100243	XL	420/A/A	51.4	11.0	10.0 - 12.0	12.8	35.4	11.2	12	16.5	587	2756@50

GEOLANDAR CV[®] G058

ALL-SEASON Crossovers/SUVs | Minivans



An all-season tire that delivers complete confidence to drivers of crossovers and midsize SUVs.

FEATURES AND BENEFITS



COMPETITIVE WET TRACTION

New tread compound and design for optimal wet grip and confident braking.



SUPERIOR WINTER TRACTION

Engineered with features to stay flexible as temperatures drop.



LONG TREAD LIFE

Optimized contact patch and proprietary tread compound for long-lasting wear.



QUIET RIDE

A distinctive, multi-pitch tread pattern helps reduce road noise.



Non-staggered Fitments and

Front Position Tires Used in Staggered Fitments

6 5 0 0 0 Mile Limited Treadwear Warranty

Rear Position Tires Used in Staggered Fitment Applications

3 2 5 0 0 Mile Limited Treadwear Warranty



As awarded by
The Chicago Athenaeum:
Museum of Architecture
and Design

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT GOLD INFLATION PRESSURE (LBS@PSI)
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
215/65R16 98H	110105804	SL	740/A/A	22.8	6.5	6.0-7.5	8.7	27.0	6.4	11	12.3	770	1653@51
215/70R16 100H	110105805	SL	740/A/A	25.8	6.5	5.5-7.0	8.5	27.9	6.4	11	12.6	745	1764@51
225/70R16 103H	110105807	SL	740/A/A	27.5	6.5	6.0-7.5	8.9	28.4	6.8	12	12.8	732	1929@51
235/70R16 106H	110105809	SL	740/A/A	29.7	7.0	6.0-8.0	9.4	29.0	7.0	11	13.1	716	2094@51
215/60R17 96H	110105811	SL	740/A/A	24.4	6.5	6.0-7.5	8.5	27.2	6.4	11	12.5	763	1565@51
215/65R17 99H	110105812	SL	740/A/A	24.1	6.5	6.0-7.5	8.8	28.0	6.4	11	12.8	742	1709@51
215/70R17 101H	110105813	SL	740/A/A	26.7	6.5	5.5-7.0	8.5	28.9	6.4	11	13.2	718	1819@51
225/55R17 97V	110105814	SL	740/A/A	25.0	7.0	6.0-8.0	9.1	26.8	7.2	11	12.3	775	1609@51
225/60R17 99H	110105815	SL	740/A/A	25.7	6.5	6.0-8.0	8.9	27.6	6.8	11	12.6	753	1709@51
225/65R17 102H	110105816	SL	740/A/A	26.6	6.5	6.0-8.0	6.8	28.5	6.8	11	13.0	730	1874@51
235/55R17 99H	110105817	SL	740/A/A	26.1	7.5	6.5-8.5	9.5	27.2	7.6	11	12.5	764	1709@51
235/60R17 102V	110105818	SL	740/A/A	26.8	7.0	6.5-8.5	9.4	28.1	7.0	11	12.8	740	1874@51
235/65R17 108V	110105819	XL	740/A/A	30.2	7.0	6.5-8.5	9.5	29.1	7.0	11	13.2	714	2205@50
245/65R17 107H	110105820	SL	740/A/A	31.0	7.0	7.0-8.5	9.8	29.5	7.3	11	13.4	704	2149@51
255/60R17 106H	110105821	SL	740/A/A	30.0	7.5	7.0-9.0	10.2	29.0	7.6	11	13.2	716	2094@51
215/55R18 99V	110105823	XL	740/A/A	26.1	7.0	6.0-7.5	8.8	27.3	6.9	11	12.6	760	1709@50
225/55R18 98V	110105825	SL	740/A/A	27.2	7.0	6.0-8.0	9.0	27.8	7.2	11	12.8	748	1653@51
225/60R18 100H	110105826	SL	740/A/A	27.6	6.5	6.0-8.0	8.9	28.5	6.8	11	13.1	728	1764@51
235/50R18 97V	110105828	SL	740/A/A	28.7	7.5	6.5-8.5	9.6	27.2	8.0	11	12.6	763	1609@51
235/55R18 100V	110105829	SL	740/A/A	28.0	7.5	6.5-8.5	9.4	28.0	7.6	11	12.9	741	1764@51
235/60R18 107V	110105830	XL	740/A/A	30.4	7.0	6.5-8.5	9.4	29.1	7.0	11	13.3	715	2149@50
235/65R18 106V	110105831	SL	740/A/A	30.5	7.0	6.5-8.5	9.4	30.0	7.0	11	13.7	692	2094@51
245/60R18 105H	110105832	SL	740/A/A	30.2	7.0	7.0-8.5	9.7	29.5	7.3	11	13.5	704	2039@51
255/55R18 109V	110105833	XL	740/A/A	32.2	8.0	7.0-9.0	10.3	28.9	8.2	11	13.3	718	2271@50
225/55R19 99V	110105834	SL	740/A/A	28.2	7.0	6.0-8.0	9.1	28.7	7.2	11	13.3	723	1709@51
235/50R19 103V	110105835	XL	740/A/A	30.1	7.5	6.5-8.5	9.6	28.6	7.8	10	13.3	726	1929@50
235/55R19 105V	110105836	XL	740/A/A	30.3	7.5	6.5-8.5	9.5	29.2	7.6	11	13.5	711	2039@50
245/55R19 103H	110105837	SL	740/A/A	31.5	7.5	7.0-8.5	9.8	29.8	8.0	11	13.7	697	1929@51
255/50R19 107V	110105838	XL	740/A/A	32.8	8.0	7.0-9.0	10.4	29.1	8.6	11	13.4	714	2149@50
235/55R20 102V	110105839	SL	740/A/A	30.6	7.5	6.5-8.5	9.5	30.1	7.6	11	13.9	691	1874@51
245/50R20 102V	110105840	SL	740/A/A	31.7	7.5	7.0-8.5	9.9	29.6	8.0	11	13.8	701	1874@51
255/50R20 109V	110105841	XL	740/A/A	34.2	8.0	7.0-9.0	10.2	30.1	8.6	11	13.9	690	2271@50
255/55R20 110V	110105842	XL	740/A/A	35.2	8.0	7.0-9.0	10.3	31.2	8.2	11	14.4	666	2337@50
265/50R20 107V	110105843	SL	740/A/A	35.7	8.5	7.5-9.5	10.7	30.4	9.0	11	14.1	683	2149@51

GEOLANDAR X-CV®

ALL-SEASON Crossovers/SUVs



The GEOLANDAR X-CV is engineered to perform on today's luxury sport crossovers and SUVs.

FEATURES AND BENEFITS



SUPERIOR HANDLING

All-new tread pattern with reinforced shoulder provides sharp, sure handling and stability.



ALL-SEASON TRACTION

Specially designed tread pattern for confident traction on wet and wintry roads.



QUIET RIDE

A staggered five-pitch block variation reduces noise.



LONG TREAD LIFE

A wider flat contact patch and new advanced silica compound promotes long-lasting, even wear.



Non-staggered Fits and

Front Position Tires Used in Staggered Fits

5 0 0 0 0 Mile Limited Treadwear Warranty

Rear Position Tires Used in Staggered Fitment Applications

2 5 0 0 0 Mile Limited Treadwear Warranty



As awarded by
The Chicago Athenaeum:
Museum of Architecture
and Design

TIRES SIZE	PART NO.	LOAD I.D.	UTOG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
255/55R18 109W	110157001	XL	520/A/A	32.6	8.0	7.0 - 9.0	10.4	29.0	8.0	11	13.2	720	2271@50
235/45R19 99W	110157002	XL	520/A/A	25.8	8.0	7.5 - 9.0	9.3	27.4	7.6	11	12.8	757	1709@50
235/55R19 105W	110157003	XL	520/A/A	30.0	7.5	6.5 - 8.5	9.7	29.2	7.3	11	13.5	713	2039@50
255/50R19 107W	110157004	XL	520/A/A	32.4	8.0	7.0 - 9.0	10.4	29.1	8.0	11	13.4	718	2149@50
255/55R19 111W	110157005	XL	520/A/A	35.1	8.0	7.0 - 9.0	10.4	30.0	8.0	11	13.8	692	2403@50
265/50R19 110W	110157006	XL	520/A/A	34.8	8.5	7.5 - 9.5	10.9	29.5	8.3	11	13.5	708	2337@50
275/55R19 111W	110157007	SL	520/A/A	39.5	8.5	7.5 - 9.5	11.2	30.9	8.6	11	14.1	676	2403@51
235/45R20 100W	110157008	XL	520/A/A	27.6	8.0	7.5 - 9.0	9.3	28.4	7.6	11	13.3	732	1764@50
245/45R20 103W	110157024	XL	520/A/A	28.9	8.0	7.5 - 9.0	9.6	28.7	8.0	11	13.4	725	1929@50
255/45R20 105W	110157009	XL	520/A/A	31.1	8.5	8.0 - 9.5	10.0	29.1	8.3	11	13.5	718	2039@50
255/50R20 109W	110157010	XL	520/A/A	34.8	8.0	7.0 - 9.0	10.4	30.1	8.0	11	13.9	692	2271@50
255/55R20 110W	110157011	XL	520/A/A	35.1	8.0	7.0 - 9.0	10.4	31.0	8.0	11	14.2	674	2337@50
265/45R20 108W	110157012	XL	520/A/A	32.8	9.0	8.5 - 10.0	10.5	29.4	8.6	11	13.6	709	2205@50
265/50R20 111W	110157013	XL	520/A/A	35.1	8.5	7.5 - 9.5	10.9	30.5	8.3	11	14.0	685	2403@50
275/40R20 106W	110157014	XL	520/A/A	33.1	9.5	9.0 - 11.0	10.9	28.7	9.1	11	13.4	727	2094@50
275/45R20 110W	110157015	XL	520/A/A	35.3	9.0	8.5 - 10.5	10.8	29.8	8.9	11	13.7	702	2337@50
275/50R20 113W	110157016	XL	520/A/A	39.2	8.5	7.5 - 9.5	11.2	30.9	8.7	11	14.2	676	2149@50
285/45R20 112W	110157025	XL	520/A/A	39.5	9.5	9.0 - 10.5	11.3	30.0	9.3	12	13.9	693	2469@50
295/40R20 110W	110157026	XL	520/A/A	39.3	10.5	10.0 - 11.5	11.9	29.1	9.8	12	13.5	714	2337@50
265/45R21 104W	110157017	SL	520/A/A	32.2	9.0	8.5 - 10.0	10.5	30.4	8.6	11	14.1	688	1984@51
275/40R21 107W	110157018	XL	520/A/A	33.5	9.5	9.0 - 11.0	10.9	29.7	9.1	11	13.9	702	2535@50
275/45R21 110W	110157019	XL	520/A/A	35.9	9.0	8.5 - 10.5	10.8	30.8	8.9	11	14.3	678	2337@50
295/35R21 107W	110157020	XL	520/A/A	34.2	10.5	10.0 - 11.5	11.9	29.1	9.8	12	13.6	715	2149@50
295/40R21 111W	110157021	XL	520/A/A	37.3	10.5	10.0 - 11.5	11.9	30.3	9.8	12	14.1	688	2403@50
265/40R22 106W	110157022	XL	520/A/A	34.6	9.5	9.0 - 10.5	10.7	30.4	8.7	11	14.3	685	2094@50
275/40R22 108W	110157023	XL	520/A/A	35.7	9.5	9.0 - 11.0	10.9	30.7	9.1	11	14.4	678	2205@50

GEOLANDAR® H/T G056

ALL-SEASON Crossovers/SUVs | Trucks



All-season performance for highway confidence in all conditions.

FEATURES AND BENEFITS



QUIET RIDE

Unique symmetric tread pattern minimizes road noise for a quiet ride.



COMPETITIVE ALL-SEASON TRACTION

Advanced compound and symmetric tread pattern combine to offer superior wet and winter grip.



LONG TREAD LIFE

A flat profile, 3D siping and an advanced silica compound provide long-lasting, even wear.



ON-ROAD DURABILITY

Sturdy construction provides the strength to stand up to everyday demands.



7 0 0 0 0

Mile Limited Treadwear Warranty
on P-metric sizes

5 0 0 0 0

Mile Limited Treadwear Warranty
on LT-metric sizes

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDEWALL TYPE
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	SINGLE	DUAL	
P235/75R15 108T	110105604	XL	720/A/B	31.4	6.5	6.0-8.0	9.1	29.0	7.2	12	13.0	717	2183@50	-	OWL
265/70R15 112H	110105639	SL	720/A/A	36.1	8.0	7.0-9.0	10.8	29.5	8.1	13	13.2	704	2469@51	-	BW
P225/75R16 106T	110105601	XL	720/A/B	30.5	6.0	6.0-7.5	8.7	29.3	6.9	12	13.2	710	2094@50	-	BW
P235/70R16 104T	110105602	SL	720/A/B	30.4	7.0	6.0-8.0	9.4	28.9	7.2	12	13.0	718	1984@51	-	OWL
P235/75R16 109T	110105605	XL	720/A/B	33.2	6.5	6.0-8.0	9.2	29.9	7.2	12	13.4	694	2271@50	-	OWL
P245/70R16 106H	110105608	SL	720/A/A	38.1	7.0	6.5-8.0	9.8	29.5	7.5	12	13.3	704	2094@51	-	OWL
P245/75R16 109T	110105610	SL	720/A/B	36.9	7.0	6.5-8.0	9.6	30.4	7.5	12	13.6	683	2271@51	-	OWL
P255/65R16 106T	110105612	SL	720/A/B	33.3	7.5	7.0-9.0	10.2	29.0	7.8	12	13.1	716	2094@51	-	OWL
P255/70R16 109T	110105615	SL	720/A/B	36.0	7.5	6.5-8.5	10.2	30.1	7.8	12	13.5	690	2271@51	-	OWL
P265/70R16 111T	110105621	SL	720/A/B	38.0	8.0	7.0-9.0	10.7	30.6	8.1	13	13.7	680	2403@51	-	OWL
P265/75R16 114T	110105624	SL	720/A/B	40.1	7.5	7.0-9.0	10.5	31.6	8.1	13	14.1	657	2601@51	-	OWL
275/70R16 114H	110105642	SL	720/A/A	40.8	8.0	7.0-9.0	11.0	31.1	8.3	12	13.9	668	2601@51	-	BW
P235/70R17 108T	110105603	XL	720/A/B	32.9	7.0	6.0-8.0	9.4	30.0	7.2	12	13.6	693	2205@50	-	OWL
P235/75R17 108S	110105677	SL	720/A/B	35.1	6.5	6.0-8.0	9.3	31.1	7.3	12	14.0	667	2205@51	-	BW
P245/65R17 105T	110105607	SL	720/A/B	33.9	7.0	7.0-8.5	9.7	29.6	7.5	12	13.4	703	2039@51	-	BW
P245/70R17 108H	110105609	SL	720/A/A	35.7	7.0	6.5-8.0	9.8	30.6	7.5	12	13.8	680	2205@51	-	OWL
P255/65R17 108T	110105613	SL	720/A/B	35.7	7.5	7.0-9.0	10.2	30.1	7.8	12	13.6	690	2205@51	-	OWL
P255/70R17 110T	110105616	SL	720/A/B	37.5	7.5	6.5-8.5	10.2	31.0	7.8	12	14.0	670	2337@51	-	OWL
P265/65R17 110T	110105619	SL	720/A/B	38.6	8.0	7.5-9.5	10.6	30.6	8.1	12	13.8	678	2337@51	-	OWL
P265/70R17 113T	110105622	SL	720/A/B	40.1	8.0	7.0-9.0	10.7	31.9	8.1	13	14.3	652	2535@51	-	OWL
P245/60R18 104H	110105606	SL	720/A/A	32.6	7.0	7.0-8.5	9.6	29.6	7.3	11	13.5	703	1984@51	-	BW
255/60R18 112V	110105670	XL	720/A/A	35.7	7.5	7.0-9.0	10.2	30.0	8.0	11	13.7	692	2469@50	-	BW
P255/65R18 109T	110105614	SL	720/A/B	38.5	7.5	7.0-9.0	10.3	31.1	7.8	12	14.1	668	2271@51	-	BW
P255/70R18 112H	110105617	SL	720/A/A	38.7	7.5	6.5-8.5	10.2	32.0	7.8	12	14.5	648	2469@51	-	BW
P265/60R18 109H	110105618	SL	720/A/A	38.1	8.0	7.5-9.5	10.7	30.5	8.1	12	13.9	682	2271@51	-	BW
P265/65R18 112T	110105620	SL	720/A/B	38.2	8.0	7.5-9.5	10.5	31.5	8.1	12	14.3	660	2469@51	-	BW
P265/70R18 114S	110105623	SL	720/A/B	40.9	8.0	7.0-9.0	10.7	32.6	8.1	13	14.7	637	2601@51	-	OWL
275/60R18 113H	110105672	SL	720/A/A	39.0	8.0	7.5-9.5	10.9	31.0	8.3	12	14.1	670	2535@51	-	BW
P275/65R18 114T	110105627	SL	720/A/B	41.7	8.0	7.5-9.5	10.9	32.1	8.3	12	14.5	647	2601@51	-	OWL
285/60R18 116H	110105643	SL	720/A/A	40.7	8.5	8.0-10.0	11.5	31.5	8.8	12	14.3	660	2756@51	-	BW
P255/60R19 108H	110105611	SL	720/A/A	36.2	7.5	7.0-9.0	10.2	31.1	8.0	11	14.2	669	2205@51	-	BW
265/55R19 109V	110105681	SL	720/A/A	36.4	8.5	7.5-9.5	11.0	30.5	8.7	12	14.0	682	2271@51	-	BW
245/60R20 107 H	110105644	SL	720/A/A	35.8	7.0	7.0-8.5	9.8	31.5	7.3	11	14.5	659	2149@51	-	BW
275/55R20 113H	110105671	SL	720/A/A	40.3	8.5	7.5-9.5	11.1	31.8	8.9	12	14.6	653	2535@51	-	BW
P275/60R20 114H	110105626	SL	720/A/A	41.9	8.0	7.5-9.5	10.9	32.9	8.6	12	15.0	631	2601@51	-	BW
285/50R20 112V	110105645	SL	720/A/A	40.7	9.0	8.0-10.0	11.6	31.3	9.8	12	14.4	665	2469@51	-	BW
275/50R21 113V	110105680	XL	720/A/A	39.9	8.5	7.5-9.5	11.1	31.9	9.4	12	14.8	651	2535@50	-	BW
P275/50R22 111H	110105678	SL	720/A/A	41.2	8.5	7.5-9.5	11.1	32.8	9.2	12	15.2	633	2403@51	-	BW
285/45R22 114H	110105669	XL	720/A/A	39.2	9.5	9.0-10.5	10.9	32.0	9.8	12	14.9	648	2601@50	-	BW
LT215/85R16 115/112R	110105658	E	-	36.7	6.0	5.5-7.0	8.4	30.5	6.4	14	13.6	682	2680@80	2470@80	BW
LT225/75R16 115/112S	110105659	E	-	36.6	6.0	6.0-7.0	8.7	29.3	6.8	14	13.2	708	2680@80	2470@80	BW
LT235/85R16 120/116R	110105660	E	-	43.5	6.5	6.0-7.5	9.4	31.9	7.0	14	14.2	651	3042@80	2778@80	BW
LT245/75R16 120/116S	110105661	E	-	42.1	7.0	6.5-8.0	9.9	30.6	7.6	14	13.7	679	3042@80	2778@80	OWL
LT265/75R16 123/120R	110105662	E	-	46.5	7.5	7.0-8.0	10.6	31.7	8.1	15	14.1	655	3415@80	3085@80	OWL
LT285/75R16 126/123S	110105675	E	-	54.0	8.0	7.5-9.0	11.7	32.8	8.7	16	14.6	633	3750@80	3415@80	OWL
LT225/75R17 116/113S	110105679	E	-	39.0	6.0	6.0-7.5	8.7	30.7	6.9	14	13.8	677	2755@80	2535@80	BW
LT235/80R17 120/117R	110105663	E	-	42.8	6.5	6.0-7.5	9.2	31.9	7.0	14	14.3	651	3085@80	2835@80	OWL
LT245/70R17 119/116R	110105664	E	-	41.8	7.0	6.5-8.0	9.6	30.7	7.6	14	13.8	677	3000@80	2755@80	OWL
LT245/75R17 121/118S	110105665	E	-	43.9	7.0	6.5-7.5	9.7	31.7	7.6	14	14.2	656	3195@80	2910@80	OWL

(Continued next page)

GEOLANDAR® H/T GO56

(Continued from previous page)

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDEWALL TYPE
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	SINGLE	DUAL	
LT265/70R17 121/118S	110105666	E	-	47.3	8.0	7.0 - 8.5	10.7	31.8	8.2	15	14.3	653	3195@80	2910@80	OWL
LT285/70R17 121/118S	110105676	E	-	54.2	8.5	7.5 - 9.0	11.7	32.8	8.7	16	14.6	634	3195@80	2910@80	OWL
LT275/65R18 123/120S	110105667	E	-	50.3	8.0	7.5 - 9.0	11.1	32.2	8.4	16	14.5	645	3415@80	3085@80	OWL
LT275/70R18 125/122R	110105668	E	-	52.6	8.0	7.0 - 8.5	11.1	33.3	8.4	16	15.0	623	3640@80	3305@80	OWL
LT265/60R20 121/118R	110105674	E	-	51.8	8.0	7.5 - 9.5	10.7	32.8	8.4	15	15.0	633	3195@80	2910@80	BW
LT275/65R20 126/123S	110105673	E	-	56.0	8.0	7.5 - 9.5	11.0	34.3	8.4	16	15.6	606	3750@80	3415@80	BW
30X9.50R15 104 S	110105640	C	-	35.0	7.5	6.5 - 8.5	9.5	29.4	7.0	13	13.1	706	1985@50	-	BW
31X10.50R15 109 S	110105641	C	-	39.7	8.5	7.0 - 9.0	10.7	30.4	7.9	13	13.5	683	2270@50	-	BW

GEOLANDAR® A/T Go15

ALL-SEASON SUVs | Trucks



An all-weather, all-terrain tire that delivers both on- and off-road duties.

FEATURES AND BENEFITS



COMPETITIVE ALL-WEATHER TRACTION

Severe snow service-rated (3PMSF) for confident wet and winter traction.



LONG TREAD LIFE

A flatter profile and Enduro compound designed to deliver longer treadwear and increased tread life.



OFF-ROAD DURABILITY

Dependable off-road performance from a sturdy, Endurocore construction.



ON/OFF-ROAD TRACTION

Advanced tread design provides capable off-road traction while staying quiet on the highway.



6 0 0 0 0

Mile Limited Treadwear Warranty on P/E metric sizes

5 0 0 0 0

Mile Limited Treadwear Warranty on LT-metric sizes

P/E-metric

LT-metric

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDEWALL TYPE
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	SINGLE	DUAL	
205/70R15 96H	110101570	SL	600/A/B	27.3	6.0	5.0-7.0	8.3	26.3	6.1	12	11.9	790	1565@51	-	BW
215/70R15 98H	110101581	SL	600/A/B	26.7	6.5	5.5-7.0	8.7	26.9	6.5	12	12.1	773	1653@51	-	OWL
P225/70R15 100T	110101571	SL	600/A/B	29.5	6.5	6.0-7.5	8.9	27.5	6.7	12	12.4	755	1753@51	-	OWL
P235/70R15 102T	110101587	SL	600/A/B	29.5	7.0	6.0-8.0	9.4	28.0	7.0	13	12.6	742	1896@51	-	OWL
P235/75R15 108T	110101510	XL	600/A/B	33.0	6.5	6.0-8.0	9.1	29.0	7.0	13	13.0	716	2183@50	-	OWL
265/70R15 112H	110101572	SL	600/A/B	37.7	8.0	7.0-9.0	10.6	29.7	8.0	13	13.2	700	2469@51	-	BW
215/60R16 95H	110101586	SL	600/A/B	24.9	6.5	6.0-7.5	8.7	26.1	6.5	12	11.9	796	1521@51	-	BW
215/65R16 98H	110101573	SL	600/A/B	26.2	6.5	6.0-7.5	8.8	27.0	6.5	12	12.3	769	1653@51	-	BW
215/70R16 100H	110101574	SL	600/A/B	28.2	6.5	5.5-7.0	8.7	27.9	6.5	12	12.6	745	1764@51	-	BW
225/70R16 103H	110101575	SL	600/A/B	30.3	6.5	6.0-7.5	9.1	28.4	6.7	12	12.8	732	1929@51	-	BW
235/60R16 100H	110101576	SL	600/A/B	29.1	7.0	6.5-8.5	9.4	27.0	7.1	12	12.3	768	1764@51	-	BW
P235/70R16 104T	110101511	SL	600/A/B	32.4	7.0	6.0-8.0	9.3	29.0	7.0	13	13.1	716	1984@51	-	OWL
P245/70R16 106T	110101512	SL	600/A/B	34.8	7.0	6.5-8.0	9.6	29.6	7.2	13	13.3	703	2094@51	-	OWL
P245/75R16 109T	110101513	SL	600/A/B	37.7	7.0	6.5-8.0	9.7	30.5	7.2	13	13.7	681	2271@51	-	OWL
255/65R16 109H	110101514	SL	600/A/B	34.8	7.5	7.0-9.0	10.3	29.1	7.6	12	13.1	714	2271@51	-	BW
P255/70R16 109T	110101515	SL	600/A/B	35.9	7.5	6.5-8.5	10.1	30.2	7.6	13	13.5	689	2271@51	-	OWL
P265/70R16 111T	110101516	SL	600/A/B	38.1	8.0	7.0-9.0	10.6	30.7	8.0	13	13.7	677	2403@51	-	OWL
P265/75R16 114T	110101517	SL	600/A/B	41.1	7.5	7.0-9.0	10.6	31.7	8.0	13	14.1	656	2601@51	-	OWL
275/70R16 114H	110101577	SL	600/A/B	41.8	8.0	7.0-9.0	11.0	31.2	8.2	13	13.9	665	2601@51	-	BW
215/60R17 96H	110101583	SL	600/A/B	27.1	6.5	6.0-7.5	8.7	27.2	6.5	12	12.5	765	1565@51	-	BW
215/65R17 103H	110101676	XL	600/A/B	28.0	6.5	6.0-7.5	8.7	28.1	6.5	12	12.8	740	1929@50	-	BW
225/60R17 99H	110101663	SL	600/A/B	28.0	6.5	6.0-8.0	8.9	27.7	6.7	12	12.7	751	1709@51	-	BW
225/65R17 102H	110101518	SL	600/A/B	30.3	6.5	6.0-8.0	8.9	28.5	6.7	12	13.0	728	1874@51	-	BW
235/65R17 108H	110101519	XL	600/A/B	32.1	7.0	6.5-8.5	9.3	29.1	7.0	12	13.2	713	2205@50	-	BW
235/70R17 109H	110101584	XL	600/A/B	34.6	7.0	6.0-8.0	9.4	29.8	7.0	13	13.5	696	2271@50	-	BW
P235/75R17 108T	110101520	SL	600/A/B	37.0	6.5	6.0-8.0	9.2	30.9	7.0	13	13.9	671	2205@51	-	OWL
P245/65R17 105T	110101521	SL	600/A/B	35.1	7.0	7.0-8.5	9.6	29.6	7.2	12	13.4	702	2039@51	-	OWL
P245/70R17 108T	110101522	SL	600/A/B	36.4	7.0	6.5-8.0	9.7	30.6	7.2	13	13.8	680	2205@51	-	OWL
255/65R17 114H	110101578	XL	600/A/B	36.8	7.5	7.0-9.0	10.2	30.1	7.6	12	13.6	690	2601@50	-	BW
P255/70R17 110T	110101523	SL	600/A/B	37.3	7.5	6.5-8.5	10.1	31.2	7.6	13	14.0	666	2337@51	-	OWL
P255/75R17 113T	110101524	SL	600/A/B	40.7	7.0	6.5-8.5	10.0	32.1	7.6	13	14.4	647	2535@51	-	OWL
P265/65R17 110T	110101525	SL	600/A/B	37.5	8.0	7.5-9.5	10.5	30.7	8.0	12	13.8	677	2337@51	-	OWL
P265/70R17 113T	110101526	SL	600/A/B	40.6	8.0	7.0-9.0	10.6	31.7	8.0	13	14.2	655	2535@51	-	OWL
275/65R17 115H	110101579	SL	600/A/B	40.5	8.0	7.5-9.5	10.9	31.1	8.1	12	14.0	667	2679@51	-	BW
285/65R17 116H	110101588	SL	600/A/B	41.4	8.5	8.0-10.0	11.5	31.5	8.5	13	14.2	659	2756@51	-	BW
P285/70R17 117T	110101527	SL	600/A/B	45.0	8.5	7.5-9.5	11.3	32.8	8.5	13	14.7	633	2833@51	-	OWL
225/55R18 98H	110101589	SL	600/A/B	28.9	7.0	6.0-8.0	9.3	27.7	7.2	11	12.8	750	1653@51	-	BW
225/60R18 104H	110101674	XL	600/A/B	29.6	6.5	6.0-8.0	8.9	28.6	6.7	12	13.1	726	1984@50	-	BW
235/55R18 104H	110101675	XL	600/A/B	30.2	7.5	6.5-8.5	9.6	28.2	7.5	11	13.0	737	1984@50	-	BW
235/60R18 107H	110101528	XL	600/A/B	33.0	7.0	6.5-8.5	9.3	29.1	7.1	12	13.3	713	2149@50	-	BW
245/60R18 109H	110101673	XL	600/A/B	33.0	7.0	7.0-8.5	9.6	29.6	7.4	12	13.5	702	2271@50	-	BW
255/55R18 109H	110101618	XL	600/A/B	34.4	8.0	7.0-9.0	10.4	29.1	8.1	12	13.3	715	2271@50	-	BW
255/70R18 113H	110101529	SL	600/A/B	40.1	7.5	6.5-8.5	10.3	32.0	7.6	13	14.5	648	2535@51	-	BW
265/60R18 110H	110101530	SL	600/A/B	38.0	8.0	7.5-9.5	10.8	30.5	8.0	12	13.9	681	2337@51	-	BW
265/65R18 114H	110101531	SL	600/A/B	41.1	8.0	7.5-9.5	10.6	31.6	8.0	12	14.3	658	2601@51	-	BW
265/70R18 116H	110101532	SL	600/A/B	42.6	8.0	7.0-9.0	10.7	32.6	8.0	13	14.7	636	2756@51	-	BW
275/60R18 113H	110101582	SL	600/A/B	41.0	8.0	7.5-9.5	10.9	31.1	8.2	12	14.1	669	2535@51	-	BW
275/65R18 116H	110101533	SL	600/A/B	42.8	8.0	7.5-9.5	11.1	32.0	8.1	12	14.5	648	2756@51	-	BW

(Continued next page)

GEOLANDAR® A/T Go15

(Continued from previous page)

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)		SIDEWALL TYPE
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	SINGLE	DUAL	
285/60R18 116H	110101580	SL	600/A/B	42.3	8.5	8.0-10.0	11.5	31.4	8.7	13	14.2	662	2756@51	-	BW
235/55R19 105H	110101621	XL	600/A/B	32.0	7.5	6.5-8.5	9.6	29.1	7.5	11	13.5	713	2039@50	-	BW
255/55R19 111H	110101619	XL	600/A/B	36.2	8.0	7.0-9.0	10.4	30.0	8.1	12	13.8	692	2403@50	-	BW
245/50R20 105H	110101677	XL	600/A/B	34.1	7.5	7.0-8.5	9.8	29.8	8.2	12	13.8	697	2039@50	-	BW
265/50R20 107H	110101620	SL	600/A/B	38.8	8.5	7.5-9.5	10.9	30.4	8.9	12	14.0	684	2149@51	-	BW
275/55R20 117H	110101534	XL	600/A/B	40.8	8.5	7.5-9.5	11.1	31.8	8.7	12	14.6	653	2833@50	-	BW
275/60R20 115H	110101535	SL	600/A/B	44.5	8.0	7.5-9.5	10.9	33.1	8.2	12	15.1	627	2679@51	-	BW
285/50R20 112H	110101590	SL	600/A/B	42.8	9.0	8.0-10.0	11.7	31.3	9.6	12	14.4	665	2469@51	-	BW
285/45R22 114H	110101591	XL	600/A/B	41.2	9.5	9.0-10.5	11.3	32.1	9.4	12	14.9	647	2601@50	-	BW
LT215/75R15 100/97S	110101628	C	-	31.2	6.0	5.5-7.0	8.4	27.8	6.5	16	12.5	748	1765@50	1610@50	OWL
LT235/75R15 104/101S	110101629	C	-	36.4	6.5	6.0-7.0	9.1	29.0	7.2	17	13.0	716	1985@50	1820@50	OWL
LT215/85R16 115/112R	110101630	E	-	39.9	6.0	5.5-7.0	8.6	30.5	6.5	16	13.6	682	2680@80	2470@80	OWL
LT225/75R16 115/112R	110101631	E	-	39.2	6.0	6.0-7.0	8.7	29.4	6.9	17	13.2	705	2680@80	2470@80	OWL
LT235/85R16 120/116R	110101632	E	-	47.0	6.5	6.0-7.5	9.3	31.9	7.2	17	14.2	652	3042@80	2778@80	OWL
LT245/70R16 118/115R	110101679	E	-	42.6	7.0	6.5-8.0	9.9	29.6	7.6	17	13.3	702	2910@80	2680@80	BW
LT245/75R16 120/116S	110101633	E	-	45.6	7.0	6.5-8.0	9.8	30.6	7.6	17	13.7	679	3042@80	2778@80	OWL
LT255/70R16 115/112S	110101681	D	-	44.3	7.5	6.5-8.5	10.4	30.2	8.0	17	13.5	688	2680@65	2470@65	BW
LT265/75R16 123/120R	110101634	E	-	48.7	7.5	7.0-8.0	10.6	31.7	8.3	18	14.1	655	3415@80	3085@80	OWL
LT285/75R16 126/123R	110101635	E	-	56.4	8.0	7.5-9.0	11.4	32.8	8.8	18	14.5	634	3750@80	3415@80	OWL
LT295/75R16 128/125R	110101666	E	-	59.5	8.0	7.5-9.5	11.6	33.7	9.1	18	14.9	617	3970@80	3640@80	BW
LT305/70R16 124/121R	110101665	E	-	56.9	9.0	8.0-9.5	12.2	33.0	9.6	18	14.6	630	3525@65	3195@65	BW
LT315/75R16 127/124R	110101636	E	-	64.4	8.5	8.0-11.0	12.0	34.5	9.4	18	15.2	602	3860@65	3525@65	OWL
LT235/80R17 120/117R	110101637	E	-	46.5	6.5	6.0-7.5	9.2	31.9	7.2	17	14.3	651	3085@80	2835@80	OWL
LT245/65R17 117/114S	110101680	E	-	42.7	7.0	7.0-8.5	9.7	29.8	7.6	17	13.5	698	2835@80	2600@80	OWL
LT245/70R17 119/116R	110101638	E	-	45.4	7.0	6.5-8.0	9.7	30.6	7.6	17	13.8	678	3000@80	2755@80	OWL
LT245/75R17 121/118S	110101639	E	-	47.0	7.0	6.5-7.5	9.6	31.7	7.6	17	14.2	656	3195@80	2910@80	OWL
LT255/65R17 119/116S	110101682	E	-	45.5	7.5	7.5-9.0	10.2	30.3	8.0	17	13.7	686	3000@80	2755@80	BW
LT265/65R17 120/117R	110101678	E	-	46.9	8.0	8.0-9.5	10.6	30.7	8.3	17	13.9	676	3085@80	2835@80	OWL
LT265/70R17 121/118S	110101640	E	-	51.0	8.0	7.0-8.5	10.7	31.9	8.3	18	14.3	651	3195@80	2910@80	OWL
LT285/70R17 121/118S	110101641	E	-	55.2	8.5	7.5-9.0	11.4	32.8	8.8	18	14.7	633	3195@80	2910@80	OWL
LT285/75R17 121/118S	110101642	E	-	60.4	8.0	7.5-9.5	11.2	33.9	8.8	18	15.1	613	3195@80	2910@80	OWL
LT315/70R17 121/118S	110101643	E	-	61.2	9.5	8.0-11.0	12.4	34.4	9.8	18	15.3	604	3195@65	2910@65	OWL
LT265/60R18 119/116S	110101683	E	-	47.6	8.0	8.0-9.5	10.7	30.6	8.5	17	13.9	679	3000@80	2755@80	OWL
LT265/70R18 124/121R	110101645	E	-	53.2	8.0	7.0-9.0	10.7	32.8	8.3	18	14.8	633	3525@80	3195@80	OWL
LT275/65R18 123/120S	110101646	E	-	52.7	8.0	7.5-9.0	10.8	32.3	8.6	17	14.6	643	3415@80	3085@80	OWL
LT275/70R18 125/122S	110101647	E	-	54.7	8.0	7.0-8.5	10.9	33.3	8.6	18	15.0	623	3640@80	3305@80	OWL
LT285/65R18 125/122S	110101648	E	-	55.2	8.5	8.0-10.0	11.3	32.8	8.9	17	14.8	634	3640@80	3305@80	BW
LT285/75R18 129/126S	110101649	E	-	63.7	8.0	7.5-9.5	11.0	34.7	8.8	18	15.5	598	4080@80	3750@80	BW
LT295/70R18 129/126S	110101650	E	-	63.9	8.5	7.5-10.0	11.6	34.4	9.2	18	15.4	603	4080@80	3750@80	BW
LT325/60R18 124/121S	110101664	E	-	66.1	9.5	9.0-11.5	12.8	33.7	10.3	16	15.1	617	3523@65	3195@65	BW
LT265/60R20 121/118S	110101652	E	-	52.2	8.0	7.5-9.5	10.5	32.8	8.5	17	15.0	633	3195@80	2910@80	BW
LT275/55R20 120/117S	110101653	E	-	52.3	8.5	7.5-9.5	10.9	32.3	8.6	16	14.8	643	3085@80	2835@80	BW
LT275/60R20 123/120S	110101654	E	-	56.3	8.0	7.5-9.5	11.1	33.3	8.6	17	15.2	624	3415@80	3085@80	BW
LT275/65R20 126/123R	110101655	E	-	57.2	8.0	7.5-9.5	10.9	34.3	8.6	17	15.6	606	3750@80	3415@80	BW
LT285/55R20 122/119S	110101656	E	-	55.1	9.0	8.0-10.0	11.4	32.6	9.4	17	14.9	636	3305@80	3000@80	BW
LT285/60R20 125/122S	110101657	E	-	59.6	8.5	8.0-10.0	11.4	33.9	9.1	17	15.4	612	3640@80	3305@80	BW
LT285/65R20 127/124S	110101658	E	-	60.5	8.5	8.0-10.0	11.6	34.8	9.0	17	15.8	598	3860@80	3525@80	BW
LT295/55R20 123/120S	110101622	E	-	57.5	9.5	8.0-10.0	11.9	33.0	9.5	16	15.1	629	3415@80	3085@80	BW
LT295/60R20 126/123S	110101659	E	-	59.9	8.5	8.0-10.0	11.7	34.2	9.4	17	15.5	607	3750@80	3415@80	BW
LT295/65R20 129/126S	110101660	E	-	68.3	8.5	8.0-10.0	11.7	35.4	9.2	17	16.0	587	4080@80	3750@80	BW
LT305/55R20 121/118S	110101661	E	-	57.1	9.5	8.5-11.0	12.0	33.5	9.6	16	15.3	619	3195@65	2910@65	BW
LT325/60R20 121/118S	110101662	D	-	67.8	9.5	9.0-12.0	12.8	35.6	10.3	16	16.1	584	3195@50	2910@50	BW
LT285/50R22 121/118Q	110101669	E	-	62.3	9.0	8.5-10.0	11.5	33.7	9.3	16	15.5	617	3195@80	2910@80	BW
LT285/55R22 124/121Q	110101668	E	-	63.8	9.0	8.5-10.0	11.7	34.7	9.3	16	15.9	599	3525@80	3195@80	BW
LT325/50R22 122R	110101667	E	-	68.5	10.0	9.5-11.5	13.1	35.1	10.5	16	16.1	592	3305@65	-	BW
30X9.50R15 104S	110101624	C	-	36.6	7.5	6.5-8.5	9.4	29.8	7.2	17	13.3	697	1985@50	-	OWL
31X10.50R15 109S	110101625	C	-	41.2	8.5	7.0-9.0	10.6	30.7	8.2	18	13.6	676	2270@50	-	OWL
32X11.50R15 113S	110101626	C	-	49.4	9.0	8.0-10.0	11.5	31.8	8.8	18	14.0	654	2535@50	-	OWL
33X12.50R15 108S	110101627	C	-	51.7	10.0	8.5-11.0	12.6	32.8	9.8	18	14.4	634	2205@35	-	OWL
35X12.50R18 123R	110101644	E	-	64.1	10.0	8.5-11.0	12.4	34.6	9.8	17	15.5	601	3415@65	-	OWL
35X12.50R20 121R	110101651	E	-	61.1	10.0	8.5-11.0	12.4	34.7	9.8	16	15.7	599	3195@65	-	BW

GEOLANDAR X-AT[®]

ALL-SEASON SUVs | Trucks



Extreme versatility takes you from peak to pavement and back with absolute authority.

FEATURES AND BENEFITS



OFF-ROAD DURABILITY

Protects against impacts and punctures for ultimate peace of mind.



LONG TREAD LIFE

Optimized contact area and unique compound provide flatter footprint and longer tread life.



QUIET RIDE

Distinctive tread grooves dramatically reduce pattern and road noise for a smooth, quiet ride in the segment.



OFF-ROAD TRACTION

Specially-engineered tread pattern provides strength and grip no matter how rugged the road.



4 5 0 0 0 Mile Limited Treadwear Warranty



As awarded by
The Chicago Athenaeum:
Museum of Architecture
and Design

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)	
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	SINGLE	DUAL
LT235/70R16 104/101Q	110116037	C	-	40.3	7.0	6.0-8.0	9.4	29.2	7.5	16	13.2	711	1985@50	1820@50
LT265/75R16 123/120Q	110116002	E	-	54.5	7.5	7.0-8.0	10.4	32.0	8.3	17	14.2	650	3415@80	3085@80
LT235/80R17 120/117Q	110116039	E	-	50.9	6.5	6.0-8.0	9.3	32.2	7.3	16	14.4	646	3085@80	2835@80
LT245/75R17 121/118Q	110116038	E	-	50.9	7.0	6.5-8.0	9.6	31.8	7.7	16	14.3	653	3195@80	2910@80
LT265/65R17 120/117Q	110116028	E	-	53.1	8.0	8.0-9.5	10.9	30.7	8.6	17	13.8	676	3085@80	2835@80
LT265/70R17 121/118Q	110116006	E	-	55.8	8.0	7.0-8.5	10.8	32.0	8.6	17	14.3	650	3195@80	2910@80
LT285/70R17 121/118Q	110116007	E	-	61.1	8.5	7.5-9.0	11.7	33.1	9.1	18	14.8	628	3195@80	2910@80
LT295/70R17 121/118Q	110116008	E	-	64.8	8.5	7.5-10.0	11.7	33.6	9.4	18	15.0	619	3195@80	2910@80
LT265/60R18 119/116Q	110116048	E	-	53.5	8.0	7.5-9.5	10.6	30.7	8.7	17	14.0	676	3000@80	2755@80
LT265/65R18 122/119Q	110116040	E	-	57.0	8.0	8.0-9.5	10.9	31.7	8.6	17	14.4	655	3305@80	3000@80
LT265/70R18 124/121Q	110116042	E	-	59.6	8.0	7.0-9.0	11.0	32.9	8.6	17	14.8	632	3525@80	3195@80
LT275/65R18 123/120Q	110116041	E	-	60.1	8.0	8.0-9.5	11.1	32.3	8.8	18	14.6	643	3415@80	3085@80
LT275/70R18 125/122Q	110116012	E	-	62.4	8.0	7.0-8.5	11.0	33.4	8.8	18	15.0	622	3640@80	3305@80
LT285/60R18 122/119Q	110116029	E	-	60.5	8.5	8.5-10.0	11.6	31.6	9.4	18	14.3	657	3305@80	3000@80
LT285/65R18 125/122Q	110116013	E	-	62.4	8.5	8.0-10.0	11.6	32.8	9.1	18	14.8	634	3640@80	3305@80
LT285/75R18 129/126Q	110116014	E	-	66.1	8.0	7.5-9.5	11.5	35.1	8.9	18	15.7	592	4080@80	3750@80
LT295/70R18 129/126Q	110116015	E	-	67.7	8.5	7.5-10.0	12.0	34.6	9.4	18	15.5	601	4080@80	3750@80
LT305/70R18 126/123Q	110116016	E	-	69.9	9.0	8.5-10.0	12.4	35.0	9.8	18	15.6	593	3750@65	3415@65
LT325/65R18 127/124Q	110116030	E	-	73.9	9.5	9.0-12.0	13.1	34.8	10.5	19	15.5	598	3860@65	3525@65
LT265/60R20 121/118Q	110116043	E	-	58.0	8.0	8.0-9.5	10.7	32.8	8.7	17	15.0	634	3195@80	2910@80
LT275/55R20 120/117Q	110116044	E	-	57.1	8.5	7.5-9.5	11.2	32.2	8.7	17	15.2	643	3085@80	2835@80
LT275/60R20 123/120Q	110116045	E	-	60.4	8.0	7.5-9.5	10.9	33.2	8.8	17	15.5	626	3415@80	3085@80
LT275/65R20 126/123Q	110116022	E	-	64.2	8.0	7.5-9.5	11.3	34.3	8.8	18	15.6	605	3750@80	3415@80
LT285/50R20 119/116Q	110116049	E	-	-	9.0	8.0-10.0	-	-	-	-	-	-	-	-
LT285/55R20 122/119Q	110116032	E	-	61.6	9.0	8.5-10.0	11.8	32.5	9.6	18	14.9	639	3305@80	3000@80
LT285/60R20 125/122Q	110116033	E	-	63.4	8.5	8.5-10.0	11.5	33.7	9.4	18	15.3	617	3640@80	3305@80
LT295/60R20 126/123Q	110116046	E	-	64.6	8.5	8.5-10.5	11.8	34.1	9.6	18	15.5	609	3750@80	3415@80
LT295/65R20 129/126Q	110116023	E	-	69.7	8.5	8.0-10.0	12.0	35.3	9.4	18	16.0	588	4080@80	3750@80
LT305/55R20 121/118Q	110116024	E	-	65.7	9.5	8.5-11.0	12.4	33.4	9.9	18	15.2	622	3195@65	2910@65
LT325/60R20 126/123Q	110116031	E	-	76.2	9.5	9.5-11.5	13.4	35.5	10.6	19	16.0	585	3750@65	3415@65
31X10.50R15 109Q	110116001	C	-	46.3	8.5	7.0-9.0	10.6	30.7	8.4	17	13.6	676	2270@50	-
35X12.50R17 121Q	110116003	E	-	70.3	10.0	8.5-11.0	12.8	34.8	10.0	19	15.4	598	3195@65	-
37X12.50R17 124Q	110116004	D	-	76.9	10.0	8.5-11.0	13.0	36.8	10.0	19	16.2	565	3525@50	-
37X13.50R17 121Q	110116005	E	-	80.2	11.0	8.5-11.0	14.0	36.8	10.9	19	16.2	565	3195@65	-
33X12.50R18 118Q	110116009	E	-	64.2	10.0	8.5-11.0	12.5	32.7	10.0	19	14.7	636	2910@65	-
33X12.50R18 122Q	110116034	F	-	64.1	10.0	8.5-11.0	12.6	32.7	10.0	19	14.7	636	3305@80	-
35X12.50R18 128Q	110116010	F	-	72.8	10.0	8.5-11.0	12.5	34.7	10.0	19	15.5	598	3970@80	-
37X13.50R18 128Q	110116011	E	-	80.2	11.0	8.5-11.0	13.8	36.7	10.9	19	16.3	566	3970@65	-
33X12.50R20 114Q	110116017	E	-	65.7	10.0	8.5-11.0	12.6	32.6	10.0	19	14.9	636	2600@65	-
33X12.50R20 119Q	110116035	F	-	65.6	10.0	8.5-11.0	12.7	32.7	10.0	19	14.9	636	3000@80	-
35X12.50R20 121Q	110116018	E	-	71.2	10.0	8.5-11.0	12.6	34.7	10.0	19	15.7	598	3195@65	-
35X12.50R20 125Q	110116036	F	-	71.2	10.0	8.5-11.0	12.6	34.7	10.0	19	15.7	599	3640@80	-
35X13.50R20 121Q	110116019	E	-	74.7	11.0	9.5-12.0	13.5	34.7	10.9	19	15.7	598	3195@65	-
37X12.50R20 126Q	110116020	E	-	76.9	10.0	8.5-11.0	12.9	36.7	10.0	19	16.5	566	3750@65	-
37X13.50R20 127Q	110116021	E	-	80.7	11.0	8.5-11.0	13.7	36.8	10.9	19	16.5	565	3860@65	-

(Continued next page)

GEOLANDAR X-AT®

(Continued from previous page)

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)	
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	SINGLE	DUAL
35X12.50R22 121Q	110116025	F	-	71.9	10.0	8.5 - 11.0	12.6	34.7	10.0	19	16.0	598	3195@80	-
37X12.50R22 127Q	110116026	F	-	76.7	10.0	9.0 - 11.5	12.6	36.9	10.0	19	16.8	563	3860@80	-
37X13.50R22 123Q	110116027	E	-	81.1	11.0	8.5 - 11.0	13.5	36.8	10.9	19	16.8	564	3415@65	-

GEOLANDAR M/T^{GOO3}

MUD TERRAIN SUVs/Trucks



Rock-solid engineering results in a tire capable of conquering just about anything that dares stand in its way.

FEATURES AND BENEFITS



OFF-ROAD TRACTION

An innovative tread pattern and triple-polymer compound provide outstanding grip wherever you venture.



OFF-ROAD DURABILITY

Rock-solid GEO-SHIELD[®] construction is engineered to withstand punishment from even the most brutal trail.



QUIET RIDE

Advanced pitch variation contributes to a quieter, comfortable highway ride.



LONG TREAD LIFE

High-density triple-polymer compound and wide, flat profile combine for exceptional wear performance.



TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)	
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	SINGLE	DUAL
LT215/75R15 100/97Q	110133306	C	-	32.4	6.0	5.5-7.0	8.2	28.0	6.8	17	12.6	743	1765@50	1610@50
LT235/75R15 104/101Q	110133307	C	-	37.0	6.5	6.0-7.0	8.9	29.2	7.4	17	13.0	712	1985@50	1820@50
LT225/75R16 115/112Q	110133313	E	-	43.9	6.0	6.0-7.0	8.7	29.5	7.0	17	13.3	704	2680@80	2470@80
LT235/85R16 120/116Q	110133311	E	-	50.5	6.5	6.0-7.5	9.4	32.0	7.4	17	14.2	650	3042@80	2778@80
LT245/75R16 120/116Q	110133312	E	-	48.3	7.0	6.5-8.0	10.0	30.5	7.8	17	13.6	682	3042@80	2778@80
LT255/85R16 123/120Q	110133349	E	-	54.9	7.0	6.5-8.0	10.0	33.2	7.8	18	14.7	626	3415@80	3085@80
LT265/75R16 123/120Q	110133310	E	-	54.9	7.5	7.0-8.0	10.7	31.9	8.4	18	14.2	651	3415@80	3085@80
LT285/75R16 126/123Q	110133309	E	-	60.2	8.0	7.5-9.0	11.4	33.2	9.0	19	14.7	626	3750@80	3415@80
LT305/70R16 124/121Q	110133314	E	-	64.2	9.0	8.0-9.5	12.4	33.1	10.0	20	14.7	628	3525@65	3195@65
LT315/75R16 127/124 Q	110133308	E	-	68.8	8.5	8.0-11.0	12.5	34.8	10.0	20	15.3	598	3860@65	3525@65
LT225/65R17 1007/103Q	110133339	D	-	39.2	6.5	6.0-8.0	8.6	28.7	7.2	17	13.1	723	2150@65	1930@65
LT235/80R17 120/117 Q	110133321	E	-	49.4	6.5	6.0-7.5	9.2	32.1	7.4	17	14.4	647	3085@80	2835@80
LT245/75R17 121/118 Q	110133322	E	-	51.6	7.0	6.5-7.5	9.9	31.7	7.8	17	14.2	655	3195@80	2910@80
LT255/75R17 111/108 Q	110133319	C	-	48.7	7.0	6.5-8.5	10.0	32.3	8.0	18	14.5	643	2405@50	2205@50
LT255/80R17 121/118Q	110133367	E	-	53.4	7.0	6.5-8.5	9.8	33.3	7.8	18	14.8	624	3195@80	2910@80
LT265/65R17 120/117Q	110133366	E	-	53.2	8.0	7.5-9.5	10.7	30.7	8.7	18	13.8	677	3085@80	2835@80
LT265/70R17 121/118 Q	110133315	E	-	56.4	8.0	7.0-8.5	10.9	31.9	8.7	18	14.3	651	3195@80	2910@80
LT275/70R17 121/118Q	110133368	E	-	58.2	8.0	7.0-8.5	11.0	32.4	8.9	19	14.5	640	3195@80	2910@80
LT285/70R17 121/118 Q	110133320	E	-	58.2	8.5	7.5-9.0	11.6	32.9	9.4	19	14.7	632	3195@80	2910@80
LT285/75R17 121/118Q	110133342	E	-	63.3	8.0	7.5-9.5	11.1	34.1	9.0	19	15.2	610	3195@80	2910@80
LT295/70R17 121/118 Q	110133318	E	-	65.5	8.5	7.5-10.0	12.0	33.5	9.6	20	15.0	619	3195@80	2910@80
LT275/65R18 123/120Q	110133330	E	-	58.2	8.0	7.5-9.0	10.9	32.4	9.0	19	14.6	642	3415@80	3085@80
LT275/70R18 125/122 Q	110133329	E	-	61.9	8.0	7.0-8.5	11.2	33.1	9.0	19	14.9	627	3640@80	3305@80
LT285/65R18 125/122 Q	110133328	E	-	60.4	8.5	8.0-10.0	11.6	32.8	9.4	19	14.8	633	3640@80	3305@80
LT285/70R18 127/124Q	110133346	E	-	64.2	8.5	7.5-9.5	11.4	33.9	9.0	19	15.2	612	3860@80	3525@80
LT285/75R18 129/126Q	110133343	E	-	65.7	8.0	7.5-9.5	11.2	35.0	9.0	19	15.6	594	4080@80	3750@80
LT295/70R18 129/126 Q	110133325	E	-	65.9	8.5	7.5-10.0	12.0	34.4	9.6	20	15.4	603	4080@80	3750@80
LT305/70R18 126/123 Q	110133324	E	-	69.9	9.0	8.5-10.0	12.4	34.8	10.0	20	15.5	598	3750@65	3415@65
LT315/70R18 127/124Q	110133365	E	-	71.6	9.5	8.0-10.5	12.4	35.6	10.1	20	15.9	584	3860@65	3525@65
LT275/55R20 120/117Q	110133352	E	-	57.5	8.5	7.5-9.5	10.9	32.2	9.1	19	14.7	646	3085@80	2835@80
LT275/65R20 126/123 Q	110133335	E	-	64.8	8.0	7.5-9.5	11.0	34.3	9.0	19	15.6	605	3750@80	3415@80
LT295/55R20 123/120 Q	110133344	E	-	63.9	9.5	8.0-10.0	12.0	33.0	9.9	20	15.1	629	3415@80	3085@80
LT295/60R20 126/123 Q	110133336	E	-	66.8	8.5	8.0-10.0	11.7	34.1	9.6	20	15.5	609	3750@80	3415@80
LT295/65R20 129/126Q	110133364	E	-	69.2	8.5	8.5-10.5	11.6	35.3	9.6	20	16.0	589	4080@80	3750@80
LT305/55R20 121/118 Q	110133333	E	-	65.0	9.5	8.5-11.0	12.4	33.4	10.0	20	15.2	622	3195@65	2910@65
LT305/55R20 125/122Q	110133358	F	-	64.9	9.5	9.0-11.0	12.4	33.5	10.0	20	15.3	620	3640@80	3305@80
LT315/60R20 125/122Q	110133350	D	-	71.9	9.5	8.5-11.0	12.8	35.0	10.4	20	15.9	593	3640@65	3305@65
LT285/55R22 124/121Q	110133347	E	-	63.9	9.0	8.0-10.0	11.6	34.8	9.5	19	16.0	598	3525@80	3195@80
LT325/50R22 122Q	110133351	E	-	75.8	10.0	9.0-12.0	13.1	35.1	10.8	20	16.1	592	3305@65	-
30X9.50R15 104Q	110133305	C	-	40.8	7.5	6.5-8.5	9.6	29.8	7.7	19	13.3	698	1985@50	-
31X10.50R15 109Q	110133301	C	-	47.6	8.5	7.0-9.0	10.9	30.6	8.6	19	13.6	678	2270@50	-
32X11.50R15 113Q	110133303	C	-	55.1	9.0	8.0-10.0	11.8	31.7	9.3	20	14.0	655	2535@50	-
33X12.50R15 108Q	110133304	C	-	57.1	10.0	8.5-11.0	13.0	32.6	10.2	21	14.3	638	2205@35	-
35X12.50R15 113Q	110133302	C	-	67.2	10.0	8.5-11.0	13.0	34.6	10.2	21	15.2	600	2535@35	-
33X12.50R17 120Q	110133323	E	-	64.8	10.0	8.5-11.0	12.8	32.6	10.2	21	14.6	636	3085@65	-
35X12.50R17 121Q	110133316	E	-	70.8	10.0	8.5-11.0	13.2	34.7	10.2	21	15.4	598	3195@65	-
37X12.50R17 124Q	110133317	D	-	76.1	10.0	8.5-11.0	13.1	36.8	10.2	21	16.2	565	3525@50	-
40X13.50R17 121Q	110133353	D	-	86.9	11.0	8.5-11.0	14.2	39.7	10.9	21	17.3	523	3195@50	-

(Continued next page)

GEOLANDAR M/T[®] G003

(Continued from previous page)

TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)	
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	SINGLE	DUAL
33X12.50R18 118Q	110133327	E	-	65.0	10.0	8.5 - 11.0	12.8	32.6	10.2	21	14.7	637	2910@65	-
33X12.50R18 122Q	110133360	F	-	64.9	10.0	8.5 - 11.0	12.7	32.7	10.2	21	14.7	635	3305@80	-
35X12.50R18 123Q	110133326	E	-	71.6	10.0	8.5 - 11.0	12.9	34.7	10.2	21	15.5	598	3415@65	-
35X12.50R18 128Q	110133361	F	-	71.5	10.0	8.5 - 11.0	13.1	34.8	10.2	21	15.5	598	3970@80	-
33X12.50R20 114Q	110133332	E	-	64.8	10.0	8.5 - 11.0	12.7	32.7	10.2	21	14.9	636	2600@65	-
33X12.50R20 119Q	110133362	F	-	66.1	10.0	8.5 - 11.0	12.6	32.7	10.2	21	15.0	635	3000@80	-
35X11.50R20 124Q	110133357	E	-	67.7	9.0	8.0 - 10.5	11.3	34.8	9.3	21	15.8	597	3525@80	-
35X12.50R20 121Q	110133331	E	-	71.2	10.0	8.5 - 11.0	12.6	34.7	10.2	21	15.7	598	3195@65	-
35X12.50R20 125Q	110133359	F	-	71.3	10.0	8.5 - 11.0	12.6	34.8	10.2	21	15.8	597	3640@80	-
35X13.50R20 126Q	110133370	F	-	76.3	11.0	9.5 - 12.0	13.7	34.7	11.1	21	15.7	599	3750@80	-
37X12.50R20 126Q	110133337	E	-	76.7	10.0	8.5 - 11.0	12.8	36.7	10.2	21	16.5	566	3750@65	-
37X13.50R20 127Q	110133334	E	-	80.9	11.0	8.5 - 11.0	13.9	36.6	11.1	21	16.5	567	3860@65	-
33X12.50R22 109Q	110133354	E	-	65.4	10.0	8.5 - 11.0	12.2	32.8	10.4	21	15.2	634	1030@65	-
35X12.50R22 117Q	110133348	E	-	70.1	10.0	8.5 - 11.0	12.8	34.7	10.2	21	16.0	598	2835@65	-
35X12.50R22 121Q	110133363	F	-	71.3	10.0	8.5 - 11.0	12.7	34.8	10.2	21	16.0	598	3195@80	-
37X12.50R22 123Q	110133341	E	-	76.9	10.0	9.0 - 11.5	12.1	36.9	10.2	21	16.8	564	3415@65	-
37X13.50R22 123Q	110133340	E	-	80.7	11.0	8.5 - 11.0	13.1	36.8	11.1	21	16.8	564	3415@65	-
37X13.50R24 120Q	110133345	E	-	77.8	11.0	8.5 - 11.0	13.2	36.9	11.1	21	17.0	564	3085@65	-

GEOLANDAR X-MT®

MUD TERRAIN SUVs/Trucks



The hardest of hard-core off-road tires in the GEOLANDAR family takes you to the top without looking back.

FEATURES AND BENEFITS



EXTREME OFF-ROAD TRACTION

High void-to-lug ratio and deep side blocks provide game-changing traction on even the steepest climbs.



OFF-ROAD DURABILITY

With GEO-SHIELD® construction wrapped in a high-density compound, hazardous terrain will never look the same.



LONG TREAD LIFE

High-density, triple-polymer tread compound produces slow, even wear.



QUIET RIDE

Optimized tread pattern reduces pattern noise for a quieter, more comfortable on-road ride.



reddot award 2019
winner



TIRE SIZE	PART NO.	LOAD I.D.	UTQG RATING	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
					MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
35X12.50R17 121Q	110155501	E	-	75.0	10.0	8.5 - 11.0	13.0	34.8	10.2	21	15.4	598	3195@65
37X12.50R17 121Q	110155504	D	-	80.2	10.0	8.5 - 11.0	13.0	36.8	10.2	21	16.2	565	3525@50
37X13.50R17 121Q	110155505	E	-	84.0	11.0	8.5 - 11.0	13.9	36.7	11.1	21	16.2	566	3195@65
40X13.50R17 121Q	110155509	D	-	93.5	11.0	8.5 - 11.0	14.2	39.7	11.1	21	17.3	523	3195@50
35X12.50R18 123Q	110155502	E	-	75.4	10.0	8.5 - 11.0	13.1	34.8	10.2	21	15.5	598	3415@65
37X13.50R18 124Q	110155506	D	-	84.0	11.0	8.5 - 11.0	14.0	36.7	11.1	21	16.3	566	3525@50
38X13.50R18 126Q	110155516	D	-	85.3	11.0	9.0 - 11.5	13.7	37.6	11.1	21	16.7	552	3750@50
38X15.50R18 128Q	110155517	D	-	120.7	12.5	11.0 - 14.0	15.7	37.7	12.2	21	16.7	551	3970@50
35X12.50R20 121Q	110155503	E	-	74.5	10.0	8.5 - 11.0	12.7	34.8	10.2	21	15.8	597	3195@65
38X13.50R20 128Q	110155507	E	-	86.9	11.0	9.5 - 12.0	13.8	37.7	11.1	21	16.9	551	3970@65
38X15.50R20 125Q	110155508	D	-	91.0	12.0	11.0 - 14.0	15.2	37.7	12.2	21	16.9	551	3640@50
40X15.50R20 128Q	110155510	D	-	97.2	12.0	11.0 - 14.0	15.2	39.8	12.2	21	17.7	522	3970@50
38X13.50R22 126Q	110155514	E	-	86.0	11.0	9.5 - 12.0	13.9	37.7	11.1	21	17.1	551	3750@65
38X15.50R22 128Q	110155515	E	-	92.8	12.5	11.0 - 14.0	15.4	37.7	12.2	21	17.1	551	3970@65
40X15.50R22 128Q	110155511	E	-	98.5	12.0	11.0 - 14.0	15.1	39.8	12.2	21	17.9	522	3970@65
38X13.50R24 123Q	110155512	E	-	86.6	11.0	8.5 - 11.0	13.7	37.8	11.1	21	17.4	550	3415@65
40X15.50R24 128Q	110155513	E	-	98.1	12.5	11.0 - 14.0	15.4	39.9	12.2	21	18.2	521	3970@65

WINTER TIRES

Confident winter handling no matter what the season brings.

BluEarth[®]*WINTER V906

BluEarth[®]*WINTER V906 SUV

iceGUARD[®] iG53

iceGUARD[®] G075

BluEarth[®] *WINTER[®] V906 BluEarth[®] *WINTER[®] V906 SUV



WINTER Performance Cars | CUVs | SUVs

The V & W- speed rated BluEarth Winter V906 and V906 SUV are Yokohama's all-new winter performance tires for sedans, CUVs and smaller SUVs.



FEATURES AND BENEFITS



OUTSTANDING SNOW TRACTION

Advanced polymer compound and adaptive 3D Sipes provide powerful traction on ice and snow.



EXCELLENT WET PERFORMANCE

A silica rich compound provides superior performance on wet and icy road surfaces.



SUPERIOR HANDLING

A directional tread and robust construction provide responsive handling on all winter road surfaces.



RELIABLE TREAD LIFE

Uniform tread blocks are positioned to improve overall road contact and promote even tread wear.

TIRE SIZE	PART NO.	LOAD I.D.	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
				MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
205/55R16 94V	110109601	XL	21.3	6.5	5.5 - 7.5	8.3	25.1	6.7	11	11.6	827	1477@50
205/50R17 93V	110109617	XL	21.1	6.5	5.5 - 7.5	8.3	25.2	6.7	11	11.7	826	1433@50
205/55R17 95V	110109603	XL	22.8	6.5	5.5 - 7.5	8.3	26.3	6.6	11	12.1	790	1521@50
215/50R17 95V	110109608	XL	22.9	7.0	6.0 - 7.5	8.8	25.6	7.0	10	11.9	812	1521@50
215/55R17 98V	110109604	XL	24.9	7.0	6.0 - 7.5	8.9	26.6	6.9	10	12.2	781	1653@50
215/65R17 99V	110109602	SL	24.0	6.5	6.0 - 7.5	8.6	28.4	6.2	11	12.9	732	1709@51
225/45R17 94V	110109607	XL	23.3	7.5	7.0 - 8.5	9.0	25.2	7.2	10	11.7	824	1477@50
225/50R17 98V	110109606	XL	25.3	7.0	6.0 - 8.0	9.1	26.1	7.3	10	12.0	796	1653@50
225/55R17 101V	110109605	XL	25.7	7.0	6.0 - 8.0	9.3	27.1	7.3	10	12.4	767	1819@50
235/55R17 103V	110109623*	XL	26.3	7.5	6.5 - 8.5	9.5	27.4	7.6	10	12.6	757	1929@50
225/40R18 92W	110109612	XL	22.5	8.0	7.5 - 9.0	9.1	25.1	7.2	10	11.8	827	1389@50
225/45R18 95V	110109616	XL	24.5	7.5	7.0 - 8.5	8.8	26.1	7.3	10	12.1	797	1521@50
225/50R18 95V	110109611	SL	26.2	7.0	6.0 - 8.0	9.2	27.0	7.3	10	12.5	768	1521@51
225/50R18 99V	110109610	XL	26.5	7.0	6.0 - 8.0	9.1	27.0	7.3	10	12.5	768	1709@50
225/55R18 102V	110109622*	XL	27.0	7.0	6.0 - 8.0	9.1	28.0	7.3	10	12.9	743	1874@50
235/45R18 98V	110109615	XL	25.2	8.0	7.5 - 9.0	9.3	26.6	7.6	10	12.3	782	1653@50
245/40R18 97W	110109614	XL	24.9	8.5	8.0 - 9.5	9.7	25.9	8.0	10	12.1	801	1609@50
245/45R18 100V	110109613	XL	26.9	8.0	7.5 - 9.0	9.6	26.9	8.0	10	12.5	773	1764@50
235/55R20 102V	110109620*	SL	30.6	7.5	6.5 - 8.5	9.6	30.3	7.6	10	14.0	685	1874@51
275/45R20 110V	110109618*	XL	34.9	9.0	8.5 - 10.5	10.9	30.0	8.9	10	13.9	692	2337@50
305/40R20 112V	110109619*	XL	37.4	11.0	10.0 - 12.0	12.6	30.0	10.3	10	13.9	693	2469@50
295/40R21 111V	110109621*	XL	37.0	10.5	10.0 - 11.5	12.0	30.6	10.1	10	14.2	679	2403@50

*SUV sizes

ice GUARD[®] iG53

WINTER Passenger Cars



An advanced studless winter tire for confident traction on ice and snow when you need it most.

FEATURES AND BENEFITS



EXCELLENT SNOW TRACTION

Advanced tread design provides hundreds of biting edges for confident snow traction.



COMPETITIVE ICE TRACTION

Absorptive compound improves grip in icy conditions and provides greater resistance to wear.



FUEL EFFICIENT

Unique construction and compound combine to create a fuel efficient design.



PREDICTABLE HANDLING

Distinctive uni-directional tread design enhances road contact for better handling in all conditions.



TIRE SIZE	PART NO.	LOAD I.D.	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (3/32 INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
				MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
175/70R14 84T	110115320	SL	16.0	5.0	4.5 - 6.0	7.0	23.9	5.8	11	10.9	868	1102@51
195/65R15 91T	110115325	SL	19.0	6.0	5.5 - 7.0	8.0	25.2	6.5	11	11.5	823	1356@51
195/50R16 84H	110115326	SL	18.1	6.0	5.5 - 7.0	7.8	23.7	6.7	11	11.0	877	1102@51
205/65R16 95T	110115329	SL	22.6	6.0	5.5 - 7.5	8.3	26.6	6.8	11	12.1	782	1521@50
225/60R16 98T	110115332	SL	24.5	6.5	6.0 - 8.0	8.9	26.9	7.5	12	12.2	774	1653@51
205/50R17 93H	110115333	XL	23.1	6.5	5.5 - 7.5	8.3	25.2	7.2	11	11.7	826	1433@50
215/45R17 87H	110115334	SL	21.4	7.0	7.0 - 8.0	8.3	24.6	7.5	11	11.5	843	1201@51
215/65R17 99T	110115336	SL	25.6	6.5	6.0 - 7.5	8.7	28.0	7.2	11	12.8	741	1709@51
225/45R17 91H	110115337	SL	23.1	7.5	7.0 - 8.5	8.8	25.1	7.8	11	11.7	828	1356@51
235/45R17 97H	110115340	XL	25.8	8.0	7.5 - 9.0	9.3	25.6	8.2	12	11.8	813	1609@50
235/55R17 99H	110115341	SL	26.5	7.5	6.5 - 8.5	9.6	27.3	8.2	12	12.5	760	1709@51
245/45R17 99H	110115342	XL	26.9	8.0	7.5 - 9.0	9.5	25.9	8.7	12	12.0	803	1709@50
215/55R18 95H	110115343	SL	25.8	7.0	6.0 - 7.5	8.9	27.5	7.5	11	12.7	756	1521@51
225/40R18 92H	110115344	XL	22.7	8.0	7.5 - 9.0	9.1	25.1	7.8	11	11.8	827	1389@50
225/45R18 95H	110115345	XL	25.1	7.5	7.0 - 8.5	8.9	25.9	7.8	11	12.1	802	1521@51
225/50R18 95H	110115346	SL	26.0	7.0	6.0 - 8.0	9.1	27.0	7.8	11	12.5	769	1521@51
235/45R18 94H	110115347	SL	24.9	8.0	7.5 - 9.0	9.3	26.5	8.2	12	12.3	785	1477@51
235/50R18 101H	110115348	XL	28.7	7.5	6.5 - 8.5	9.4	27.6	8.2	12	12.7	754	1819@50
245/40R18 97H	110115349	XL	26.7	8.5	8.0 - 9.5	9.6	25.9	8.7	12	12.1	802	1609@50
245/50R18 104H	110115351	XL	30.2	7.5	7.0 - 8.5	9.8	27.9	8.7	12	12.9	745	1984@50

iceGUARD® G075

WINTER Crossovers/SUVs | Minivans | Trucks



The ultimate snowshoes for maximum winter grip in your SUV, crossover or light truck.

FEATURES AND BENEFITS



EXCELLENT WINTER TRACTION

Three dimensional sipes and micro-edges provide biting edges that grip the snow.



ON-ROAD DURABILITY

Durable tread compound resists wear and provides more stability for CUVs and SUVs.



FUEL EFFICIENT

Special construction and compound create a fuel-efficient design.



PRECISE HANDLING

Distinctive uni-directional tread design enhances road contact for better handling in all conditions.



TIRE SIZE	PART NO.	LOAD I.D.	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)
				MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REV PER MILE	
225/70R16 103T	110175101	SL	28.9	6.5	6.0 - 7.5	8.8	28.4	7.4	13	12.8	732	1929@51
235/70R16 106T	110175102	SL	32.4	7.0	6.0 - 8.0	9.3	28.9	7.7	13	13.0	718	2094@51
265/70R16 112S	110175103	SL	35.7	8.0	7.0 - 9.0	10.6	30.4	8.7	14	13.6	683	2469@51
225/65R17 102T	110175105	SL	29.3	6.5	6.0 - 8.0	8.9	28.5	7.3	13	13.0	730	1874@51
235/60R17 102T	110175106	SL	28.7	7.0	6.5 - 8.5	9.4	28.0	7.7	13	12.8	742	1874@51
235/65R17 108T	110175107	XL	32.2	7.0	6.5 - 8.5	9.5	29.0	7.7	13	13.2	717	2205@50
245/65R17 107T	110175108	SL	33.3	7.0	7.0 - 8.5	9.8	29.4	8.0	13	13.3	707	2149@51
245/70R17 110T	110175109	SL	34.8	7.0	6.5 - 8.0	9.6	30.5	8.0	13	13.8	681	2337@51
265/65R17 112S	110175110	SL	37.5	8.0	7.5 - 9.5	10.7	30.4	8.7	13	13.7	683	2469@51
265/70R17 115S	110175111	SL	38.8	8.0	7.0 - 9.0	10.6	31.6	8.7	14	14.2	658	2679@51
225/60R18 100T	110175113	SL	28.9	6.5	6.0 - 8.0	8.9	28.5	7.3	13	13.1	729	1764@51
235/60R18 107T	110175115	XL	31.7	7.0	6.5 - 8.5	9.3	29.0	7.7	13	13.3	716	2149@50
235/65R18 106T	110175116	SL	32.8	7.0	6.5 - 8.5	9.3	29.9	7.7	13	13.6	694	2094@51
245/60R18 105T	110175117	SL	34.0	7.0	7.0 - 8.5	9.7	29.4	8.0	13	13.4	706	2039@51
255/55R18 109T	110175118	XL	35.5	8.0	7.0 - 9.0	10.4	29.1	8.9	13	13.3	714	2271@50
255/60R18 112T	110175119	XL	35.1	7.5	7.0 - 9.0	10.2	30.0	8.3	13	13.7	692	2469@50
255/70R18 113T	110175141	SL	39.1	7.5	6.5 - 8.5	10.1	32.1	8.3	13	14.5	647	2535@51
265/60R18 110S	110175120	SL	37.5	8.0	7.5 - 9.5	10.6	30.4	8.7	13	13.8	683	2337@51
285/60R18 116T	110175121	SL	42.1	8.5	8.0 - 10.0	11.4	31.4	9.3	13	14.2	661	2756@51
225/55R19 99T	110175122	SL	30.0	7.0	6.0 - 8.0	9.1	28.8	7.9	13	13.3	721	1709@51
235/50R19 99T	110175145	SL	30.4	7.5	6.5 - 8.5	9.7	28.2	8.3	13	13.1	736	1709@51
235/55R19 101T	110175123	SL	30.6	7.5	6.5 - 8.5	9.6	29.1	8.3	13	13.4	714	1819@51
245/55R19 103T	110175124	SL	33.1	7.5	7.0 - 8.5	9.9	29.6	8.6	14	13.6	703	1929@51
255/50R19 107T	110175125	XL	34.2	8.0	7.0 - 9.0	10.4	29.1	8.9	14	13.4	714	2149@50
255/55R19 111T	110175126	XL	35.7	8.0	7.0 - 9.0	10.4	30.0	9.0	14	13.8	693	2403@50
265/50R19 110T	110175127	XL	35.5	8.5	7.5 - 9.5	10.9	29.3	9.3	14	13.5	708	2337@50
245/50R20 102T	110175129	SL	33.1	7.5	7.0 - 8.5	9.8	29.6	8.6	14	13.8	701	1874@51
255/50R20 109T	110175130	XL	35.3	8.0	7.0 - 9.0	10.2	30.0	9.0	14	13.9	692	2271@50
265/45R20 108T	110175146	XL	36.0	9.0	8.5 - 10.0	10.7	29.3	9.3	14	13.6	709	2205@50
265/50R20 111T	110175131	XL	37.9	8.5	7.5 - 9.5	10.9	30.3	9.3	14	14.0	685	2403@50
275/40R20 106T	110175132	XL	35.1	9.5	9.0 - 11.0	10.9	28.6	9.6	14	13.3	727	2094@50
275/45R20 110T	110175133	XL	36.6	9.0	8.5 - 10.5	10.8	29.6	9.6	14	13.7	702	2337@50
275/55R20 117T	110175134	XL	40.6	8.5	7.5 - 9.5	11.2	31.9	9.6	14	14.6	652	2833@50
275/60R20 116S	110175140	XL	42.9	8.0	7.5 - 9.5	11.0	32.8	9.6	14	15.0	633	2756@50
285/50R20 112T	110175135	SL	41.4	9.0	8.0 - 10.0	11.6	31.1	10.0	14	14.3	669	2469@51
295/35R21 107T	110175136	XL	37.7	10.5	10.0 - 11.5	11.8	29.2	10.3	14	13.7	711	2149@50

LIGHT TRUCK COMMERCIAL/UTILITY

Multi-purpose utility without compromise.

Y356
TY213B



Y356 UTILITY

The **Y356** meets the multi-purpose needs of many light trucks, minivans, and light utility vehicles. A comfortable ride, good wet-road traction and sure-footed dry-road handling without excessive tire noise is delivered by the three-groove tread block pattern and three-pitch variations. Strength and versatility of the **Y356** is provided by tough two-ply steel-belt plus two-ply polyester construction, while use of a special tread compound prolongs tread life.

FEATURES AND BENEFITS

Heavy-Duty, Two Steel Plus Nylon Belt Edge Construction delivers durability and a stable ride.

Three-Groove Tread Block Pattern produces a comfortable ride.

New Light Truck Tread Compound prevents steel belt edge rise during high speeds.

Zig-Zag Groove and Three-Pitch Variation Block Pattern reduces hydroplaning in rain for better high-speed traction.

Two-Ply Polyester Carcass Body Construction reduces tire pattern noise during highway driving.

H-Performance Rated up to 130 MPH.



TIRE SIZE	PART NO.	LOAD I.D.	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)	
				MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)		STATIC RADIUS (INCHES)	REV PER MILE	SINGLE	DUAL
LT185R14 (D)	110135603	D	24.3	5.5	5.0 - 6.0	7.10	25.7	11	12	809	1850@65	1765@65
LT195/75R14 99/96 (D)	110135602	D	23.3	5.5	5.0 - 6.0	7.40	25.8	11	12	808	1710@65	1565@65

TY213B UTILITY/COMMERCIAL

The **TY213B** is designed for outstanding stability, reliable water drainage and lasting tread life for highway and urban applications.

FEATURES AND BENEFITS

Five Rib Design with new, wider tread offers improved handling and excellent all-weather traction.

Shallow Grooves and Improved Compounding reduce rolling resistance for improved fuel efficiency.

Combination Construction featuring a polyester casing and ultra-tough steel belts provides outstanding durability.

Load Range E capacity handles heavy duty applications.



TIRE SIZE	PART NO.	LOAD I.D.	UNIT WEIGHT (LBS.)	RIM WIDTH		INFLATED DIMENSIONS		TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX. LOAD AT COLD INFLATION PRESSURE (LBS@PSI)	
				MEASURED (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)		STATIC RADIUS (INCHES)	REV PER MILE	SINGLE	DUAL
LT215/85R16 10	140133214	E	38.0	6.0	5.5 - 7.0	8.6	30.5	14	14.0	685.0	2680@80	2470@80

ORIGINAL EQUIPMENT REFERENCE MANUAL

Tires listed in this section can also be used as replacement tires. In addition, we offer a wide variety of replacement fitments for the passenger and light truck categories.

AUDI
BMW
CHRYSLER
DODGE
INFINITI
LEXUS
LOTUS

MAZDA
MERCEDES-BENZ
MITSUBISHI
NISSAN
PORSCHE
RAM
SCION

SMART
SUBARU
SUZUKI
TOYOTA
VOLKSWAGEN

CONSUMER PASSENGER, LIGHT TRUCK AND SUV

OE REFERENCE CHART

MODEL	TIRE SIZE	TIRE NAME	PART #	YEAR
Audi				
A6	255/40R19 100YXLAO	ADVAN Sport (V103S)	110110676	2013-2017
A6	255/40R19 100Y XL AOE	ADVAN Sport (V103S)	110110313	2013-2017
A7	265/35R20 99Y XL AO	ADVAN Sport (V103S)	110110315	2011-2017
A7	255/40R19 100Y XL AO	ADVAN Sport (V103S)	110110313	2013-2017
A7	255/40R19 100Y XL AO	ADVAN Sport (V103S)	110110676	2013-2017
S6	255/40R19 100Y XL AO	ADVAN Sport (V103S)	110110676	2013-2017
S7	265/35R20 99Y XL AO	ADVAN Sport (V103S)	110110315	2011-2017
S7	255/40R19 100Y XL AO	ADVAN Sport (V103S)	110110676	2013-2017
Q7	265/50R19 110Y XL AO	ADVAN Sport (V103B)	110110339	2009-2015
Q7	275/45R20 110Y XL AO	ADVAN Sport (V103B)	110110340	2009-2015
BMW				
M3 - F	275/40ZR18 (103Y)	ADVAN Sport (V107E)	110193380	2021-2022
M3 - R	285/35ZR19 (103Y)	ADVAN Sport (V107E)	110193381	2021-2022
M4 - F	275/40ZR18 (103Y)	ADVAN Sport (V107E)	110193380	2021-2022
M4 - R	285/35ZR19 (103Y)	ADVAN Sport (V107E)	110193381	2021-2022
M5 - F	275/40ZR19 (105Y)	ADVAN Sport (V105)	110193337	2018-2022
M5 - R	285/40ZR19 (107Y)	ADVAN Sport (V105E)	110193338	2018-2022
X3	225/60R18 104W	ADVAN Sport (V107D)	110133809	2019-2022
X4	225/60R18 104W	ADVAN Sport (V107D)	110133809	2019-2022
X3	245/50R19 105W	ADVAN Sport ZPS (V105)	110133802	2018-2022
X4	245/50R19 105W	ADVAN Sport ZPS (V105)	110133802	2018-2022
X3 - F	245/45R20 103Y	ADVAN Sport (V105T)	110133805	2018-2022
X3 - R	275/40R20 106Y	ADVAN Sport (V105E)	110133804	2018-2022
X4 - F	245/45R20 103Y	ADVAN Sport (V105T)	110133805	2018-2022
X4 - R	275/40R20 106Y	ADVAN Sport (V105E)	110133804	2018-2022
X5 - F	275/40R21 107Y	ADVAN Sport (V105)	110133807	2018-2021
X5 - F	275/40R21 107Y	ADVAN Sport (V107E)	110133813	2022
X5 - R	315/35R21 111Y	ADVAN Sport (V107E)	110133814	2022
X5 - R	315/35R21 111Y	ADVAN Sport (V105E)	110133808	2018-2021
X6 - F	275/40R21 107Y	ADVAN Sport (V105)	110133807	2018-2021
X6 - F	275/40R21 107Y	ADVAN Sport (V107E)	110133813	2022
X6 - R	315/35R21 111Y	ADVAN Sport (V105E)	110133808	2018-2021
X6 - R	315/35R21 111Y	ADVAN Sport (V107E)	110133814	2022
CHRYSLER				
Jeep Compass	225/55R18 98H	GEOLANDAR G055	110133531	2019-2022
Pacifica	235/65R17 104T	AVID S34RV	110133527	2017-2022
Town & Country	225/65R16 100S	AVID S33	110133506	2008-2014
Town & Country	225/65R17 102T	AVID S33B	110133510	2013-2016
Voyager	235/65R17 104T	AVID S34RV	110133527	2020-2022
Dodge				
Dart	225/45R17 91H	AVID S34PV	110133524	2014-2016
Dart	225/40R18 92V	AVID S34NV	110133523	2013-2016
Grand Caravan	225/65R16 100S	AVID S33	110133506	2008-2014
Grand Caravan	225/65R17 102T	AVID S33B	110133510	2013-2020
Infiniti				
Infiniti G37	P225/45R19 92V	ADVAN A83A	110183050	2011-2016
Lexus				
GS350	225/50R17 94W	ADVAN A10F	110193212	2007-2012
GS450h	245/40R18 93Y	ADVAN A10F	110193213	2007-2012
GS460	245/40R18 93Y	ADVAN A10F	110193213	2008-2012
NX	225/65R17 102H	GEOLANDAR G91AV	110193235	2015-2021
NX	225/60R18 100H	GEOLANDAR G91HV	110193246	2015-2021
Lotus				
Elise - F	175/55R16 80W	ADVAN Neova AD07	110107035	2004-2018
Elise - R	225/45R17 91W	ADVAN Neova AD07	110107036	2004-2018
Elise Cup 250 - F	195/50R16 88W	ADVAN A052	110105274	2018-2021
Elise Cup 250 - R	225/45R17 94W	ADVAN A052	110105276	2018-2021
Elise S Cup - F	195/50R16 84W	ADVAN A048	110104804	2016-2018
Elise S Cup - F	195/50R16 88W	ADVAN A052	110105274	2019-2020
Elise S Cup - R	225/45R17 90W	ADVAN A048	110104805	2016-2018
Elise Sport - R	225/45R17 91W	ADVAN Sport (V105)	110110516	2018-2021
Elise Sport - R	225/45R17 90W	ADVAN A048	110104805	2004-2014
Elise Sport 220 - F	195/50R16 84W	ADVAN Sport V105	110193353	2019-2021
Elise Sport 220 - R	225/45R17 91W	ADVAN Sport (V105)	110110516	2018-2021
Elise Sprint - F	195/50R16 84W	ADVAN Sport V105	110193353	2019-2021
Elise Sprint - R	225/45R17 91W	ADVAN Sport (V105)	110110516	2018-2021
Elise Sprint 220 - F	195/50R16 84W	ADVAN Sport V105	110193353	2019-2021
Elise Sprint 220 - R	225/45R17 91W	ADVAN Sport (V105)	110110516	2018-2021
Exige - F	195/50R16 84W	ADVAN A048	110104804	2004-2014
Exige - R	225/45R17 90W	ADVAN A048	110104805	2004-2014
Mazda				
CX-3	P215/60R16 94H	AVID S34FV	110193250	2016-2022
CX-3	P215/50R18 92V	AVID S34FV	110193251	2016-2022
CX-5	P225/65R17 100H	GEOLANDAR G91A	110193229	2012-2022
CX-9	P255/60R18 107H	GEOLANDAR H/T G056B	110193258	2016-2017
Mazda2	185/55R15 82V	AVID S34F	110193225	2011-2014
Mazda3	P205/60R16 91H	AVID S34FV	110193239	2014-2019
Mazda3	P205/50R17 88V	AVID S34D	110193217	2009-2014
Mazda5	P205/50R17 88V	AVID S34D	110193217	2009-2014
Mazda6	P225/55R17 95V	ADVAN A83A	110183051	2013-2017
Mazda6	P225/55R17 95V	ADVAN A83B	110193340	2018-2021
MX-5 Miata	205/50R16 87V	ADVAN A11A	110193207	2006-2015
MX-5 Miata Sport	195/50R16 84V	ADVAN Sport (V105)	110110603	2016-2021
MERCEDES-BENZ				
A/B Class	225/45R17 91W M0	ADVAN Sport (V105)	110110516	2015-2018
AMG C63-F	235/35ZR19 91Y XL M0	ADVAN Sport (V103S)	110110331	2008-2014
AMG C63-R	255/30ZR19 91Y XL M0	ADVAN Sport (V103S)	110110332	2008-2014
AMG G63	275/50R20 113W M0	ADVAN S.T. V802	110180241	2013-2018
AMG G65	275/50R20 113W M0	ADVAN S.T. V802	110180241	2013-2018
AMG GLA	235/50ZR19 99Y M01	ADVAN Sport V107F	110133225	2020-2022
AMG GLA	255/35ZR21 98Y M01	ADVAN Sport V107F	110133226	2020-2022
AMG GLE	275/50ZR20 113Y M0	ADVAN Sport V107D	110133220	2020-2022
GLE Coupe	275/50ZR20 113Y M0	ADVAN Sport V107D	110133220	2020-2022
AMG GLE	285/40ZR22 110Y M0	ADVAN Sport V107C	110133221	2020-2022
GLE Coupe	285/40ZR22 110Y M0	ADVAN Sport V107C	110133221	2020-2022
AMG GLE	325/35ZR22 114Y M0	ADVAN Sport V107D	110133222	2020-2022
GLE Coupe	325/35ZR22 114Y M0	ADVAN Sport V107D	110133222	2020-2022
AMG GLS	285/45ZR22 114Y M0	ADVAN Sport V107C	110133223	2020-2022
AMG GLS	325/40ZR22 114Y M0	ADVAN Sport V107D	110133224	2020-2022
AMG ML 63	295/40ZR20 106Y M0	ADVAN Sport (V103A)	110193214	2008-2009
C-Class (W205) F	225/45R18 95Y XL M0	ADVAN Sport (V105)	110110632	2016-2018
C-Class (W205) R	245/40R18 97Y XL M0	ADVAN Sport (V105)	110110633	2016-2018
C-Class (W205)	225/50R17 94W M0	ADVAN Sport (V105)	110110631	2016-2017
E-Class Coupe (S50)	235/35ZR19 91Y XL M0	ADVAN Sport (V103S)	110110331	2011-2014
E-Class Coupe (S50)	255/30ZR19 91Y XL M0	ADVAN Sport (V103S)	110110332	2011-2014
E-Class (E53 AMG Sport) (BR213) F	245/40ZR19 (98Y) XL M0	ADVAN Sport (V105)	110110634	2017-2022
E-Class (E53 AMG Sport) (BR213) R	275/35ZR19 (100Y) XL M0	ADVAN Sport (V105)	110110635	2017-2022

CONSUMER PASSENGER, LIGHT TRUCK AND SUV

OE REFERENCE CHART

MODEL	TIRE SIZE	TIRE NAME	PART #	YEAR
E-Class (E53 AMG Sport) (BR213) F	245/35ZR20 (95Y) XL M0	ADVAN SPORT (V105)	110110636	2017-2022
E-Class (E53 AMG Sport) (BR213) R	275/30ZR20 (97Y) XL M0	ADVAN Sport (V105)	110110637	2017-2022
G500	265/60R18 110V	GEOLANDAR G038G	110103830	2002-2015
GLA	235/50R18 97V M0	C.drive2	110102813	2014-2020
GLA	235/50R18 97V MOE	C.drive2 ZPS	110102814	2014-2020
S	245/50R18 100W M0	ADVAN Sport (V105C)	110110640	2013-2020
SL (F)	255/40R18 95Y M0	ADVAN Sport (V105+)	110110518	2012-2020
SL (R)	285/35R18 97Y M0	ADVAN Sport (V105+)	110110519	2012-2020
SL (BR213) F	255/35ZR19 (96Y) M0	ADVAN Sport (V105S)	110110638	2016-2020
SL (BR213) R	285/30ZR19 (98Y) M0	ADVAN Sport (V105S)	110110639	2016-2020
SLK /SLC	225/45R17 91W M0	ADVAN Sport (V105)	110110516	2012-2020
SLK /SLC	245/40R17 91W M0	ADVAN Sport (V105)	110110517	2012-2020
Mitsubishi				
Lancer DE	P205/60R16 91H	AVID S34B	110190004	2007-2017
Lancer ES	P205/60R16 91H	AVID S34B	110190004	2007-2017
Lancer Evolution X	245/40R18 93Y	ADVANA13C	110193215	2008-2016
Lancer Ralliart	215/45R18 89W	ADVANA10A	110193216	2009-2017
Outlander	P215/70R16 99H	GEOLANDAR H/T G033	110103332	2013-2015
Outlander	P215/70R16 99H	GEOLANDAR H/T G033	110103333	2015-2021
Outlander Sport	P215/70R16 99H	GEOLANDAR H/T G033	110103331	2006-2014
Nissan				
370Z - F	225/50R18 95W	ADVAN Sport (V103E)	110110337	2009-2016
370Z - R	245/45R18 96W	ADVAN Sport (V103F)	110110338	2009-2016
Murano	P235/65R18 104T	GEOLANDAR SUV G055E	110193232	2013-2015
Nismo 370Z - F	245/40ZR19 98 (Y)	ADVAN SPORT (V103)	110110131	2009-2014
Rogue	225/65R17 102H	GEOLANDAR G91AV	110193315	2016-2021
Rogue	235/60R18 103H	GEOLANDAR X-CV G99A	110193374	2021-2022
Rogue Sport	215/65R16 98H	GEOLANDAR G055G	110193319	2017-2022
Porsche				
911 Carrera 4 (997) - F	235/40ZR18 91Y N-1	ADVAN Sport (V103S)	110110333	2008-2012
911 Carrera 4 (997) - R	295/35ZR18 99Y N-1	ADVAN Sport (V103S)	110110334	2008-2012
911 Carrera (991 II) - F	235/40ZR19 92Y N0	ADVAN Sport (V105)	110110604	2016-2019
911 Carrera (991 II) - R	295/35ZR19 (100Y) N0	ADVAN Sport (V105E)	110110606	2016-2019
Cayenne E2 I/II	275/45R20 110Y XL N-0	ADVAN Sport (V103H)	110110318	2011-2017
Cayenne E2 I	295/35R21 107Y XL N-1	ADVAN Sport (V103B)	110110319	2011-2014
Cayenne E2 II	295/35R21 107Y XL N-2	ADVAN Sport (V105T)	110110588	2015-2017
Cayenne E3 - F	275/45R20 110V XL N0	AVID GT S35A	110193367	2019-2022
Cayenne E3 - R	305/40R20 112V XL N0	AVID GT S35A	110193368	2019-2022
Cayenne E3 - F	285/40R21 109V XL N0	AVID GT S35A	110193369	2019-2022
Cayenne E3 - R	315/35R21 111V XL N0	AVID GT S35A	110193370	2019-2022
Cayenne E3 - F	285/35ZR22 (106Y) XL N0	ADVAN Sport (V105)	110193371	2020-2022
Cayenne E3 - R	315/30ZR22 (107Y) XL N0	ADVAN Sport (V105E)	110193372	2020-2022
Boxster - F	235/40ZR19 92Y N0	ADVAN Sport (V105)	110110604	2016-2022
Boxster - R	265/40ZR19 98Y N0	ADVAN Sport (V105W)	110110605	2016-2022
Cayman (718) - F	235/40ZR19 92Y N0	ADVAN Sport (V105)	110110604	2016-2022
Cayman (718) - R	265/40ZR19 98Y N0	ADVAN Sport (V105W)	110110605	2016-2022
Panamera	255/40ZR20 101Y XL N-0	ADVAN Sport (V105)	110110556	2014-2016
Panamera	295/35ZR20 105Y XL N-0	ADVAN Sport (V105W)	110110557	2014-2016
RAM				
RAM 1500	LT265/70R17 121S	GEOLANDAR A/T G015	110133530	2018-2022
SCION				
tC	P225/45R18 91W	AVID S34FA	110193227	2011-2017
SMART				
ForTwo (BR453) - F	185/50R16 81H	BluEarth-A (AE50)	110193307	2016-2019
ForTwo (BR453) - R	205/40R17 80H	BluEarth-A (AE50)	110193308	2016-2019
Subaru				
BRZ	P205/55R16 89V	AVID S34M	110193231	2012-2014
Forester	P225/60R17 98H	GEOLANDAR G91F	110193233	2013-2018
Impreza	P195/65R15 89H	AVID S33B	110133003	2012-2016
Impreza	P205/50R17 88V	AVID S34D	110193217	2012-2016
Impreza	P205/55R16 89V	AVID S30B	110193228	2012-2014
Impreza	P205/55R16 89V	AVID S30D	110193238	2013-2016
Impreza	P225/40R18 88V	AVID S34P	110133601	2017-2022
Legacy	225/55R17 97V	AVID GT S35B	110133602	2019-2022
Legacy	225/50R18 95V	AVID GT S35B	110133603	2019-2022
Outback	225/65R17 102H	AVID GT S35C	110133604	2019-2022
Outback	225/60R18 100H	AVID GT S35C	110133605	2019-2022
Outback Wilderness	225/65R17 102T	GEOLANDAR A/T G015	110133606	2022
WRX STI	245/35R19 89W	ADVAN SPORT V105G	110193356	2018-2021
XV	P225/60R17 98H	GEOLANDAR G91F	110193233	2017-2021
XV Crosstrek	P225/55R17 95H	GEOLANDAR G95A	110193210	2013-2017
XV Crosstrek Hybrid	P225/55R17 95H	GEOLANDAR G91FV	110193237	2014-2016
Suzuki				
Grand Vitara	P225/70R16 101H	GEOLANDAR G92C	110193203	2006-2014
SX4	P195/65R15 89H	AVID S33B	110133003	2006-2014
TOYOTA				
4Runner	P245/60R20 107H	GEOLANDAR G96B	110193223	2010-2022
Corolla	195/65R15 91S	AVID GT S35	110193345	2018-2022
Corolla	205/55R16 91H	AVID GT S35	110193373	2020-2022
Corolla	225/40R18 88V	AVID GT S35	110193346	2018-2022
Prius	P195/65R15 89S	AVID S33D	110133509	2009-2014
Prius	P215/45R17 87V	AVID S34RY	110193312	2016-2022
Prius v	P205/60R16 91V	BluEarth S34BZ	110190005	2012-2018
RAV-4	235/55R19 101V	AVID GT S35	110193348	2018-2022
RAV-4	225/65R17 102H	GEOLANDAR G91AV	110193235	2013-2014
RAV-4 Sport	235/55R18 100H	GEOLANDAR G91AV	110193243	2013-2018
Sienna	P235/65R17 103T	BluEarth-4S S34TZ	110133710	2021-2022
Tundra	245/75R18 112T	GEOLANDAR X-CV G057	110133714	2022
Tundra	265/70R18 116T	GEOLANDAR X-CV G057	110133715	2022
Tundra	265/60R20 112H	GEOLANDAR X-CV G057	110133716	2022
VOLKSWAGEN				
Routan	225/65R16 100S	AVID S33	110133506	2009-2013

COMMERCIAL LIGHT TRUCK VEHICLES

MODEL	TIRE SIZE	TIRE NAME	PART #	YEAR
HINO				
FB (F)	215/75R17.5 124L (F)	TY303A	140130365	1998-2014
ISUZU				
N-Series (ELF in JP)	LT215/85R16 10 (E)	TY213A	140121302	2014-2021
N-Series (ELF in JP)	LT215/85R16 10 (E)	TY213B	140133214	2018-2022
N-Series (ELF in JP)	225/70R19.5 12 (F)	TY287	120128702	2014-2020
Mitsubishi FUSO				
Fuso FG (E)	LT235/85R16 114/111 (E)	Y742S	140174250	2002-2020
Fuso FH (F)	215/75R17.5 (F)	RY103	140110376	1998-2020
Fuso FH (F)	215/75R17.5 124L (F)	TY303A	140130365	1998-2022



ADVAN A048®

OE
THREE
SHIP

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
195/50R16 84W	110104804	60/AA/A	18.7	6.0	5.5 - 7.0	8.0	23.6	7.8	6	11.0	879	1102@51
195/50R16 88W	110105274	200/A/A	18.5	6.0	5.5 - 7.0	7.9	23.6	7.2	7	11.0	879	1235@49
225/45R17 90W	110104805	60/AA/A	21.1	7.5	7.0 - 8.5	8.9	24.9	8.8	6	11.6	833	1323@51
225/45R17 94W	110105276	200/A/A	18.5	7.5	7.0 - 8.0	8.5	23.4	7.6	7	11.0	888	1103@49

O.E. Fitsments

Make	Model	Year	Part No.	Make	Model	Year	Part No.
Lotus	Elise S Cup - F	2016-2018	110104804	Lotus	Exige - R	2004-2014	110104805
Lotus	Elise S Cup - R	2016-2018	110104805	Lotus	Elise Cup 250 - F	2018-2021	110105274
Lotus	Elise Sport - R	2004-2014	110104805	Lotus	Elise Cup 250 - R	2018-2021	110105276
Lotus	Exige - F	2004-2014	110104804	Lotus	Elise S Cup - F	2019-2020	110105274



ADVAN A10A/A10F

OE
THREE
SHIP

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
225/50R17 94W	110193212	160/A/A	25.4	7.0	6.0 - 8.0	8.9	25.8	7.7	10	11.9	805	1477@51
215/45R18 89W	110193216	280/A/A	23.6	7.0	7.0 - 8.0	8.4	25.6	7.6	10	12.0	810	1279@51
245/40R18 93Y	110193213	160/A/A	26.7	8.5	8.0 - 9.5	9.9	25.7	8.5	10	12.0	809	1433@51

O.E. Fitsments

Make	Model	Year	Part No.
Lexus	GS350	2007-2012	110193212
Lexus	GS450h	2007-2012	110193213
Lexus	GS460	2008-2012	110193213
Mitsubishi	Lancer Ralliart	2009-2017	110193216



ADVAN A11A

OE
THREE
SHIP

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
205/50R16 87V	110193207	280/A/A	22.4	6.5	5.5 - 7.5	8.1	24.1	6.5	10	11.2	862	1201@44

O.E. Fitsments

Make	Model	Year	Part No.
Mazda	MX-5 Miata	2006-2015	110193207



ADVAN A13C

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
245/40R18 93Y	110193215	180/A/A	25.6	8.5	8.0 - 9.5	9.9	25.6	8.8	10	12.0	810	1433@44

O.E. Fitments

Make	Model	Year	Part No.
Mitsubishi	Lancer Evolution X	2008-2016	110193215



ADVAN A83A

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
P225/55R17 95V	110183051	280/A/A	25.0	7.0	6.0 - 8.0	9.3	26.9	8.0	10	12.4	772	1521@51
P225/45R19 92V	110183050	280/A/A	25.9	7.5	7.0 - 8.5	9.0	26.8	8.0	10	12.6	775	1389@44

O.E. Fitments

Make	Model	Year	Part No.
Infiniti	Infiniti G37	2011-2016	110183050
Mazda	Mazda6	2013-2017	110183051



ADVAN A83B

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
P225/55R17 95V	110193340	280/A/A	23.8	7.0	6.0 - 8.0	9.3	27.0	7.7	10	12.4	690	1521@51

O.E. Fitments

Make	Model	Year	Part No.
Mazda	Mazda6	2018-2021	110193340

**OE^{SHIP}
THREE**

ADVAN *Neova* ADO7



TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
175/55R16 80W	110107035	180/AA/A	18.5	5.5	5.0 - 6.0	7.2	23.5	6.3	9	10.9	885	992@44
225/45R17 91W	110107036	180/AA/A	23.8	7.5	7.0 - 8.5	9.0	24.9	8.5	10	11.6	835	1356@44

O.E. Fitments

Make	Model	Year	Part No.
Lotus	Elise - F	2004-2018	110107035
Lotus	Elise - R	2004-2018	110107036

**OE^{SHIP}
THREE**

ADVAN *Sport* V103



TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
225/50R18 95W	110110337	180/A/A	28.6	7.0	6.0 - 8.0	9.1	26.8	7.4	10	12.4	776	1521@51
235/40ZR18 91Y N-1	110110333	180/AA/A	23.3	8.5	8.0 - 9.5	9.6	25.3	8.1	10	11.9	820	1356@51
245/45R18 96W	110110338	180/A/A	29.5	8.0	7.5 - 9.0	9.8	26.7	8.5	10	12.4	779	1565@51
295/35ZR18 99Y N-1	110110334	180/AA/A	29.5	10.5	10.0 - 11.5	12.5	26.1	11.0	10	12.1	797	1709@51
235/35ZR19 91Y XL M0	110110331	180/AA/A	23.0	8.5	8.0 - 9.5	9.8	25.4	8.5	10	12.0	817	1356@50
245/40ZR19 98 (Y)	110110131	180/AA/A	26.5	8.5	8.0 - 9.5	9.8	26.7	8.7	10	12.5	778	1653@50
255/30ZR19 91Y XL M0	110110332	180/AA/A	26.5	9.0	8.5 - 9.5	10.4	25.1	9.2	10	11.9	828	1356@50
255/40R19 100Y XL A0	110110313	180/AA/A	29.7	9.0	8.5 - 10.0	10.2	27.2	8.8	10	12.7	765	1764@50
255/40R19 100Y XL A0E	110110313	180/AA/A	29.7	9.0	8.5 - 10.0	10.2	27.2	8.8	10	12.7	765	1764@50
255/40R19 100Y XL A0	110110676	180/AA/A	27.0	9.0	8.5 - 10.0	9.0	27.0	9.0	10	13.0	765	1764@50
265/50R19 110Y XL A0	110110339	280/AA/A	38.5	8.5	8.5 - 10.5	10.9	29.9	9.4	11	13.9	694	2337@50
265/35R20 99Y XL A0	110110315	180/AA/A	27.1	9.5	9.0 - 10.5	10.7	27.4	9.6	10	12.9	760	1709@50
275/45R20 110Y XL A0	110110340	280/AA/A	38.5	9.0	8.5 - 10.5	10.9	29.9	9.4	11	13.9	694	2337@50
275/45R20 110Y XL N0	110110318	280/AA/A	35.5	9.0	8.5 - 10.5	11.0	29.6	9.0	11	13.8	701	2337@50
295/40ZR20 106Y M0	110193214	280/AA/A	37.7	10.5	10.0 - 11.5	11.9	29.4	10.8	10	13.7	705	2094@51
295/35R21 107Y XL N-1	110110319	280/AA/A	32.5	10.0	10.0 - 11.5	11.7	29.1	10.6	11	13.6	715	2149@50

O.E. Fitments

Make	Model	Year	Part No.	Make	Model	Year	Part No.
Audi	A6	2013-2017	110110313	Mercedes-Benz	AMG ML 63	2008-2009	110193214
Audi	A6	2013-2017	110110676	Mercedes-Benz	E-Class Coupe (550)	2011-2014	110110331
Audi	A7	2013-2017	110110313	Mercedes-Benz	E-Class Coupe (550)	2011-2014	110110332
Audi	A7	2011-2017	110110315	Nissan	370Z - F	2009-2016	110110337
Audi	A7	2013-2017	110110676	Nissan	370Z - R	2009-2016	110110338
Audi	S6	2013-2017	110110676	Nissan	Nismo 370Z - F	2009-2014	110110131
Audi	S7	2013-2017	110110676	Porsche	911 Carrera 4 (997) - F	2008-2012	110110333
Audi	Q7	2009-2015	110110339	Porsche	911 Carrera 4 (997) - R	2008-2012	110110334
Audi	Q7	2009-2015	110110340	Porsche	Cayenne E2 I	2011-2014	110110319
Mercedes-Benz	AMG C63-F	2008-2014	110110331	Porsche	Cayenne E2 I/II	2011-2017	110110318
Mercedes-Benz	AMG C63-R	2008-2014	110110332				



ADVAN Sport® V105

**O.E. ^{SHIP}
THREE**

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
195/50R16 84V	110110603	240/A/A	18.4	6.0	5.5 - 7.0	7.7	23.7	6.1	9	11.0	875	1102@51
225/45R17 91W	110110516	240/A/A	21.1	7.5	7.0 - 8.5	8.9	25.0	7.7	10	11.6	831	1356@51
225/45R17 91W MO	110110516	240/A/A	21.1	7.5	7.0 - 8.5	8.9	25.0	7.7	10	11.6	831	1356@51
225/50R17 94W MO	110110631	240/A/A	22.1	7.0	6.0 - 8.0	9.3	25.9	7.2	10	12.0	801	1477@51
245/40R17 91W MO	110110517	240/A/A	23.4	8.5	8.0 - 9.5	9.9	24.8	8.4	10	11.5	839	1356@51
225/45R18 95Y XL MO	110110632	240/A/A	21.9	7.5	7.0 - 8.5	8.9	25.9	7.4	10	12.1	801	1521@50
245/40R18 97Y XL MO	110110633	240/A/A	23.0	8.5	8.0 - 9.5	9.9	25.7	8.3	10	12.0	808	1609@50
245/50R18 100W MO	110110640	240/A/A	27.1	7.5	7.0 - 8.5	10.1	27.8	7.9	10	12.8	747	1744@51
255/40R18 95Y MO	110110518	240/AA/A	25.2	9.0	8.5 - 10.0	10.4	26.1	8.4	10	12.1	797	1521@51
285/35R18 97Y MO	110110519	240/AA/A	27.6	10.0	9.5 - 11.0	11.6	25.9	9.6	10	12.1	802	1609@51
235/40ZR19 92Y NO	110110604	240/AA/A	23.2	8.5	8.0 - 9.5	9.7	26.4	8.0	9	12.4	786	1389@51
245/40ZR19(98Y)XL MO	110110634	240/AA/A	24.9	8.5	8.0 - 9.5	10.0	26.8	8.3	10	12.5	776	1653@50
255/35ZR19 (96Y) MO	110110638	240/AA/A	25.6	9.0	8.5 - 10.0	10.2	26.0	8.9	10	12.2	798	1565@50
265/40ZR19 98Y NO	110110605	240/AA/A	27.4	9.5	9.0 - 10.5	10.9	27.3	9.6	9	12.7	760	1653@51
275/35ZR19(100Y)XL MO	110110635	240/AA/A	29.4	9.5	9.0 - 11.0	11.1	26.6	10.0	10	12.5	781	1764@50
275/40ZR19 (105Y)	110193337	240/A/A	28.2	9.5	9.0 - 11.0	10.8	27.5	9.1	9	12.8	755	2039@50
285/30ZR19 (98Y) MO	110110639	240/AA/A	27.8	10.0	9.5 - 10.5	11.3	25.9	10.0	10	12.2	803	1653@50
285/40ZR19 (107Y)	110193338	240/A/A	29.5	10.0	9.5 - 11.0	11.4	27.8	9.9	9	12.9	746	2149@50
295/35ZR19 (100Y) NO	110110606	240/AA/A	30.4	10.5	10.0 - 11.5	12.2	27.2	11.0	9	12.7	765	1764@51
245/35ZR20(95Y)XL MO	110110636	240/AA/A	26.8	8.5	8.0 - 9.5	9.8	26.7	8.9	10	12.6	778	1521@50
245/45R20 103Y	110133805	240/AA/A	29.5	8.0	7.5 - 9.0	9.8	28.7	8.3	10	13.4	724	1929@50
255/40ZR20 101YXLN-0	110110556	240/AA/A	27.8	9.0	8.5 - 10.0	10.6	28.2	9.1	10	13.2	737	1819@50
275/30ZR20(97Y)XL MO	110110637	240/AA/A	28.8	9.5	9.0 - 10.0	11.2	26.4	10.0	10	12.5	786	1609@50
275/40R20 106Y	110133804	240/A/A	30.6	9.5	9.0 - 11.0	11.1	28.7	9.9	10	13.4	724	2094@50
295/35ZR20 105YXLN-0	110110557	240/AA/A	33.9	10.5	10.0 - 11.5	12.4	28.0	10.7	10	13.1	743	2039@50
275/40R21 107Y	110133807	240/A/A	33.3	9.5	9.0 - 11.0	9.8	29.6	9.8	10	13.9	702	2150@50
295/35R21 107YXLN-2	110110588	280/AA/A	31.7	10.5	10.0 - 11.5	11.7	29.1	10.3	10	13.7	714	2149@50
315/35R21 111Y	110133808	240/A/A	36.2	11.0	10.5 - 12.5	11.5	29.6	11.6	10	13.9	701	2403@50
285/35ZR22(106Y)XLNO	110193371	240/A/A	32.1	10.0	9.5 - 11.0	11.7	29.9	9.9	10	14.1	695	2094@50
315/30ZR22(107Y)XLNO	110193372	240/A/A	33.8	11.0	10.5 - 11.5	12.6	29.5	11.2	10	13.9	704	2149@50

O.E. Fitments

Make	Model	Year	Part No.
BMW	M5 - F	2018-2021	110193337
BMW	M5 - R	2018-2021	110193338
BMW	X3 - F	2018-2022	110133805
BMW	X3 - R	2018-2022	110133804
BMW	X4 - F	2018-2022	110133805
BMW	X4 - R	2018-2022	110133804
BMW	X5 - F	2018-2021	110133807
BMW	X5 - R	2018-2021	110133808
BMW	X6 - F	2018-2021	110133807
BMW	X6 - R	2018-2021	110133808
Lotus	Elise Sport - R	2018-2021	110110516
Lotus	Elise Sport 220 - R	2018-2021	110110516
Lotus	Elise Sprint - R	2018-2021	110110516
Lotus	Elise Sprint 220 - R	2018-2021	110110516
Mazda	MX-5 Miata Sport	2016-2021	110110603
Mercedes-Benz	A/B Class	2015-2018	110110516
Mercedes-Benz	C-Class (W205)	2016-2017	110110631
Mercedes-Benz	C-Class (W205) F	2016-2018	110110632
Mercedes-Benz	C-Class (W205) R	2016-2018	110110633
Mercedes-Benz	E-Class (E53 AMG Sport) (BR213) F	2017-2021	110110634
Mercedes-Benz	E-Class (E53 AMG Sport) (BR213) F	2017-2021	110110636

Make	Model	Year	Part No.
Mercedes-Benz	E-Class (E53 AMG Sport) (BR213) R	2017-2021	110110635
Mercedes-Benz	E-Class (E53 AMG Sport) (BR213) R	2017-2021	110110637
Mercedes-Benz	S	2013-2020	110110640
Mercedes-Benz	SL (BR213) F	2016-2020	110110638
Mercedes-Benz	SL (BR213) R	2016-2020	110110639
Mercedes-Benz	SL (F)	2012-2020	110110518
Mercedes-Benz	SL (R)	2012-2020	110110519
Mercedes-Benz	SLK /SLC	2012-2020	110110516
Mercedes-Benz	SLK /SLC	2012-2020	110110517
Porsche	911 Carrera (991 II) - F	2016-2019	110110604
Porsche	911 Carrera (991 II) - R	2016-2019	110110606
Porsche	Boxter - F	2016-2021	110110604
Porsche	Boxter - R	2016-2021	110110605
Porsche	Cayenne E3 - F	2020-2021	110193371
Porsche	Cayenne E3 - R	2020-2021	110193372
Porsche	Cayenne E2 II	2015-2017	110110588
Porsche	Cayman (718) - F	2016-2021	110110604
Porsche	Cayman (718) - R	2016-2021	110110605
Porsche	Panamera	2014-2016	110110556
Porsche	Panamera	2014-2016	110110557

**OE SHIP
THREE**


ADVAN Sport® ZPS (V105)

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
245/50R19 105W	110133802	240/A/A	34.4	7.5	7.0 - 8.5	10.1	28.7	7.9	10	13.3	723	2039@50

O.E. Fitments

Make	Model	Year	Part No.
BMW	X3	2020-2021	110133802
BMW	X4	2020-2021	110133802



ADVAN Sport® (V107)

**OE SHIP
THREE**

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
225/60R18 104W	110133809	240/A/A	25.4	6.5	6.0 - 8.0	9.1	28.7	7.0	9	13.2	724	1984@50
275/40ZR18 (103Y)	110193380	240/AA/A	26.8	9.5	9.0 - 11.0	11.0	26.7	9.2	9	12.4	779	1929@50
235/50ZR19 99Y M01	110133225	240/AA/A	29.0	7.5	6.5 - 8.5	9.8	28.4	7.9	10	13.2	731	1709@51
245/35R19 89W	110193356	200/A/A	23.4	8.5	8.0 - 9.5	9.7	25.7	9.1	10	12.1	807	1279@51
285/35ZR19 (103Y)	110193381	240/AA/A	29.3	10.0	9.5 - 11.0	11.3	26.9	9.7	9	12.6	771	1929@50
275/50ZR20 113Y M0	110133220	240/AA/A	38.6	8.5	7.5 - 9.50	11.5	31.1	9.6	10	14.3	668	2535@51
255/35ZR21 98Y M01	110133226	240/AA/A	29.2	9.0	8.5 - 10.0	10.4	28.0	9.1	10	13.2	788	1653@51
275/40R21 107Y	110133813	240/A/A	32.7	9.5	9.0 - 11.0	11.1	29.7	9.8	10	13.9	700	2149@50
315/35R21 111Y	110133814	240/A/A	36.2	11.0	10.5 - 12.5	12.8	29.7	11.6	10	13.9	700	2403@50
325/35ZR22 114Y M0	110133222	240/AA/A	41.7	11.5	11.0 - 13.0	13.3	31.1	11.7	10	14.5	668	2601@51
325/40ZR22 114Y M0	110133224	240/AA/A	43.9	11.5	11.0 - 13.0	13.0	32.0	12.0	10	15.0	643	2601@51
285/40ZR22 110Y M0	110133221	240/AA/A	37.0	10.0	9.5 - 11.0	11.6	31.1	10.0	10	14.5	668	2337@51
285/45ZR22 114Y M0	110133223	240/AA/A	38.5	9.5	9.0 - 10.5	11.4	32.2	9.6	10	15.0	646	2601@51

O.E. Fitments

Make	Model	Year	Part No.	Make	Model	Year	Part No.
BMW	M3 - F	2020-2021	110193380	Mercedes-Benz	AMG GLA	2020-2022	110133226
BMW	M3 - R	2020-2021	110193381	Mercedes-Benz	AMG GLE	2020-2022	110133220
BMW	M4 - F	2020-2021	110193380	Mercedes-Benz	AMG GLE	2020-2022	110133221
BMW	M4 - R	2020-2021	110193381	Mercedes-Benz	AMG GLE	2020-2022	110133222
BMW	X3	2019-2022	110133809	Mercedes-Benz	AMG GLS	2020-2022	110133223
BMW	X4	2019-2022	110133809	Mercedes-Benz	AMG GLS	2020-2022	110133224
BMW	X5 - F	2022	110133813	Mercedes-Benz	GLE Coupe	2020-2022	110133221
BMW	X6 - F	2022	110133813	Mercedes-Benz	GLE Coupe	2020-2022	110133220
BMW	X5 - R	2022	110133814	Mercedes-Benz	GLE Coupe	2020-2022	110133222
BMW	X6 - R	2022	110133814	Subaru	WRX STI	2018-2021	110193356
Mercedes-Benz	AMG GLA	2020-2022	110133225				



ADVAN S.T.® V802

OE
THREE
SHIP

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
275/50R20 113W M0	110180241	320/A/A	40.2	8.5	7.5 - 9.5	11.1	31.0	9.6	11	14.3	670	2535@50

O.E. Fitments

Make	Model	Year	Part No.
Mercedes-Benz	AMG G63	2013-2018	110180241
Mercedes-Benz	AMG G65	2013-2018	110180241



AVID S30B/S30D

OE
THREE
SHIP

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
P205/55R16 89V	110193228	320/B/A	19.2	6.5	5.5 - 7.5	8.3	24.9	6.2	10	11.5	835	1279@51

O.E. Fitments

Make	Model	Year	Part No.
Subaru	Impreza	2012-2014	110193228
Subaru	Impreza	2013-2016	110193238



AVID S33

OE
THREE
SHIP

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
225/65R16 100S	110133506	460/B/B	24.0	6.5	6.0 - 8.0	8.9	27.6	6.6	11	12.5	754	1764@44

O.E. Fitments

Make	Model	Year	Part No.
Chrysler	Town & Country	2008-2014	110133506
Dodge	Grand Caravan	2008-2014	110133506
Volkswagen	Routan	2009-2013	110133506



AVID S33B

OE
THREE
SHIP

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
P195/65R15 89H	110133003	200/B/A	18.5	6.0	5.5 - 7.0	7.9	25.0	5.7	10	11.4	829	1279@44
225/65R17 102T	110133510	460/B/B	27.0	6.5	6.0 - 8.0	8.9	28.4	6.6	10	13.0	732	1874@51

O.E. Fitments

Make	Model	Year	Part No.
Chrysler	Town & Country	2013-2016	110133510
Dodge	Grand Caravan	2013-2020	110133510
Subaru	Impreza	2012-2016	110133003
Suzuki	SX4	2006-2014	110133003



AVID S33D

OE
THREE
SHIP

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
P195/65R15 89S	110133509	320/B/B	17.7	6.0	5.5 - 7.0	8.9	27.6	6.6	11	12.5	829	1279@44

O.E. Fitments

Make	Model	Year	Part No.
Toyota	Prius	2009-2014	110133509



AVID S34B

OE
THREE
SHIP

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
P205/60R16 91H	110190004	320/B/A	21.8	6.0	5.5 - 7.5	8.1	25.7	6.5	10	11.8	809	1356@44

O.E. Fitments

Make	Model	Year	Part No.
Mitsubishi	Lancer DE	2007-2017	110190004
Mitsubishi	Lancer ES	2007-2017	110190004



AVID S34D

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTOG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
P205/50R17 88V	110193217	320/A/A	21.4	6.5	5.5 - 7.5	8.3	25.2	6.5	10	11.7	826	1235@44

O.E. Fitments

Make	Model	Year	Part No.
Mazda	Mazda3	2009-2014	110193217
Mazda	Mazda5	2009-2014	110193217
Subaru	Impreza	2012-2016	110193217



AVID S34F/S34FA/S34FV

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTOG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
175/55R15 77V	110193314	320/B/A	14.6	5.5	5.0 - 6.0	6.9	22.6	5.5	9	10.5	918	908@51
185/55R15 82V	110193225	320/A/A	15.7	6.0	5.0 - 6.5	7.8	23.1	6.0	10	10.7	897	1047@51
P205/60R16 91H	110193239	320/B/A	19.9	6.0	5.5 - 7.5	8.2	25.7	7.0	10	11.8	807	1356@51
P215/60R16 94H	110193250	320/B/A	21.8	6.5	6.0 - 7.5	8.6	26.1	6.2	10	12.0	795	1477@51
P215/50R18 92V	110193251	320/B/A	23.8	7.0	6.0 - 7.5	8.7	26.5	6.8	10	12.3	785	1389@51
P225/45R18 91W	110193227	360/A/A	25.7	7.5	7.0 - 8.5	9.0	26.1	7.4	10	12.1	797	1356@51

O.E. Fitments

Make	Model	Year	Part No.	Make	Model	Year	Part No.
Mazda	CX-3	2016-2021	110193250	Mazda	Mazda3	2014-2019	110193239
Mazda	CX-3	2016-2021	110193251	Scion	tC	2011-2017	110193227
Mazda	Mazda2	2011-2014	110193225				



AVID S34M

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTOG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
P205/55R16 89V	110193231	320/A/A	19.6	6.5	5.5 - 7.5	8.4	24.9	6.5	10	11.5	833	1279@51

O.E. Fitments

Make	Model	Year	Part No.
Subaru	BRZ	2012-2014	110193231



AVID S34NV/S34PV

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
225/45R17 91H	110133524	320/A/A	22.9	7.5	7.0 - 8.5	8.8	25.1	7.7	10	11.7	828	1356@51
225/40R18 92V	110133523	320/A/A	22.7	8.0	7.5 - 9.0	9.0	25.1	7.7	10	11.8	827	1389@50

O.E. Fitments

Make	Model	Year	Part No.
Dodge	Dart	2013-2016	110133523
Dodge	Dart	2014-2016	110133524



AVID S34P

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
P225/40R18 88V	110133601	320/A/A	22.5	8.0	7.5 - 9.0	9.1	25.2	7.7	10	11.8	824	1235@51

O.E. Fitments

Make	Model	Year	Part No.
Subaru	Impreza	2017-2022	110133601



AVID S34RV/RV

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
235/65R17 104T	110133527	460/B/B	28.7	7.0	6.5 - 8.5	9.7	29.1	7.3	10	13.2	715	1984@51
P215/45R17 87V	110193312	320/B/A	20.9	7.0	7.0 - 8.0	8.5	24.8	6.6	10	11.5	839	1201@51

O.E. Fitments

Make	Model	Year	Part No.
Chrysler	Pacifica	2017-2022	110133527
Chrysler	Voyager	2020-2022	110133527
Toyota	Prius	2016-2022	110193312



AID GT S35

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
195/65R15 91S	110193345	280/B/A	17.4	6.0	5.5 - 7.0	8.0	25.0	6.6	9	11.4	830	1356@51
205/55R16 91H	110193373	280/B/A	18.6	6.5	5.5 - 7.5	8.3	25.1	6.9	9	11.6	827	1356@51
225/40R18 88V	110193346	280/B/A	22.7	8.0	7.5 - 9.0	9.4	25.1	7.6	10	11.8	827	1235@51
235/55R19 101V	110193348	280/B/A	28.7	7.5	6.5 - 8.5	9.5	29.0	7.5	10	13.4	716	1819@51

O.E. Fitments

Make	Model	Year	Part No.
Toyota	Corolla	2018-2022	110193345
Toyota	Corolla	2020-2022	110193373
Toyota	Corolla	2018-2022	110193346
Toyota	RAV-4	2018-2022	110193348



AID GT S35A

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
275/45R20 110VXLNO	110193367	440/A/A	32.2	9.0	8.5 - 10.5	11.0	29.9	9.0	10	13.9	694	2337@50
305/40R20 112VXLNO	110193368	440/A/A	33.7	11.0	10.0 - 12.0	12.5	29.9	10.4	10	13.7	706	2469@50
285/40R21 109VXLNO	110193369	440/A/A	32.6	10.0	9.5 - 11.0	11.7	30.0	9.8	10	14.0	693	2271@50
315/35R21 111VXLNO	110193370	440/A/A	33.9	11.0	10.5 - 12.5	12.6	29.5	11.5	10	13.8	704	2403@50

O.E. Fitments

Make	Model	Year	Part No.
Porsche	Cayenne E3 - F	2019-2022	110193367
Porsche	Cayenne E3 - F	2019-2022	110193369
Porsche	Cayenne E3 - R	2019-2022	110193368
Porsche	Cayenne E3 - R	2019-2022	110193370



AID GT S35B/S35C

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
225/55R17 97V	110133602	400/B/A	24.7	7.0	6.0 - 8.0	9.2	26.8	7.7	10	12.3	776	1609@51
225/65R17 102H	110133604	400/B/A	25.7	6.5	6.0 - 8.0	9.0	28.5	6.9	10	13.0	729	1874@51
225/50R18 95V	110133603	400/B/A	23.8	7.0	6.0 - 8.0	9.1	26.9	7.7	10	12.5	771	1521@51
225/60R18 100H	110133605	400/B/A	26.6	6.5	6.0 - 8.0	8.9	28.7	6.9	10	13.2	724	1764@51

O.E. Fitments

Make	Model	Year	Part No.
Subaru	Legacy	2019-2022	110133602
Subaru	Legacy	2019-2022	110133603
Subaru	Outback	2019-2022	110133604
Subaru	Outback	2019-2022	110133605



BluEarth AE50



TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
185/50R16 81H	110193307	300/A/A	16.6	6.0	5.0 - 6.5	7.5	23.4	6.0	10	10.9	888	1019@51
205/40R17 80H	110193308	300/A/A	18.6	7.5	7.0 - 8.0	8.4	23.4	6.9	10	11.0	887	922@44

O.E. Fitments

Make	Model	Year	Part No.
Smart	ForTwo (BR453) - F	2016-2019	110193307
Smart	ForTwo (BR453) - R	2016-2019	110193308



BluEarth S34BZ/S34TZ



TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
P205/60R16 91V	110190005	320/B/A	22.4	6.0	5.5 - 7.5	8.2	25.6	6.5	10	11.7	812	1356@51
P235/65R17 103T	110133710	500/A/B	27.8	7.0	6.5 - 8.5	9.4	28.9	7.5	10	13.1	875	1929@51

O.E. Fitments

Make	Model	Year	Part No.
Toyota	Prius v	2012-2018	110190005
Toyota	Sienna	2021-2022	110133710



C.drive 2 | C.drive 2 Z.P.S.



TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
235/50R18 97V M0	110102813	240/A/A	26.6	7.5	6.5 - 8.5	9.8	27.4	7.9	10	12.7	758	1609@51
235/50R18 97V M0E	110102814	240/A/A	30.2	7.5	6.5 - 8.5	9.8	27.4	7.9	10	12.7	758	1609@51

O.E. Fitments

Make	Model	Year	Part No.
Mercedes-Benz	GLA	2014-2020	110102813
Mercedes-Benz	GLA	2014-2020	110102814



GEOLANDAR G038G

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
265/60R18 110V	110103830	240/A/B	39.8	8.0	7.5 - 9.5	10.7	30.7	8.0	11	14.0	675	2337@44

O.E. Fitments

Make	Model	Year	Part No.
Mercedes-Benz	G500	2002-2015	110103830



GEOLANDAR G055/G055G

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
225/55R18 98H	110133531	740/B/A	30.0	7.0	6.0 - 8.0	9.1	27.8	7.3	11	12.8	747	1653@51
215/65R16 98H	110193319	280/B/A	23.4	6.5	6.0 - 7.5	8.8	27.0	6.9	10	12.3	770	1653@51

O.E. Fitments

Make	Model	Year	Part No.
Chrysler	Jeep Compass	2019-2022	110133531
Nissan	Rogue Sport	2017-2022	110193319



GEOLANDAR SUV G055E

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
P235/65R18 104T	110193232	320/B/B	32.9	7.0	6.5 - 8.5	9.5	30.2	7.1	10	13.7	689	1984@51

O.E. Fitments

Make	Model	Year	Part No.
Nissan	Murano	2013-2015	110193232



GEOLANDAR H/T G056B

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
P255/60R18 107H	110193258	280/B/A	36.0	7.5	7.0-9.0	10.2	29.8	8.3	10	13.6	697	2149@51

O.E. Fitments

Make	Model	Year	Part No.
Mazda	CX-9	2016-2017	110193258



GEOLANDAR G91A/G91AV

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
225/65R17 102H	110193315	280/B/A	27.0	6.5	6.0-8.0	8.8	28.5	6.9	10	13.0	730	1874@51
225/65R17 102H	110193235	280/B/A	27.3	6.5	6.0-8.0	8.9	28.5	6.9	10	13.0	728	1874@51
P225/65R17 100H	110193229	280/B/A	26.3	6.5	6.0-8.0	8.8	28.5	6.9	10	13.0	729	1764@44
235/55R18 100H	110193243	280/B/A	25.0	7.5	6.5-8.5	9.4	28.1	7.1	10	13.0	738	1764@51

O.E. Fitments

Make	Model	Year	Part No.	Make	Model	Year	Part No.
Lexus	NX	2015-2021	110193235	Toyota	RAV-4	2013-2014	110193235
Mazda	CX-5	2012-2022	110193229	Toyota	RAV-4 Sport	2013-2018	110193243
Nissan	Rogue	2016-2021	110193315				



GEOLANDAR G91F/G91FV

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
P225/55R17 95H	110193237	320/A/A	25.0	7.0	6.0-8.0	9.1	26.8	6.9	10	12.3	776	1521@51
P225/60R17 98H	110193233	320/B/A	24.1	6.5	6.0-8.0	8.9	27.6	6.6	10	12.6	753	1653@51

O.E. Fitments

Make	Model	Year	Part No.
Subaru	Forester	2013-2018	110193233
Subaru	XV	2017-2021	110193233
Subaru	XV Crosstrek Hybrid	2014-2016	110193237



GEOLANDAR G91HV

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
225/60R18 100H	110193246	280/B/A	29.4	6.5	6.0 - 8.0	9.0	28.7	6.9	10	13.1	725	1764@51

O.E. Fitments

Make	Model	Year	Part No.
Lexus	NX	2015-2021	110193246



GEOLANDAR G92C

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
P225/70R16 101H	110193203	280/A/B	29.6	6.5	6.0 - 7.5	9.1	28.3	6.9	10	12.8	734	1819@44

O.E. Fitments

Make	Model	Year	Part No.
Suzuki	Grand Vitara	2006-2014	110193203



GEOLANDAR G95A

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
P225/55R17 95H	110193210	320/B/A	25.1	7.0	6.0 - 8.0	9.1	26.8	6.6	10	12.3	775	1521@44

O.E. Fitments

Make	Model	Year	Part No.
Subaru	XV Crosstrek	2013-2017	110193210



GEOLANDAR G96B

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
P245/60R20 107H	110193223	280/B/A	35.9	7.0	7.0-8.5	9.6	31.6	7.3	11	14.5	657	2149@44

O.E. Fitments

Make	Model	Year	Part No.
Toyota	4Runner	2010-2021	110193223



GEOLANDAR A/T G015

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI	
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	SINGLE	DUAL
225/65R17 102T	110133606	600/A/B	29.5	6.5	6.0-8.0	8.9	28.5	6.7	12	13.0	728	1874@51	-
LT265/70R17 121S	110133530	-	50.5	7.0	7.0-8.5	10.3	31.9	8.3	18	14.3	651	3195@80	2910@80

O.E. Fitments

Make	Model	Year	Part No.
RAM	RAM 1500	2018-2022	110133530
Subaru	Outback Wilderness	2022	110133606



GEOLANDAR H/T G033

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
P215/70R16 99H	110103331	200/B/A	24.3	6.5	5.5-7.0	10.3	25.3	10.2	10	11.9	747	1709@44
P215/70R16 99H	110103332	200/B/A	24.2	6.5	5.5-7.0	8.7	27.8	5.6	10	12.6	748	1709@44
P215/70R16 99H	110103333	200/B/A	24.0	6.5	5.5-7.0	8.6	27.8	5.6	10	12.6	746	1709@44

O.E. Fitments

Make	Model	Year	Part No.
Mitsubishi	Outlander	2013-2015	110103332
Mitsubishi	Outlander	2015-2021	110103333
Mitsubishi	Outlander Sport	2006-2014	110103331



GEOLANDAR X-CV G057

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
245/75R18 112T	110133714	520/B/B	35.5	7.0	6.5-8.0	9.8	32.2	7.1	11	14.5	645	2469@51
265/70R18 116T	110133715	520/B/B	38.0	8.0	7.0-9.0	10.6	32.4	7.6	11	14.6	642	2756@51
265/60R20 112H	110133716	520/B/A	37.5	8.0	7.5-9.5	10.5	32.6	8.1	11	14.9	636	2469@51

O.E. Fitments

Make	Model	Year	Part No.
Toyota	Tundra	2022	110133714
Toyota	Tundra	2022	110133715
Toyota	Tundra	2022	110133716



GEOLANDAR X-CV G99A

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UTQG RATING	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI
				MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	
235/60R18 103H	110193374	380/B/A	25.0	7.0	6.50-8.50	10.0	29.0	7.0	9	13.0	713	1929@51

O.E. Fitments

Make	Model	Year	Part No.
Nissan	Rogue	2021-2022	110193374

LIGHT TRUCK COMMERCIAL ORIGINAL EQUIPMENT



RY103

OE^{SHIP}
THREE

TIRE SIZE	PART NO.	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI	
			MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	SINGLE	DUAL

O.E. Fitments

Make	Model	Year	Part No.
Mitsubishi Fuso	Fuso FH (F)	1998-2020	140110376



TY213A

OE
THREE
SHIP

TIRE SIZE	PART NO.	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI	
			MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	SINGLE	DUAL
LT215/85R16 10 (E)	140121302	38.4	6.0	5.5 - 7.0	8.4	30.5	5.8	15	14.2	681	2680@80	2470@80

O.E. Fitments

Make	Model	Year	Part No.
Isuzu	N-Series (ELF in JP)	2014-2021	140121302



TY213B

OE
THREE
SHIP

TIRE SIZE	PART NO.	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI	
			MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	SINGLE	DUAL
LT215/85R16 10	140133214	38.0	6.0	5.5 - 7.0	8.6	30.5	7.0	14	14.0	685.0	2680@80	2470@80

O.E. Fitments

Make	Model	Year	Part No.
Isuzu	N-Series (ELF in JP)	2018-2021	140133214



TY287

OE
THREE
SHIP

TIRE SIZE	PART NO.	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI	
			MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	SINGLE	DUAL
225/70R19.5 12 (F)	120128702	72.1	6.8	6.0 - 6.75	8.9	32.0	7.7	20	15.0	651	3640@95	3415@95

O.E. Fitments

Make	Model	Year	Part No.
Isuzu	N-Series (ELF in JP)	2014-2020	120128702



TY303A

OE
THREE
SHIP

TIRE SIZE	PART NO.	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI	
			MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	SINGLE	DUAL
215/75R17.5 124L(F)	140130365	56.0	6.0	6.75	8.1	30.4	6.8	18	14.1	684	3530@100	3420@100

O.E. Fitments

Make	Model	Year	Part No.
Hino	FB (F)	1998-2014	140130365
Mitsubishi Fuso	Fuso FH (F)	1998-2022	140130365



Y742S

OE
THREE
SHIP

TIRE SIZE	PART NO.	UNIT WEIGHT (LBS)	RIM WIDTH		INFLATED DIMENSIONS		TREAD WIDTH (INCHES)	TREAD DEPTH (32/INCH)	LOADED DIMENSIONS		MAX LOAD AT COLD INFLATION PRESSURE LBS @ PSI	
			MEASURING (INCHES)	APPROVED (INCHES)	OVERALL WIDTH (INCHES)	OVERALL DIAMETER (INCHES)			STATIC RADIUS (INCHES)	REVS PER MILE	SINGLE	DUAL
LT235/85R16 114/111 (E)	140174250	49.5	6.5	6.0 - 7.0	9.3	31.9	6.7	18	14.8	650	3042@80	2778@80

O.E. Fitments

Make	Model	Year	Part No.
Mitsubishi Fuso	Fuso FG (E)	2002-2020	140174250



A background image showing a winding road through a mountainous landscape. In the foreground, a large, detailed image of a tire tread pattern is visible on the left side. The entire page is overlaid with horizontal lines for writing.

ADVAN

AVID[®]

GEOLANDAR[®]

iceGUARD

PARADA

BluEarth⁺WINTER



Yokohama Tire Corporation

800.423.4544 | yokohamatire.com

Consumer Dealer Customer Service: 800.423.4544 ext. 2897

Consumer Dealer Customer Service Fax: 800.400.9656

Consumer Affairs: 800.722.9888

