




MERICUS

**BUILT FOR AMERICAN
TRUCKING**



**TBR
2019
PRODUCT CATALOG**

A close-up photograph of the front of a dark-colored truck. The image shows the right-side headlight, a side mirror, and the chrome grille. The truck is parked on a street, with blurred buildings and lights in the background, suggesting an urban or industrial setting. The lighting is warm, likely from the setting or rising sun.

Every commercial driver is looking for a tire that can perform. Americus tires do more than perform - they're engineered to dominate. Whether you conquer the long haul with ST1000 trailer tires, or add extra protection from hydroplaning with CS3000s, EVERY Americus Tire is Built for American Trucking.

Americus TBR tires are backed by our exclusive 5/50 free replacement warranty, No-Questions-Asked 50% Free Replacement Warranty coverage. That means the first 50% of tread life is covered for materials and workmanship. Find the Americus tire that works for your business today, and discover the aggressive performance that makes our tires great.

WARRANTY

LIMITED WARRANTY

American Omni Trading Company (AOT) hereby warrants that every new AMERICUS TBR tire purchased from AOT is free from defects in workmanship and material for the life of the original tread of a new tire less 2/32" (the life of the original usable tread ends when the tire tread has worn down with only 2/32" remaining, at which point the tire is considered to be fully worn out). This warranty applies only to the original purchaser for a period of five (5) years from the date of manufacture as determined by the DOT/Serial number.

50% FREE REPLACEMENT WARRANTY

If a defect in workmanship and materials is found in any AMERICUS TBR radial truck tire within the first 50% of tread wear (Percentage will be calculated based on difference of tread tire depth minus 2/32" compared to the original tread), AOT will refund the cost of a replacement AMERICUS TBR Radial truck tire plus the cost of mounting and balancing as follows:

1. The defective AMERICUS TBR radial truck tire must be replaced with a comparable new AMERICUS TBR Radial truck tire by an authorized dealer. Proof of replacement will be required.
2. Costs of mounting and balancing will be refunded to a maximum of \$16.00 per tire. Written proof of these will be required.
3. Applicable taxes on the new tire shall be borne by the owner.
4. 50% free replacement applies to new first quality tires only. Blems, retreads and road hazard tires are specifically excluded.

GENERAL WARRANTY

If a defect in workmanship and materials is found in any AMERICUS TBR tire not covered in the 50% free replacement warranty, a credit will be given toward the purchase of a comparable new tire in proportion of the original usable tread of the new AMERICUS TBR tire. (Percentage will be calculated based on difference of tread tire depth minus 2/32" compared to the original tread) Applicable taxes on the new tire and costs of mounting and balancing service will be borne by the owner. Adjustment on out-of-balance or out-of-round tire is allowed only during the first 2/32" of the original tread.

CASING WARRANTY

1. The casing of AMERICUS TBR radial truck tires are warranted against defects in workmanship or materials through the life of the second retread. The life of the second retread is considered to end when the remaining tread on the second retread reaches 2/32" or less.
2. If an examination shows that a casing of a AMERICUS TBR radial truck tire failed from workmanship or materials, AOT will give credit toward the purchase price of a comparable new AMERICUS TBR radial truck tire in the amount indicated below:
 - All 17.5 inch rim sizes: \$20.00
 - All 19.5 inch rim sizes: \$20.00
 - 255/70R22.5, 275/70R22.5: \$50.00
 - 11R22.5, 12R22.5, 295/75R22.5, 295/80R22.5: \$60.00
 - 11R24.5, 285/75R24.5: \$60.00
 - 315/80R22.5, 385/65R22.5, 425/65R22.5: \$60.00

Above casing warranty is valid for the first five years after date of manufacture of original tire.

EXCLUSIONS

1. All AOT warranties are limited to the original purchaser and the original vehicle on which they are mounted for a period of five (5) years from the date of manufacture and are not assignable to subsequent purchaser or vehicles.
2. This limited warranty is applicable only in the United States and Canada and any tire used or equipped on a vehicle registered or operated outside the United States and Canada are not covered by this warranty.
3. The following is not covered by Limited Warranty:
 - Tire branded or marked "Non-Adjustable" (N/A) or "Blemished" (Blem), or previously adjusted.
 - Failure, Damage or irregular wear due to:
 - road hazards (i.e. puncture, cut, snag, impact breaks, etc), wreck collision;
 - fire, accident or vandalism
 - mechanical conditions of vehicle, including improper alignment, improper inflation, improper mounting, wheel imbalance, faulty shocks or brakes;
 - overloading the tire beyond maximum load capacity stated on the sidewall;
 - misapplication of tire, use of improper inner tube;
 - alteration of the tire or addition of alien material or transfer from one vehicle to another; and radial truck tire failed due to faulty retreading or material.
 - Cost of mounting and balancing service except as noted above.
 - Loss of time or use, inconvenience or any incidental damages to include cost of towing or transportation, related property damage or consequential damages of any type or nature except as prohibited by law.
 - Tires older than five (5) years from the date of manufacture as determined by the DOT/Serial number.

OWNERS OBLIGATIONS

In order to be eligible for AOT Limited Warranty service, the owner must:

1. Present the defective tire to an authorized dealer from which the original purchase was made
2. Present proof of purchase to the satisfaction of the dealer;
3. Complete and sign an AOT Warranty Claim Form, which is available at any authorized dealer; and
4. Pay the amount due on a new tire, less the amount of credit, including taxes, mounting and balancing charges or cost of other services rendered including FET and taxes.

DISCLAIMER

This warranty, or any warranty stated or referred to herein, is exclusive and in lieu of any other warranty regarding the quality of AMERICUS TBR tires, whether expressed or implied, and remedies for breach there of shall be limited to those specifically provided herein.



AMERICUS

americustire.com



CS3000

A Premium Closed-Shoulder Drive Tire with superior anti-hydroplaning tread design. Engineered for highway and local road surfaces both paved and unpaved. SMARTWAY CERTIFICATION Pending.



Size	LI/SR	PR	TT/TL	TD	OD	SW	RIM Width Measure	Max Load	Stock #
11R22.5	144/142L	14	TL	26	41.7	11.2	8.25	6175/5840@105	AMD9310
11R22.5	146/143L	16	TL	26	41.7	11.2	8.25	6610/6005@120	AMD9311
11R24.5	146/143L	14	TL	26	43.9	10.8	8.25	6610/6005@105	AMD9312
11R24.5	149/146L	16	TL	26	43.9	10.8	8.25	7160/6610@120	AMD9313
295/75R22.5	144/141L	14	TL	28	39.9	11.7	9.00	6175/5675@110	AMD9315
295/75R22.5	146/143L	16	TL	28	39.9	11.7	9.00	6610/6005@120	AMD9316
285/75R24.5	144/141L	14	TL	28	41.5	11.1	8.25	6175/5676@110	AMD9320
285/75R24.5	147/144L	16	TL	28	41.5	11.1	8.25	6780/6175@120	AMD9321



LT2000

An All Position Steel Radial designed for high mileage and superior handling characteristics. Engineered for steer axles and all position usage.



Size	LI/SR	PR	TT/TL	TD	OD	SW	RIM Width Measure	Max Load	Stock #
7.50R16LT	122/121L	14	TL	16	31.7	8.5	6.00	3305/3195@100	AMD9161
8.25R16LT	128/126L	14	TL	16	33.7	8.8	6.50	3970/3750@98	AMD9168
9.5R17.5	143/141J	16	TL	17	33.2	9.3	6.75	6005/5675@127	AMD9102

RD3000

A Proven Lug Tread design that is dependable and reliable. Suitable for short-distance transportation for both paved and unpaved surfaces.



Size	LI/SR	PR	TT/TL	TD	OD	SW	Max Load	Stock #
225/70R19.5	128/126M	14	TL	18	31.9	8.9	3970/3750@110	AMD9820
245/70R19.5	135/133M	16	TL	19	33.0	9.8	4805/4540@120	AMD9840



OS3000

A Premium Open-Shoulder Drive Tire designed with stable and durable casing construction. The tread pattern offers superior heat dissipation for long service. SMARTWAY CERTIFICATION Pending.



Size	LI/SR	PR	TT/TL	TD	OD	SW	RIM Width Measure	Max Load	Stock #
11R22.5	144/142L	14	TL	30	41.5	11.0	8.25	6175/5840@105	AMD9710
11R22.5	146/143L	16	TL	30	41.5	11.0	8.25	6610/6005@120	AMD9711
11R24.5	146/143L	14	TL	30	43.2	10.8	8.25	6610/6005@105	AMD9712
11R24.5	149/146L	16	TL	30	43.2	10.8	8.25	7160/6610@120	AMD9713
295/75R22.5	144/141L	14	TL	30	39.9	11.7	9.00	6175/5675@110	AMD9715
295/80R22.5	150/147L	16	TL	30	41.4	11.7	9.00	7390/6780@120	AMD9716
285/75R24.5	144/141L	14	TL	31	41.3	11.1	8.25	6175/5675@110	AMD9720



AP2000

A Premium Steer / All Position Tire engineered with a highly durable casing along with a strong belt carcass. The Low Rolling Resistance tread compound produces high mileage and fuel saving. SMARTWAY CERTIFICATION Pending.



Size	LI/SR	PR	TT/TL	TD	OD	SW	RIM Width Measure	Max Load	Stock #
8R19.5	124/122L	12	TL	19	33.8	8.0	6.00	3525/3305@110	AMD9008
10R22.5	141/139L	14	TL	19	40.1	10.0	7.50	5675/5355@115	AMD9011
11R22.5	146/143M	16	TL	20	41.4	10.8	8.25	6610/6005@120	AMD9010
215/75R17.5	126/124L	14	TL	16	30.6	8.9	6.00	3748/3527@105	AMD9000
215/75R17.5	128/126L	16	TL	16	30.6	8.9	6.00	3968/3748@110	AMD9001
215/75R17.5	135/133L	16	TL	16	30.6	8.9	6.00	4805/4540@110	AMD9002
235/75R17.5	143/141L	16	TL	18	31.4	9.2	6.75	6005/5675@127	AMD9006
225/70R19.5	128/126M	14	TL	16	31.9	8.9	6.75	3970/3750@110	AMD9005
245/70R19.5	135/133L	16	TL	18	33.0	9.8	7.50	4805/4540@120	AMD9007
265/70R19.5	140/138L	16	TL	18	34.4	10.3	7.50	5510/5205@120	AMD9009
295/80R22.5	150/147M	16	TL	21	41.5	11.4	9.00	7390/6780@120	AMD9022
315/80R22.5	154/151L	18	TL	22	42.7	12.5	9.00	8270/7610@120	AMD9025



MS4000

A Premium Mixed Service Radial with high durability and casing integrity. Excellent traction in On-Off Road applications. Engineered to run cool while providing abrasion and cut resistance.



Size	LI/SR	PR	TT/TL	TD	OD	SW	RIM Width Measure	Max Load	Stock #
7.50R16LT	122/121L	14	13.7	16	31.7	8.0	6.00	3305/3195@100	AMD9260
11R22.5	146/143L	16	31.7	21	41.7	11.2	8.25	6610/6005@120	AMD9210
11R24.5	149/146L	16	43.5	20	43.5	11.0	8.25	7160/6610@120	AMD9270
12R24.5	152/149K	16	44.7	22	44.7	11.8	9.00	7830/7160@120	AMD9280
11.00R24	154/151K	16	46.7	20	46.7	11.5	8.00	8270/7610@120	AMD9250
315/80R22.5	157/154L	20	42.4	22	42.4	12.3	9.00	9090/8270@130	AMD9221
385/65R22.5	160/-K	20	42.2	20	42.2	15.2	11.75	9920@130	AMD9230



ST1000

Designed and engineered for dependable and reliable service. The ST1000 is a shallow skid radial for trailers for short, regional and long haul transportation.



Size	LI/SR	PR	TT/TL	TD	OD	SW	RIM Width Measure	Max Load	Stock #
11R22.5	144/142M	14	TL	12	41.5	11.0	8.25	6175/5840@105	AMD9175
11R24.5	146/143L	14	TL	12	43.5	11.0	8.25	6610/6005@105	AMD9190
255/70R22.5	140/137M	16	TL	12	36.6	10.0	7.50	5510/5070@120	AMD9180
295/25T22.5	144/141L	14	TL	12	39.9	11.7	9.00	6175/5675@110	AMD9185
285/75R24.5	144/141L	14	TL	12	41.3	11.1	8.25	6175/5675@110	AMD9195

AMERICUS

americustire.com



PS2000

A Premium Steer Tire for All Applications. The Wide Grooves provide excellent water dispersion. The Tread Compound is Engineered for long mileage and low rolling resistance for improved fuel economy. SMARTWAY CERTIFICATION Pending.



Size	LI/SR	PR	TT/TL	TD	OD	SW		Max Load	Stock #
11R22.5	144/142L	14	TL	18	41.3	10.8	8.25	6175/5840@105	AMD9410
11R22.5	146/143L	16	TL	18	41.5	10.8	8.25	6610/6005@120	AMD9411
11R24.5	146/143L	14	TL	18	43.5	11.0	8.25	6610/6005@105	AMD9412
11R24.5	149/146L	16	TL	18	43.5	11.0	8.25	7160/6610@120	AMD9413
295/75R22.5	144/141L	14	TL	18	39.9	11.7	9.00	6175/5675@110	AMD9415
285/75R24.5	144/141L	14	TL	18	41.3	11.1	8.25	6175/5675@110	AMD9420
ST235/85R16	132/127L	14	TL	12	31.7	9.4	6.50	4400/3860@110	AMD9401



RS2000

A Regional All Position Steer Tire engineered for all road surfaces. The tread compound delivers excellent traction in all positions for confident reliable service.



Size	LI/SR	PR	TT/TL	TD	OD	SW	RIM Width Measure	Max Load	Stock #
11R22.5	144/142L	14	TL	16	41.4	11.1	8.25	6175/5840@105	AMD9610
11R24.5	146/143L	14	TL	16	43.4	11.1	8.25	6610/6005@105	AMD9611
255/70R22.5	140/137L	16	TL	16	36.6	10.0	7.50	5510/5070@120	AMD9612
295/75R22.5	144/141L	14	TL	16	39.9	11.7	9.00	6175/5675@110	AMD9615
285/75R24.5	144/141L	14	TL	16	41.5	11.1	8.25	6175/5675@110	AMD9620

Built For American Trucking

American Omni Trading Company

1221 Park West Green Dr. | Katy, TX 77493

Corporate Phone | 281-600-TIRE

american-omni.com



★AMERICUS