

CARLISLE®

SPECIALTY TIRE AND WHEEL CATALOG



WWW.CARLISLEBRANDTIRES.COM





WELCOME

To Our Valued Customers:

The Carlstar Group is proud to be your global partner for original equipment and aftermarket specialty tires and wheels. Our product offering spans a wide range of industries from the agriculture, construction, outdoor power equipment, powersports, high speed trailer and flat free/manual markets. The diverse portfolio of solutions are offered under several leading brands including Carlisle® tires and wheels, ITP® tires and wheels, as well as Cragar®, Black Rock® and Unique® wheels and Marastar® manual tires.

The Carlstar Group employs over 3,400 passionate professionals around the globe ready and willing to assist you. With 17 facilities located in 4 countries, we strive to ensure you receive the right products where and when you need them.

This edition of the Carlisle Brand Specialty Tire and Wheel Catalog affords easy access to the latest product information, technical specifications, tread designs and applications. Use these color guides to easily find the product that serves your specialty application.



The Carlstar Group has created a culture of converting great ideas into advanced products and a legacy of excellence in product innovation, quality, and customer service.

For additional information, please visit www.carlislebrandtires.com or contact your Carlstar Representative. We appreciate your continued partnership.

Trailer

ALL PURPOSE




RADIAL TRAIL® HD 34



ULTRA SPORT RH 34




SPORT TRAIL® 35



SPORT TRAIL® LH 36



USA TRAIL® 37



CSL 16 ALL STEEL 37







RADIAL TRAIL HD

ULTRA SPORT RH

BOAT, CARGO, HORSE AND LIVESTOCK, RV, TOWABLE UTILITY, AND SPECIALTY TRAILERS

RADIAL TRAIL® HD

The Radial Trail HD tire is designed with a unique tread pattern that wears evenly over time. As the superior trailer tire in the industry, the Radial Trail HD tire is constructed with heat resistant technology and compliant with DOT standards.

SIZE	PRODUCT CODE	LOAD RANGE	DIAMETER†	WIDTH†	RIM WIDTH	MAX CAPACITY	TIRE PSI*	TREAD DEPTH (32nds)	SPEED RATING
ST145/12**	5151311	LRD	21.4	5.9	4.00	1220	65	9	81
ST145/12**	5151321	LRE	21.4	6.0	4.00	1520	80	9	81
ST175/80R13	6H04511	LRC	24.1	7.0	5.00	1360	50	8	81
ST175/80R13	6H04521	LRD	24.1	7.0	5.00	1570	65	8	81
ST185/80R13	6H04531	LRC	24.7	7.2	5.00	1480	50	8	81
ST185/80R13	6H04541	LRD	24.7	7.2	5.00	1710	65	8	81
ST205/75R14	6H04551	LRC	26.1	7.8	5.50	1760	50	9	81
ST205/75R14	6H04561	LRD	26.1	7.8	5.50	2040	65	9	81
ST215/75R14	6H04571	LRC	26.7	8.3	6.00	1870	50	9	81
ST205/75R15	6H04581	LRC	27.1	7.8	5.50	1820	50	9	81
ST205/75R15	6H04591	LRD	27.1	7.8	5.50	2150	65	9	81
ST225/75R15	6H04601	LRC	28.3	8.6	6.00	2150	50	9	81
ST225/75R15	6H04611	LRD	28.3	8.6	6.00	2540	65	9	81
ST225/75R15	6H04621	LRE	28.1	8.8	6.00	2830	80	9	81
ST235/80R16	6H04631	LRE	30.8	9.0	6.00	3520-S/3080 -D	80	10	75
ST235/85R16	6H04641	LRE	31.7	9.3	6.00	3640-S/3200-D	80	12	75
ST235/85R16	6H04651	LRF	31.7	9.3	6.00	3960-S/3520-D	95	12	75

† Indicates mounted diameter and mounted width

*NOTE: Tire PSI shown is the Recommended PSI

**NOTE: Sizes with asterisks have the Radial Trail tread pattern. Made in the USA.

ULTRA SPORT RH

The Ultra Sport RH tire offers a low profile design with a high performance look. Its tire profile and tread formulation creates a lower rolling resistance ensuring stability on the road. Compliant with DOT standards.

SIZE	PRODUCT CODE	LOAD RANGE	DIAMETER†	WIDTH†	RIM WIDTH	MAX CAPACITY	TIRE PSI*	TREAD DEPTH (32nds)	SPEED RATING
ST235/60R15	6H00901	LRD	26.2	9.2	7.00	2200	65	10	65
ST235/60R14	6H00891	LRC	25.2	9.5	7.00	1820	50	16	65

*NOTE: Tire PSI shown is the Recommended PSI



BOAT, CARGO, HORSE AND LIVESTOCK, RV, TOWABLE UTILITY, AND SPECIALTY TRAILERS

SPORT TRAIL®

Sport Trail tire features a radial look with bias construction. The tread profile and formulation creates lower rolling resistance. Often used for towable utility and boat trailers, the Sport Trail tire is long-lasting for a safe travel.

SIZE	PRODUCT CODE	LOAD RANGE	DIAMETER†	WIDTH†	RIM WIDTH	MAX CAPACITY	TIRE PSI*	TREAD DEPTH (32nds)	SPEED RATING
4.80-8	5193171	LRB	16.3	4.7	3.80	585	60	8	62
4.80-8	5193181	LRC	16.3	4.9	3.80	760	90	8	62
5.70-8	5193191	LRB	18.1	5.9	3.80	715	50	10	62
5.70-8	5193201	LRC	18.4	6.0	3.80	910	75	10	62
16.5x6.5-8	5193421	LRB	16.6	6.8	5.40	615	45	7	62
16.5x6.5-8	5193461	LRC	16.5	6.8	5.40	785	70	7	62
16.5x6.5-8	5193481	LRD	16.6	6.8	5.40	910	90	7	62
18.5x8.5-8	5193431	LRB	18.0	8.6	7.00	760	35	10	62
18.5x8.5-8	5193451	LRC	17.9	8.6	7.00	935	50	10	62
20.5x8.0-10	5193441	LRB	20.9	8.0	6.00	910	35	10	62
20.5x8.0-10	5193471	LRC	20.9	8.0	6.00	1100	50	10	62
20.5x8.0-10	5193491	LRD	20.7	8.3	6.00	1320	70	10	62
20.5x8.0-10	5193501	LRE	20.6	8.2	6.00	1520	90	10	62
20.5x8.0-10	5193511	LRF	20.8	8.4	6.00	1650	105	10	62

† Indicates mounted diameter and mounted width

*NOTE: Tire PSI shown is the Recommended PSI


BOAT, CARGO, HORSE AND LIVESTOCK, RV, TOWABLE UTILITY, AND SPECIALTY TRAILERS
SPORT TRAIL® LH

Sport Trail LH tire brings an optimized tread pattern for larger bias trailer tires (>12" rim diameter). The tread and contour were designed to increase endurance, reduce heat build-up and maintain even wear for extended tread life.

SIZE	PRODUCT CODE	LOAD RANGE	DIAMETER†	WIDTH†	RIM WIDTH	MAX CAPACITY	TIRE PSI*	TREAD DEPTH (32nds)	SPEED RATING
4.80-12	6H01291	LRB	20.6	5.0	4.00	785	60	6	87
4.80-12	6H01301	LRC	20.6	5.0	4.00	990	90	6	87
5.30-12	6H01391	LRB	21.6	5.3	4.00	855	55	6	87
5.30-12	6H01381	LRC	21.6	5.3	4.00	1050	90	6	87
ST175/80D13	6H01581	LRB	24.0	6.9	4.50	1100	35	8	87
ST175/80D13	6H01361	LRC	24.0	6.9	4.50	1360	50	8	87
ST185/80D13	6H01371	LRC	24.4	7.1	4.50	1480	50	8	87
ST185/80D13	6H02231	LRD	24.4	7.1	4.50	1710	65	8	87
ST205/75D14	6H01351	LRC	25.8	7.9	5.50	1760	50	8	87
ST215/75D14	6H01421	LRC	26.7	8.4	6.00	1870	50	8	87
ST205/85D14.5	6H01451	LRF	27.8	8.0	6.00	2830-S/2470-D	95	9	87
ST205/75D15	6H01231	LRC	27.1	8.0	5.50	1820	50	8	87
ST205/90D15	6H01441	LRD	29.4	8.0	5.50	2600-S/2270-D	65	12	87
ST225/75D15	6H01401	LRC	28.3	8.6	6.00	2150	50	9	87
ST225/75D15	6H01411	LRD	28.3	8.6	6.00	2540	65	9	87
ST225/90D16	6H01431	LRE	31.8	8.7	6.00	3520-S/3080-D	80	12	87

† Indicates mounted diameter and mounted width *NOTE: Tire PSI shown is the Recommended PSI

USA TRAIL®

The USA Trail tire is built for long-lasting wear with its bias-ply construction. With rugged grooves to channel water in wet conditions, the USA Trail tire is compliant with DOT standards and made in the USA.

SIZE	PRODUCT CODE	LOAD RANGE	DIAMETER†	WIDTH†	RIM WIDTH	MAX CAPACITY	TIRE PSI*	TREAD DEPTH (32nds)	SPEED RATING
5.70-8***	519886	LRB	18.57	5.82	3.75	715	50	11	62
4.80-8	519056	LRB	17.1	5.1	3.80	585	60	6	62
4.80-8	519058	LRC	17.4	5.1	3.80	760	90	6	62
5.70-8	519086	LRB	19.2	6.0	3.80	715	50	10	62
5.70-8	519087	LRC	18.8	6.0	3.80	910	75	10	62
5.70-8	519088	LRD	18.9	6.1	3.80	1070	100	10	62
16.5x6.50-8 E4	519297	LRC	16.2	6.6	5.40	785	70	7	62
16.5x6.50-8 E4	519298	LRD	16.3	6.7	5.40	910	90	7	62
18.5x8.50-8	519471	LRB	18.0	8.4	7.00	760	35	10	62

† Indicates mounted diameter and mounted width *NOTE: Tire PSI shown is the Recommended PSI



USA TRAIL

CSL 16

BOAT, CARGO, HORSE AND LIVESTOCK, RV, TOWABLE UTILITY, AND SPECIALTY TRAILERS

USA TRAIL® (continued)

SIZE	PRODUCT CODE	LOAD RANGE	DIAMETER†	WIDTH†	RIM WIDTH	MAX CAPACITY	TIRE PSI*	TREAD DEPTH (32nds)	SPEED RATING
18.5x8.50-8	519472	LRC	17.7	8.5	7.00	935	50	10	62
6.90-9	519572	LRC	22.0	7.1	4.50	1100	60	10	62
20.5x8.00-10	519141	LRB	21.0	8.4	6.00	910	35	10	62
20.5x8.00-10	519142	LRC	20.7	8.5	6.00	1100	50	10	62
20.5x8.00-10	519143	LRD	20.5	8.6	6.00	1320	70	10	62
20.5x8.00-10	519144	LRE	20.9	8.7	6.00	1520	90	10	62
4.80-12	519062	LRB	21.0	5.0	4.00	785	60	8	62
4.80-12	519063	LRC	21.3	5.1	4.00	990	90	8	62
5.30-12	519076	LRB	21.8	5.3	4.00	855	55	8	62
5.30-12	519077	LRC	22.1	5.3	4.00	1050	80	8	87
ST175/80D13	519161	LRC	25.0	6.7	4.50	1360	50	10	65
ST195/75D14**	519307	LRD	24.6	7.2	5.50	1870	65	10	62
ST195/75D14**	519306	LRC	24.9	7.2	5.50	1610	50	10	62
ST205/75D14	519300	LRC	26.0	8.3	5.50	1760	50	10	65
ST215/75D14	519315	LRC	26.4	8.4	6.00	1870	50	10	65
ST205/75D15	519400	LRC	27.1	8.0	5.50	1820	50	10	65
ST225/75D15	519410	LRC	28.1	8.9	6.00	2150	50	10	65
ST225/75D15	519412	LRD	28.6	9.0	6.00	2540	65	10	65

† Indicates mounted diameter and mounted width

*NOTE: Tire PSI shown is the Recommended PSI

**NOTE: Sizes with asterisks have the Sure Trail tread pattern. Made in the USA.

***Note: Sizes with asterisks have the Extra Grip tread pattern.

CSL 16 ALL STEEL

The CSL 16 tire offers heavy duty hauling capabilities for large equipment and extremely heavy loads. Its all-steel body is essential for a load rating of up to 4,400 pounds of towing capacity. Its robust construction combined with an industrial highway tread design leads to extended service life on the highway and protects against environmental elements.

SIZE	PRODUCT CODE	LOAD RANGE	DIAMETER†	WIDTH†	RIM WIDTH	MAX CAPACITY	TIRE PSI*	TREAD DEPTH (32nds)	SPEED RATING
ST235/80R16	6H08101	G	30.6	9.2	6.50	4080/3640	110	12	81
ST235/85R16	6H08111	G	31.7	9.3	6.50	4400/3850	110	11.6	81



UNITED STATES

- Aiken, SC
- Clinton, TN
- Edwardsville, KS
- Kent, WA
- Fontana, CA
- Franklin (Nashville), TN
- Jackson, TN
- McDonough, GA
- Slinger, WI



Budapest, Hungary

Meizhou, China



Corporate Office

The Carlstar Group, LLC

725 Cool Springs Blvd.

Suite 500

Franklin, TN 37067

Tel: **+1 615-503-0220**

Email: **brand@carlstargroup.com**

© 2020 The Carlstar Group, LLC.

All rights reserved.

Revision 02/20. Part #CSL-L-2004

Customer Service:

USA

Tel: **+1 800-827-1001**

Email: **orders@carlstargroup.com**

Warranty Department:

Tel: **+1 800-260-7959**

Email: **customer.care@carlstargroup.com**

Canada

Waterloo Tel: **1(800)265-6155**

Edmonton Tel: **1(877)842-6275**

AUTHORIZED CARLSTAR DISTRIBUTOR

